ISSUE 187 NOVEMBER 2008

Better Homes and Gardens®

WOOD®

22 GREATEST SHOP TIPS EVER! p.62

Quick & Easy Nightstand

(and Matching Bed p.24)

plus

- Super-simple Router Table p.6
- Bow-front Display Case p.56
- Desk Clock p.74
- Fluting Jig for Routers p.16

- Precisely Cut Tapers Using Basic Jigs p.32
- Are "Hybrid" Saws a Good Buy? We Test 'Em! p.50
- Make *ANY* Tablesaw Cut Accurately, Cleanly p.40

p.36

Display until November 18, 2008
0 92567 14072 5
$6.99 U.S.



Grizzly Industrial®

Purveyors of Fine Machinery®

New! 10" Heavy-Duty Cabinet Table Saws *w/Riving Knife*

Perfect for cutting panels and wide stock!

- Motor: 3 HP, 220V, single-phase or 5 HP, 220V/440V*, 3-phase
- Precision ground cast iron table
- Table size w/extension: 27" x 75¾"
- Max. depth of cut: 3⅜" @ 90°, 2¼" @ 45°
- Arbor: ⅝"
- 52" rip capacity
- Approx. shipping weight: 514 lbs.

Riving Knife can be used with quick release guard!

EXTREME SERIES

*440V OPERATION REQUIRES PURCHASE OF ADDITIONAL COMPONENTS. CALL TECH. SERVICE FOR MORE INFO.

G0651 3 HP, single-phase
INTRODUCTORY PRICE $1695.00

G0652 5 HP, 3-phase
INTRODUCTORY PRICE $1695.00

Includes 10" Blade!
See it on Page 23 of the 2008 Catalog.

$139 Anywhere in Lower 48 States

New! Heavy-Duty 17" Extreme Bandsaw *w/ Cast Iron Wheels*

Only Grizzly offers these features for this price!

Cast Iron Wheels & Trunnion

MADE IN ISO 9001 FACTORY!

See it on Page 97 of the 2008 Catalog.

- Motor: 2 HP, 110V/220V, single-phase, TEFC
- Larger precision ground cast iron table size: 24" x 17"
- Table tilt: 5° left, 45° right
- Max. cutting height: 12"
- 2 blade speeds: 1700 & 3500 FPM
- Double ball bearing blade guides
- Quick change blade release/tensioner
- Approx. shipping weight: 414 lbs.

Includes Deluxe Re-saw Fence, Miter Gauge & ½" Blade

G0513X2
INTRODUCTORY PRICE $950.00

$89 Anywhere in Lower 48 States

12" Baby Drum Sander

- Sanding motor: 1½ HP, 110V, single-phase
- Conveyor motor: 1/10 HP, 110V, single-phase, variable speed 0-15 FPM
- Drum surface speed: 2300 FPM
- Max. stock dimensions: 12" wide x 3½" thick
- Min. stock length: 8"
- Sanding drum size: 4"
- Sanding belt: 3" hook & loop
- Approx. shipping weight: 160 lbs.

SIDE HANDLES FOR PORTABILITY!

2 ADJUSTABLE PRESSURE ROLLERS & INDUSTRIAL-DUTY BELT



G0459
ONLY $650.00

$69 Anywhere in Lower 48 States

10" Left-Tilting Table Saws *w/Cast Iron Router Table*

- Motor: 3 HP, 220V, single-phase or 5 HP, 220V, single-phase
- Precision ground cast iron table
- Table size w/wings attached: 27" x 48"
- Cutting capacity: 8" L, 26" R
- Approx. shipping weight: 500 lbs.

ROUTER AND WOOD NOT INCLUDED

G1023SLW
3 HP, single-phase
ONLY $1050.00

G1023SLWX
5 HP, single-phase
ONLY $1195.00

INCLUDES SHOP FOX® CLASSIC™ FENCE

$139 Anywhere in Lower 48 States

10" Left-Tilting Table Saw *w/7' Rails & Extension Table*

- Motor: 3 HP, 220V, single-phase
- Precision ground cast iron table
- Extension table size: 27" x 44"
- Arbor: ⅝" (accepts dado blades up to 13/16")
- Cutting capacity: 8" L, 54" R
- Max. depth of cut: 3" @ 90°, 2⅛" @ 45°
- Approx. shipping weight: 532 lbs.

54" Cutting Capacity!

INCLUDES SHOP FOX® CLASSIC™ FENCE & CAST IRON MITER GAUGE

WOOD MAGAZINE TOP VALUE APPROVED 2003

G1023SLX ONLY $1295.00

$139 Anywhere in Lower 48 States

19" Heavy-Duty Extreme Series® Bandsaw

- Motor: 3 HP, 220V, single-phase, TEFC
- Precision ground cast iron table
- Table size: 26¾" x 19" x 1½"
- Cutting capacity/throat: 18¼"
- Max. cutting height: 12"
- Blade size: 143" L (⅛" - 1¼" wide)
- 2 Blade speeds: 1700, 3500 FPM
- Approx. shipping weight: 458 lbs.

Includes Aluminum Re-saw Fence Attachment, Dual Ball Bearing Blade Guides, Cast Iron Wheels & Fence

MADE IN ISO 9001 FACTORY!

EXTREME SERIES

G0514X
ONLY $1150.00

$89 Anywhere in Lower 48 States

21" Super Heavy-Duty Bandsaws *w/Tilting Geared Table*

- Motor: 3 HP or 5 HP, 220V, single-phase
- Precision ground cast iron table
- Table size: 29½" x 20¾" x 1⅞"
- Table tilt: 5° L, 45° R
- Cutting capacity/throat: 20"
- Max. cutting height: 14"
- Blade size: 165" long (¼" - 1⅜")
- Blade speed: 4600 FPM
- Approx. shipping weight: 684 lbs.

Includes 1" Blade, Cast Iron Wheels & Fence

G0566 3 HP
ONLY $1850.00

G0531 5 HP
ONLY $1895.00

$169 Anywhere in Lower 48 States

Professional Spindle Shapers

- Motor: 5 HP, 220V, single-phase, TEFC or 7½ HP, 220V/440V*, 3-phase
- Precision ground cast iron table size: 35½" x 28"
- Spindle sizes: ¾", 1" & 1¼" x 7½"
- Spindle speeds: 3600, 5100, 8000 & 10,000 RPM
- Spindle travel: 3¼"
- Max. cutter dia.: 5⅞"
- Approx. shipping weight: 602 lbs.

EXTREME SERIES

5 HP, SINGLE-PHASE
G5912Z ONLY $2195.00

7½ HP, 3-PHASE
G7214Z ONLY $2195.00

Includes Fence & Cast Iron Miter Gauge

*440V OPERATION REQUIRES PURCHASE OF ADDITIONAL COMPONENTS. CALL TECH. SERVICE FOR MORE INFO.

$139 Anywhere in Lower 48 States

10052R4

PRICING CODE 08WOODM

MENTION THIS CODE WHEN PLACING YOUR ORDER

1-800-523-4777

TECHNICAL SERVICE: 570-546-9663 FAX: 800-438-5901

FULL YEAR WARRANTY GRIZZLY Power Tools & Machinery

BillMeLater VISA MasterCard AMERICAN EXPRESS DISCOVER

Providing Quality & Service for 25 Years!

BUY DIRECT & SAVE!

- OVER A MILLION SQUARE FEET PACKED TO THE RAFTERS WITH MACHINERY & TOOLS
- 2 OVERSEAS QUALITY CONTROL OFFICES STAFFED WITH QUALIFIED GRIZZLY ENGINEERS
- HUGE PARTS FACILITY WITH OVER 1 MILLION PARTS IN STOCK AT ALL TIMES
- TRAINED SERVICE TECHNICIANS AT ALL 3 LOCATIONS
- MOST ORDERS SHIPPED THE SAME DAY • 24 HOUR ORDERING BY PHONE OR ONLINE

GRIZZLY INDUSTRIAL, INC. 1983 25th ANNIVERSARY 2008 MO • PA • WA

New! 15" Planer w/Spiral Cutterhead

An unbeatable combination of stability, power, smoothness & mobility!

- Motor: 3 HP, 220V, single-phase
- Precision ground cast iron tables & extension wings
- Table size: 15" x 20"
- Max. cutting height: 8"
- Feed rate: 16 & 30 FPM
- Cutterhead speed: 5000 RPM
- 2 speed gearbox
- Magnetic safety switch
- Heavy-duty cast iron construction
- Approx. shipping weight: 675 lbs.

Foot Operated Built-in Mobile Base Provides Versatile Positioning

G0453Z
INTRODUCTORY PRICE $1295.00

$139 ANYWHERE IN LOWER 48 STATES

See it on Page 57 of the 2008 Catalog.

New! 8" Jointer w/Spiral Cutterhead!

Versatile parallelogram table adjustment system!

- Motor: 3 HP, 220V, single-phase, TEFC
- Precision ground cast iron tables
- Total table size: 8" x 76⅜"
- Infeed table size: 8" x 43⅜"
- 4 row spiral cutterhead
- Cutterhead speed: 5350 RPM
- Max. rabbeting depth: ½"
- Deluxe cast iron fence size: 35"L x 1¼"W x 5"H
- Approx. shipping weight: 597 lbs.

Extra Long Infeed Table & Extra Tall Fence

INCLUDES FREE SAFETY PUSH BLOCKS

EXTREME SERIES

G0490X
INTRODUCTORY PRICE $1075.00

$139 ANYWHERE IN LOWER 48 STATES

See it on Page 41 of the 2008 Catalog.

20" Planer

- Motor: 5 HP, 220V, single-phase
- Table size: 20" x 25¾" (20" x 55⅝" w/ extension)
- Max. cutting width: 20"
- Max. cutting height: 8"
- Min. stock length: 7½"
- Max. cutting depth: ⅛"
- Feed rate: 16 FPM & 20 FPM
- Cutterhead dia.: 3⅛"
- Knives: 4 HSS
- Cutterhead speed: 5000 RPM
- Approx. shipping weight: 920 lbs.

Precision Ground Cast Iron Bed & Infeed/Outfeed Tables

G0454 ONLY $1295.00

$169 ANYWHERE IN LOWER 48 STATES

20" Extreme Series® Planer w/Spiral Cutterhead

- Motor: 5 HP, 220V, single-phase
- Precision ground cast iron table size: 20" x 25¾" (20" x 55⅞" w/ extension)
- Max. depth of cut: ⅛"
- Max cutting height: 8⅝"
- Cutterhead speed: 4800 RPM
- Feed rate: 16 & 20 FPM
- Approx. shipping weight: 909 lbs.

EXTREME SERIES

MADE IN ISO 9001 FACTORY!

G1033X ONLY $2395.00

$169 ANYWHERE IN LOWER 48 STATES

24" Professional Planers

- Cutterhead motor: 5 HP, 220V, single-phase or 7½ HP, 220V/440V*, 3-phase
- Feed motor: 2 HP
- Precision ground cast iron table size: 24⅛" x 31⅛"
- Max. cutting depth: ⅛"
- Max cutting height: 8"
- Feed rate: 17-26 FPM
- Cutterhead speed: 5200 RPM
- Knives: 4 HSS
- Approx. shipping weight: 1130 lbs.

Z SERIES

Variable Feed Speeds & Lever Adjustable Feed Rollers

*440V OPERATION REQUIRES PURCHASE OF ADDITIONAL COMPONENTS. CALL TECH. SERVICE FOR MORE INFO.

5 HP, SINGLE-PHASE
G5851Z ONLY $3795.00

7½ HP, 220V/440V*, 3-PHASE
G7213Z ONLY $3795.00

$250 ANYWHERE IN LOWER 48 STATES

12" x 83½" Parallelogram Jointer

- Motor: 3 HP, 220V, single-phase
- Precision ground cast iron table size: 12¾" x 83½"
- Cutterhead knives: (4) 12" x ⅛" 19/64"
- Cutterhead dia.: 3¾"
- Cutterhead speed: 4950 RPM
- Max.depth of cut: ⅛"
- Max. rabbeting capacity: ¾"
- Approx. shipping wt: 1036 lbs.

INCLUDES FREE SAFETY PUSH BLOCKS

Handles Fold In For Added Safety

G0609
ONLY $1595.00

$250 ANYWHERE IN LOWER 48 STATES

10" Extreme Series® Jointers

- Motor: 3 HP, 220V, single-phase
- Precision ground cast iron table size: 11" x 84"
- Max. depth of cut: ⅛" • Rabbeting capacity: ½"
- Cutterhead speed: 5000 RPM
- Cutterhead dia.: 3⅛"
- Approx. shipping weight: 977 lbs.

Built Like a Tank w/ Heavy-Duty Cast Iron Base

4 BLADE CUTTERHEAD
G0455 ONLY $1695.00

SPIRAL CUTTERHEAD
G0480 ONLY $2095.00

$169 ANYWHERE IN LOWER 48 STATES

The Ultimate 12" Extreme Series® Jointers

- Motor: 3 HP, 220V, single-phase, TEFC
- Precision ground cast iron table size: 12½" x 80"
- Center mounted fence: 4¾" x 39¼"
- Max. depth of cut: 5/16" • Bevel jointing: 90° - 45°
- Cutterhead dia.: 4"
- Cutterhead speed: 5900 RPM
- Approx. shipping weight: 1253 lbs.

G9860 INCLUDES FREE H2404 JOINTER PAL® KNIFE SETTING JIG

EXTREME SERIES

MADE IN ISO 9001 FACTORY!

4 BLADE CUTTERHEAD
G9860 ONLY $3150.00

INCLUDES FREE SAFETY PUSH BLOCKS

SPIRAL CUTTERHEAD
G9860ZX ONLY $4150.00

$250 ANYWHERE IN LOWER 48 STATES

3 GREAT SHOWROOMS!
BELLINGHAM, WA
MUNCY, PA
SPRINGFIELD, MO

grizzly.com
OVER 12,000 PRODUCTS ONLINE!

FREE 2008 CATALOG!
700 FULL-COLOR PAGES OF HIGH QUALITY MACHINES, TOOLS & ACCESSORIES

in this issue

WOOD MAGAZINE SHOP TESTED APPROVED®

This seal is your assurance that we build every project, verify every fact, and test every reviewed tool in our workshop to guarantee your success and complete satisfaction.

PROJECTS

6 **Super-simple router table**
16 **Quick-and-easy fluting jig**
24 **Pencil-post bed**
36 **Cover project: Nightstand**
56 **Bow-front display case**
68 **Calendar frame**
74 **Deco desk clock**

TECHNIQUES

32 **Cut perfect tapers the first time**
Two easy-to-make jigs help you precisely taper workpieces from 8" to 80" long.

40 **Make *any* tablesaw a top performer**
Jigs and tricks make benchtop machines, and even hand-me-down saws, dead-on accurate.

62 **The 22 all-time best shop tips**

TOOLS & MATERIALS

18 **Buy the best bed-joint hardware**

50 **Tool test: Hybrid tablesaws**
These machines combine features of contractor- and cabinet-style saws. Is one right for you?

DEPARTMENTS

8 **Shop Tips**
78 **Ask *WOOD*.**
92 **What's Ahead**

on the web

woodmagazine.com

ONLINE INDEX HELPS FIND ANY *WOOD*® MAGAZINE ARTICLE FAST!

We've indexed every issue dating back nearly 25 years so you can instantly find the project, technique, or tool review you're looking for. Go to woodmagazine.com/index, or click on Article Index on the home page.



POST YOUR PRIDE AND JOY

Rob Rosano of Methuen, Mass., showed off these photos of his furniture-quality router table in the online photo gallery. Post photos of your own shop projects at woodmagazine.com/shopshots.



8 MINUTES TO SUPER-SIMPLE DRAWERS

That's all the time it takes to watch the free drawer-making seminar at woodmagazine.com/videos. Next time you're waiting for a glue-up to dry, pour a cup of coffee and watch this or other skill-building videos. It's like having *WOOD* magazine's experts in your shop.

OUR EDITORS WORK WOOD, TOO

Learn from them as they solve problems in their personal shops and share their solutions in blogs at woodmagazine.com/editorblogs. Or share your insights, photos, and projects-in-progress on your own blog. Discover how at woodmagazine.com/startablog.

INNOVATIVE PRODUCTS

SHOP FOX® is one of the fastest growing machinery lines in the country, offering an unbeatable combination of quality and affordability to all segments of the woodworking trade.

2 YEAR WARRANTY

We offer a 2 Year Warranty on all SHOP FOX® machines!

UNPARALLELED SERVICE HUGE SELECTION SUPERB QUALITY

SHOP FOX®

19" HEAVY-DUTY BANDSAW

MADE IN AN ISO 9001 FACTORY!

- 2 HP, 110V/220V, single-phase, TEFC motor
- 19" x 26¾" precision ground cast iron table
- Table tilt: 10° L, 45° R
- 2 blade speeds: 1700 & 3500 FPM
- Cutting height: 12"
- Cast iron wheels
- Quick release blade tensioning

Includes ⅝" blade, fence and miter gauge

W1729

2 HP, 10" CONTRACTOR TYPE TABLE SAWS

- 2 HP, 110V/220V, single-phase motor
- Heavy-duty cast iron extension wings
- SHOP FOX® Alumina-Classic® Fence
- Cast iron miter gauge w/adjustable stops
- Rip capacity w/standard rails: 28½"
- Arbor: ⅝" ➤ Blade tilt: 45°R

MADE IN AN ISO 9001 FACTORY!

*110V Operation Requires Additional Purchases

Includes both standard & dado inserts

W1714 Right Tilt

W1726 Left Tilt

8" JOINTER *w/Parallelogram Adjustable Beds*

- 3 HP, 220V, single-phase, TEFC motor
- Precision ground cast iron parallelogram design table measures 8" x 76⅝"
- 4 knife, 5350 RPM cutterhead
- Rabbeting capacity: ⅝"
- Quick adjust levers
- Large center mounted cast iron fence

Internal Magnetic Safety Switch w/Thermal Protection

W1741

Built-in Mobile Base

SHOP FOX®

2½ HP SHAPER

- 2½ HP, 220V, single-phase motor
- Precision ground cast iron table measures 28" x 30"
- Spindle travel: 3"
- 2 spindle speeds: 7000 & 10,000 RPM
- Includes ½" & ¾" spindles and ¼" & ½" router bit collets
- Convenient pedestal controls

New

Split adjustment fence & fully adjustable cutter guard

W1763

Built-in Mobile Base

1 HP POWER FEEDER

New

- 1 HP, 220V motor
- 4 feed speeds: 13, 26, 33 & 66 FPM
- Vert. movement: 9"
- Horiz. movement: 17"
- Max. roller height: 7"
- Forward & reverse rotation

W1767

MADE IN AN ISO 9001 FACTORY!

1 HP POWER FEEDER *w/4 Rollers*

New

- 1 HP, 220V, single-phase motor
- 4 feed speeds: 13, 26, 36 & 72 FPM
- Vert. movement: 9½"
- Horiz. movement: 24¼"

W1768

MADE IN AN ISO 9001 FACTORY!

20" PLANER *w/Spiral Cutterhead*

- 5 HP, 220V, single-phase, TEFC motor
- Precision ground cast iron table measures 20" x 25¾"
- 2 feed speeds: 18 & 23 FPM
- 4 row spiral cutterhead w/carbide inserts
- Cutterhead speed: 5500 RPM
- Heavy-duty cast iron construction

MADE IN AN ISO 9001 FACTORY!

Magnetic Safety Switch w/Thermal Overload Protection

W1718

SHOP FOX®

HEAVY-DUTY MORTISING MACHINE *w/Stand*

- 1½ HP, 110V/220V, single-phase, TEFC motor
- Table size: 19" x 12½"
- Head tilts ±30°
- X & Y table movement
- Chisel capacity: ¼" - 1"
- Accepts ⅝", & ¾" collars
- Solid cast iron construction

Steel Cabinet Stand w/Indexed Storage Shelf for Mortising Chisels

W1743

37" DUAL DRUM SANDERS

- 10 HP, 220V, single-phase or 15 HP, 220V/440V*, 3-phase sanding drum motor
- ¼ HP conveyor motor
- Drum diameter: 6"
- Industrial rubber conveyor belt
- Variable conveyor feed rate: 6 - 18 FPM
- Control panel with amp load meter
- Max. stock dimensions: 36½" wide x 4" thick

New

*440V Operation Requires Additional Purchases

State-of-the-art Computer Balanced Dual Drums

10 HP, Single-Phase **W1772**

15 HP, 3-Phase **W1773**

3 HP CYCLONE DUST COLLECTOR

New

- 3 HP, 220V, single-phase, TEFC Class "F" motor
- 8" intake hole
- 0.2 - 2 micron filters
- Magnetic switch w/remote control
- Noise reducing mufflers
- 55 gal. steel collection drum w/casters

Includes steel stand & detailed instruction manual

W1809

SHOP FOX® is a registered trademark of Woodstock International, Inc.

WOODSTOCK INTERNATIONAL INC.

VISIT OUR WEBSITE OR CALL TOLL FREE TO FIND AN AUTHORIZED DEALER NEAR YOU.

SHOPFOX.BIZ 1-800-840-8420

sales@shopfox.biz

WHOLESALE ONLY

10376

Better Homes and Gardens®
WOOD®
woodmagazine.com

November 2008 | **Vol. 25, No. 6** | **Issue No. 187**

We asked our staff:

What's the favorite piece of furniture you've ever built?

My rendition of the Greene and Greene Ford house server in mahogany with ebony buttons and splines.

The first serious furniture project I built: a cherry crib for my son from *WOOD* magazine plans.

The window seat and bookcases in my wife's studio.

EDITOR-IN-CHIEF
BILL KRIER

Managing Editor **MARLEN KEMMET**
Deputy Editor **DAVE CAMPBELL**
Art Director **KARL EHLERS**
Senior Design Editor **KEVIN BOYLE**
Techniques Editor **BOB WILSON**
Tool & Techniques Editor **BOB HUNTER**
Multimedia Editor **LUCAS PETERS**
Multimedia Editor **CRAIG RUEGSEGGER**
Design Editor **JEFF MERTZ**
Projects Editor **LARRY JOHNSTON**
Associate Art Director **GREG SELLERS**
Assistant Art Director **CHERYL A. CIBULA**
Production/Office Manager **MARGARET CLOSNER**
Administrative Assistant **SHERYL MUNYON**

Photographers
MARTY BALDWIN, JASON DONNELLY, DEAN SCHOEPPNER, JAY WILDE
Contributing Illustrators **TIM CAHILL, LORNA JOHNSON, ROXANNE LeMOINE**
Technical Consultants **JEFF HALL, BRIAN SIMMONS**
Contributing Craftsman **JIM HEAVEY**
Contributing Proofreaders **BABS KLEIN, IRA LACHER, JIM SANDERS**

SUBSCRIBER SERVICE
Go to woodmagazine.com/help or write to
WOOD magazine, P.O. Box 37439, Boone, IA 50037-0439

Publisher **MARK L. HAGEN**

ADVERTISING AND MARKETING
CHICAGO: 333 N. Michigan Ave., Suite 1500, Chicago, IL 60601
Marketing Manager **AMANDA SALHOOT**
Advertising Manager **JACK CHRISTIANSEN**
Account Executive **RYAN INTERLAND**
Direct Response Advertising Representative **LISA GREENWOOD**
Assistants **GAYLE CHEJN, NIA WILLIAMS**
ATLANTA: Navigate Media
DETROIT: RPM Associates

Business Manager **JEFF STILES**
Associate Consumer Marketing Director **DAN HOLLAND**
Associate Director of Marketing-Newsstand **TOM DEERING**
Production Manager **SANDY WILLIAMS**
Advertising Operations Manager **JIM NELSON**
E-Commerce Manager **MATT SNYDER**

Vice President/Group Publisher **TOM DAVIS**

MEREDITH PUBLISHING GROUP
President **JACK GRIFFIN**
Executive Vice President **DOUG OLSON**
Chief Revenue Officer **TOM HARDY**
Finance & Administration **MIKE RIGGS**
Manufacturing **BRUCE HESTON**
Consumer Marketing **DAVID BALL**
Corporate Sales **MICHAEL BROWNSTEIN**
Meredith 360° **JACK BAMBERGER**
Interactive Media **LAUREN WIENER**
Corporate Marketing **NANCY WEBER**
Research **BRITTA WARE**
Chief Technology Officer **TINA STEIL**
New Media Marketing Services **ANDY WILSON**

Meredith Corporation

President and Chief Executive Officer **STEPHEN M. LACY**
Chairman of the Board **WILLIAM T. KERR**

In Memoriam — E.T. Meredith III (1933–2003)

Our subscribers list is occasionally made available to carefully selected firms whose products may be of interest to you. If you prefer not to receive information from these companies by mail or by phone, please let us know. Send your request along with your mailing label to Magazine Customer Service, P.O. Box 37452, Des Moines, IA 50037-0452.

© Copyright Meredith Corporation 2008. All rights reserved. Printed in the U.S.A.
Retail Sales
Retailers can order copies of WOOD for resale
by e-mailing jennifer.buser@meredith.com

Premium Quality
ZAR
Oil-Based
Wood Stain
110
Salem Maple
WHEN THE SAWDUST SETTLES...
ZAR® finishes on top!
Whether you're creating your own masterpiece or want to give new life to a treasured family heirloom, only the best wood stain will do. ZAR Wood Stain's controlled penetration formula allows you to work at your own pace. ZAR Wood Stain wipes on easily and penetrates evenly for uniform color tone without streaks, lapmarks or blotches. So whether you're a professional or just want professional looking results - use ZAR Wood Stains and Clear Finishes.
You control the stain, It doesn't control you!
Before
After
ZAR Wood Stain
Before
After
Other Wood Stain
For a free brochure and the name of your nearest dealer call 1-800-272-3235, or visit us online at ugl.com.
Circle No. 128
UGL
UNITED GILSONITE LABORATORIES
P.O. BOX 70, SCRANTON, PA 18501 • JACKSONVILLE, IL • JACKSON, MS • DAYTON, NV

Portable Router Table

Here's your low-cost ticket to accurate, convenient, and safe table-mounted routing.



Note: All stock ¾" medium-density fiberboard or birch plywood

You can spend a grand or more on a full-featured router table, but this super-simple version helps you tackle most of the same jobs for just a few bucks. You need only a quarter-sheet of ¾" MDF or plywood and a few hours of shop time.

With this table, you can work without fear of a handheld router tipping on a narrow edge, rout profiles without a bearing-guided bit, and handle tricky jobs, such as routing grooves into workpiece ends.

To make one, first cut all of its parts to size. At the center of the base along its length, measure 5" from one edge. Visually center your router subbase there, and mark mounting-hole centers **[Photo A]**. Using a straightedge, draw connecting lines between the hole centers to form a triangle. Now draw a line from one corner to the center of the opposite side, splitting the triangle **[Photo B]**. Repeat for the other corners and sides. The lines intersect at the precise router subbase center.

Using a Forstner bit, drill a 1½" hole at the intersection of the lines. Then drill countersunk holes for machine screws that fit your router base. (The ones that come with your router will be too short, so buy screws ¾" longer than the originals.) Now glue and screw the parts together to form the base and fence. Mount your router (without the subbase) on the underside, lay the table on two sawhorses, clamp the fence in position, and you're ready to rout.

Project design: **Jeff Mertz**
Illustration: **Roxanne LeMoine**



Draw a line at the base-length center. Then rough-position the base 5" from the edge and mark the base mounting-hole centers.



Draw a line between each triangle corner and its opposite side center to mark where to drill the router bit opening.

What's The Secret To Flawless Edge Profiles With NO REWORK?

Quadra-Cut™



Freud's New Quadra-Cut™ 4 Cutter Design

How It Works!

Two large cutter wings shear upward to remove most of the stock for fast, extremely smooth cuts.



Two small cutter wings shear downward for an ultra-fine finish, even when routing crossgrain in delicate materials!



U.S. Patent No. 8,899,252

For A Smooth Sanded Finish... ...Without The Rework!



"Mirror-smooth finish with sharp, clean details!"
– Chris Marshall, Woodworker's Journal

"Super-smooth cuts!"
– Glen Huey, Popular Woodworking

Look For These Popular Profiles in 1/2" Shank Quadra-Cut™ Design:

- Classical Cove & Round Bit
- Rounding Over Bit, 3/8" Radius
- Rounding Over Bit, 1/2" Radius
- Rounding Over Bit, 1" Radius
- Beading Bit, 5/16" Radius
- Beading Bit, 1-1/8" Radius
- Table Top Classical Bold Bit
- Table Edge Bit
- Rounding Over Bit, 5/8" Radius
- Rounding Over Bit, 1-1/2" Radius
- Raised Panel Bits

Another Industry 1st By Freud

Non-Stick Perma-SHIELD Coating

Titanium Tiplo Hi-Density Carbide freud

freud®
Precisely the best

To sign up for Freud's e-mail newsletter or to find a dealer near you visit: www.freudtools.com

Red router bits are a registered trademark of Freud America, Inc. (US) 7-800-472-7307

Shop Tips

Helping you work faster, smarter, and safer

Two lines are better than one for cutting accurately

No matter how old or young, the first time we cut wood on the bandsaw, we learn to follow a single cutline, staying to one side of it. So it runs against our nature to accept that two parallel lines drawn on the workpiece are better than one. I'm not sure why shooting for the gap—1/16" is plenty—between the lines is easier, but since I started using this technique, I rarely let the blade wander over the line as I saw. Ironically, by giving myself more room for error, I get even closer to the perfect curved cut. To create the two lines, I simply freehand a line parallel to the original cutline. Go ahead and try it; I'll bet it'll work for you, too.

—Warren Perkins, Millington, Mich.



Diminutive clamps for delicate glue-ups

I make small, decorative boxes to hold coin and stamp collections, so I frequently have to edge-glue wood as thin as 3/16". My larger clamps aren't suited to this delicate process, so I made the clamps you see here.

The threaded rod and wing nuts give me fine control that lets me carefully control the pressure. I keep small scrapwood clamping cauls and C-clamps on hand. If the workpiece starts to bow as I apply pressure, I simply clamp the cauls on top with a backer board beneath, separating them from the workpiece with waxed paper.

—Merlin Lafferty, Sebring, Fla.





continued on page 10

The Top Tipster

Photo: Stelick Photography

To craft the intricate parts for his wooden model tractors, trucks, and trains, retired die-maker Warren Perkins needs a steady hand and a sharp eye. And it also doesn't hurt that his elegant Top Shop Tip gives him an edge at the bandsaw.

Warren Perkins earns a Craftsman 12" compound mitersaw for sending this issue's Top Shop Tip. Way to go, Warren!

Top tips earn tools!

Tell us how you've solved a workshop stumper. If we print it, you'll get $100 and a copy of *450+ Best-Ever Shop Tips* (woodmagazine.com/450tips). And, if your idea garners Top Shop Tip honors, we'll also reward you with a tool prize worth at least $300.

Send your best ideas, along with photos or drawings and your daytime phone number, to: **Shop Tips, WOOD Magazine, 1716 Locust St., LS-221, Des Moines, IA 50309-3023**. Or, by e-mail: shoptips@woodmagazine.com. Include your contact info in the e-mail.

Because we try to publish original tips, please send your tips only to *WOOD®* magazine. Sorry, submitted materials can't be returned.

STRENGTH. REBORN.

Introducing the NEW family of JET® Bandsaws featuring:

TRIANGULAR STABILITY CONTROL

TSC™

Exclusively by JET®

The ALL-NEW JET® TSC Bandsaws are designed with a Triangular frame to provide superior column rigidity that enables precision sawing >> The first pure performance based line of bandsaws built exclusively for the serious woodworker >> 3-position quick tension blade release >> 2-speed poly v-belt drive >> Up to 12-1/4" resaw capacity for cutting large pieces of wood, slicing veneers and cutting book matched panels >> Micro adjustable upper and lower ball bearing blade guides >> **Visit your local quality JET dealer for more information.**



20" 18" 16"

JET®

www.jettools.com/TSC

QUALITY | INNOVATION | SERVICE

©2008 WMH Tool Group, Inc. The color WHITE is a registered trademark of WMH Tool Group, Inc.

Circle No. 1588

freud®

OPEN THE DOOR TO ITALY

WOOD MAGAZINE

Interior Door Contest

Build an Interior Door & Enter to Win a FREE Trip for 2 to Italy by Freud

Contest Runs:

Sept 15 '08 - Jan 15 '09

For More Details Go To:

www.WOODMagazine.com/Door

Subject to Official Rules at www.woodmagazine.com/door. No purchase necessary to enter or win. To enter, visit www.woodmagazine.com/door for the entry form, and e-mail the completed entry form and up to five (5) pictures of an interior door that you have built/created that highlights routing techniques to doors@woodmagazine.com. The door must be created by the entrant using his/her own equipment. Entry photos must be taken by the entrant, non-professional, unpublished and may not have won any prize or award. Freud's Door to Italy Contest begins 9/15/08 and ends 1/15/09. Entries must be received by 11:59 p.m., E.T. on 1/15/09. Open to legal residents of the 50 United States, and the District of Columbia, 21 years or older. One entry per household. Void where prohibited. Sponsor: Meredith Corporation

Shop Tips

Project plans ready for the big screen

Like most people, I have trouble finding space on the workbench for all the plans, parts, and tools required for a project. To get my plans out of the way but still keep them accessible, I hung a 48" retracting window shade from a ceiling joist. I tape the plans to the shade and, when I need them, they are only a "pull" away. The shade not only stores the plans and provides easy viewing, it preserves them from the usual wear and tear that takes place in the workshop.

—Don Loeffler, Menomonee Falls, Wis.



Roll out a just-right-height temporary table

It's always a time-consuming exercise to get a support table to match the height of my workstation when I need extra space. A single roller stand fulfills the height adjustability requirement, but it tends to be unstable for stationary work. But two roller stands, and a plywood tabletop with channels to fit over the rollers, provides just the right solution. Build the top as shown, and you have a temporary adjustable-height table anytime you need the extra workspace.

—Allan Rice, Winnipeg, Man.





continued on page 12

How Do You Create Beautiful, Customized Doors with any Wood Species?

Win A FREE Trip For Two To Italy!
Contest Runs Sept. 15 to Jan. 15
www.woodmagazine/door.com
for more details

Rail Bit

For Making Extended Tenon Cuts

NEW Freud Innovation
Simply remove the top cutter to produce extended tenons of virtually any length for extra strong, long lasting joints.



This Same Rail Bit allows for Stub & Extended Tenons

Stile Bit

For Stile Cuts

Rail Bit

For Making Stub Tenon Cuts on Rails

Raised Panel Bit

For Making Raised Panel Cuts

With Freud's New Entry & Interior Door Router Bit Sets!

Now you Can Create Beautiful, Customized Doors with Strong Joints.

Imagine the Possibilities...

Thanks to Freud's patented innovation, you now have the ability to make door joints with precisely fit tenons of any length. Use the bits right out of the box for high quality stub tenons, or by simply removing the top of the Rail bit, create extended tenons (for stronger joints) at all four critical corners of your door. Combine with Freud's flawless Stile bit design, even add Freud's award winning **Quadra Cut™** Raised Panel Door bits, you can create unique interior doors with any design or wood species. These router bits come set up for 1-3/4" height (for entry doors) and can easily be adjust for 1-3/8" height (for interior doors).

Instructional DVD Included

Two Piece Bit Sets Available:
- Roundover Profile (#99-267)
- Ogee Profile (#98-268)
- Cove & Bead Profile (#98-269)

Three Piece Bit Sets Available:
- Roundover Profile with Bevel Raise Panel Bit (#98-300)
- Roundover Profile with Cove Raised Panel Bit (#98-302)

Premium TiCo Hi-Density Carbide by freud

Non-Stick Perma-SHIELD Coating

Another Industry 1st by Freud

freud®
Precisely the best.

Red router bits are a registered trademark of Freud America, Inc.

ISO 9001 VISION 2000

1-800-334-4107 **www.freudtools.com**

Ready for the next level?

Berea Brand Pen Kits!

- High Quality
- Original Designs
- Reasonably Priced

Visit us at www.bereahardwoods.com or call or e-mail us at 1-877-736-5487 or bereahard@aol.com

BereaHardWoods Co. Inc.
18745 Sheldon Rd • Middleburg Hts., OH 44130

Circle No. 2127

PROUD OF WHAT YOU MAKE?

US, TOO.

Introducing

WORK SHARP
The Wood Tool Sharpener

NEW from the makers of Drill Doctor

Cutting Edge Technology for Woodworkers

Take a look at our latest project. It's the result of years of work, listening to woodworkers like you, and then building the wood tool sharpener that you wanted. Take a tour of the features and see what you think:

150mm Tempered Glass Grinding Wheel— provides an always flat and true, maintenance-free grinding surface on which to adhere PSA Abrasives

580 rpm wheel speed— Powerful 1/5 HP Motor

Sharpening Port Lapping Surface— "plunge-pull" sharpening technique and Sharpening Port abrasive increases burr removal and speeds sharpening

Sharpening Port— enables precise and repeatable angles of 20°, 25°, 30°, and 35° for chisels and plane irons up to 2" wide

Dry Cooling System— routed airflow and heat sink system keeps tools cool without the mess of a wet system

5-STAR BEST RATING WOOD MAGAZINE 2007

AWFS 2007 WINNER SEQUOIA AWARDS

Innovative Edge-Vision™ Slotted Wheel lets you see the cutting edge as you sharpen!

TWO FULL 2 YEAR WARRANTY

Learn more about the award-winning Work Sharp at
www.worksharptools.com
or call 1-800-597-6170

Ask for it at Sears, Rockler, Woodcraft, and wherever you buy your tools.

Circle No. 1665

Shop Tips

Outrigger steadies your trim router

As a wheelchair-bound woodworker, I have to find novel ways to work efficiently in the shop. Holding a trim router steadily at arm's length was a challenge until I came up with the subbase you see here. Made out of ¼" clear acrylic, I added a ¼×3½" carriage bolt that serves as a stabilizing outrigger. I double-face-tape my workpiece down to a flat surface and adjust the height of the bolt, enabling me to rout it with no wobble at all.

—Edwin Frampton, Clarksboro, N.J.



Small tools stay put in magnetic sticky pockets

I like to keep a small steel rule, a punch, and other useful items handy in my shop apron pocket. But they frequently fall out when I bend over to pick something off the floor. I solved this problem by duct-taping a ⅜"-diameter rare-earth magnet on the back of my apron, behind the pocket. Now all of my metal odds and ends stay securely tucked in my pocket, but not so securely that they aren't easy to retrieve when I need them.

—Andy Newhouse, Syracuse, N.Y.



Large-capacity bowl press on a low-capacity budget

Commercial presses cost beaucoup bucks. So I came up with this low-dough version for gluing up segmented turnings. It consists of three pieces of ¾×12×12" plywood that ride on ⅜" threaded rod. Nuts and washers hold the top and bottom pieces in place, and the middle piece acts as the press. I simply turn the T-knobs to apply pressure. Even large bowls aren't a problem for this press because one rod detaches to allow easy access.

—John Hoffmann, Lancaster, N.Y.



continued on page 14

Sawdust. It invades your workshop, threatening to take over. But with **CleanStream Pro Filters** on your side, sawdust doesn't stand a chance. CleanStream adds true HEPA filtration to your wet/dry vac. So no matter what kind of dust you're sucking up, 99.97% of even the finest particles, down to 0.3 microns, are kept out of the air. CleanStream won't clog, and it lasts longer than any other filter out there. We even have a one-year guarantee to prove it. Declare victory over sawdust today. With CleanStream. ***www.cleanstream.com***

Cleanstream and GORE are registered trademarks of W.L. Gore & Associates, Inc. © 2008 W.L. Gore & Associates, Inc.

Available at: The Home Depot, Sears, Lowe's, Menards

Circle No. 2124

BESSEY® INVENTED THE ORIGINAL PARALLEL CLAMP...
NOW THE BEST IS EVEN BETTER!



Introducing the NEW K Body® REVO™

Built bigger, better and stronger for woodworkers who want the best!

The industry leading parallel clamp just got better. Introducing the most powerful parallel clamp you can buy, the K Body® REVO™. We took the best features of the classic K Body®, a favorite among serious woodworkers for over 30 years, and added many upgrades and features to create the revolutionary K Body® REVO™. The REVO™ offers a 30% increase in clamping surface, 1500 lbs. of clamping force, a larger comfort grip handle, precise parallel clamping and the ability to quickly convert to a spreader. BESSEY®. Simply better®.

BESSEY® Tools North America • 1.800.828.1004 • www.besseytools.com

Circle No. 745

Built to Last A Lifetime.

"Holy '----'! This is what made in the U.S.A. used to be... solid... well-built... and man, does it pull dust! Thank you for a great product!"

J.H. - Michigan

Oneida has won every tool test to date in dust collection.

2006 American Woodworker Editors' Pick

Proudly Made in the USA with USA Components.

- Motors made in Arkansas
- Fan Wheels made in PA
- Filters made in Ohio...

Super Gorilla Series 1.5, 2, 3, and New 5hp

Ductwork Design Service

Oneida Air Systems

Now Available in Europe. See Web for Distributor.

Call Today for FREE Catalog!

1.800.732.4065

Order Online!

www.oneida-air.com

Circle No. 2039

Shop Tips

Workbench expansion gives you a leg up

I was building a corner cabinet when I realized my workbench wasn't quite wide enough for the project. To solve the problem, I enlisted my bench vise to create a temporary workbench addition, as shown.

The extension top is a separate, compact table that's quickly but firmly held in place by the vise. To install it, I first use the bench vise to align the surface of the extension flush with the benchtop. Then I use the leg leveler to firmly position the rest of the extension and take some of the pressure off the vise.

—Dave Wywial, Janesville, Wis.



Find more free plans for your shop at woodmagazine.com/freeplans

4-WAY MONEY MAKER

MOLDS • PLANES • SANDS • SAWS

- **Shape 3 sides per pass!**
- **Choose from 500+ Patterns!**
- **RISK FREE 30-Day Trial Offer!**

Highest Profit: MAKE CURVED MOLDING!

Now, turn a $5.00 rough board into $75.00 worth of high-dollar molding in just minutes. Make over 500 standard patterns, curved molding, tongue & groove, picture frame stock, any custom design. QUICKLY CONVERTS from Molder/Planer to Drum Sander or power-feed Multi-Blade Ripsaw. Made in U.S.A. 5-Year Warranty. Choose from 12", 18" or 25" models.

Variable Feed Makes the Difference!

Just a twist of the dial adjusts the Woodmaster from 70 to over 1,000 cuts per inch. Produces a glass-smooth finish on tricky grain patterns no other planer can handle. Plenty of American-made "muscle" to handle money-saving, "straight-from-the-sawmill" lumber. Ideal for high-value curved molding.

Custom Woodworker has Competitive Edge Thanks to Woodmaster

"Woodmaster really changed the way I do woodworking. It set my career in the right direction. Making curved molding with the Woodmaster really separates me from my competition – it's like a PhD in woodworking."

– Gary Striegler, President, Striegler & Associates Custom Homebuilders

WATCH Gary Striegler make curved molding: visit www.woodmastertools.com

NEW!

SHAPE 3 SIDES IN 1 PASS!

NEW 3-Side Molding System turns your Woodmaster into a POWERFUL 3-SIDE MOLDER that efficiently & AFFORDABLY cuts T&G flooring, paneling, much more!

HURRY! CALL NOW FOR YOUR FREE DVD & BUSINESS STARTER KIT!

CALL TODAY and we'll RUSH you our new Woodmaster DVD & Business Plan! You'll learn exactly how to start & operate a profitable molding business! Includes business plan, instructive DVD, full specs, prices, LIMITED-TIME SAVINGS OFFER, and info on easy financing.

CALL TOLL FREE 1-800-821-6651 Ext. P340

Woodmaster Tools, Inc. Dept. P340, 1431 N. Topping Ave., Kansas City, MO 64120 · www.woodmastertools.com



FREE DVD!

Call Toll-Free 1-800-821-6651 Ext. P340

The Woodmaster Molder/Planer is a MOLDING FACTORY!

Quick-Change Molding Head lets you create custom molding from any stock. Choose from over 500 standard trim and picture frame patterns...or design your own!

Commercial-Duty Thickness Planer features infinitely variable feed rate. Use higher speeds for fast stock removal... slow down to get over 1,000 cuts per inch for fine finish passes.



Power-Feed Drum Sander saves hours of tedious hand sanding. Speeds production, improves quality. No more waves or cross grain scratches.

New Ripsaw Attachment lets you gang rip with power feed in a fraction of the time it takes for hand-fed passes on an ordinary table saw.

Quick & Easy Jig

Right-on-the-money Fluting Jig

Mount your router to this simple-to-build jig, and guide it arrow-straight down the workpiece to rout flutes with dead-on precision. Build the jig shown, drilling mounting holes in the base to attach to your router base. Then, mark a centerline across the jig top and bottom directly under the centerpoint of the router collet. Extend the centerline up the front edge of the base.

To machine flutes, first mark the flute centerlines on your workpiece. Then, align the centerline on the jig's front edge with one of the flute locations, and slide the guides snugly against the edges of the workpiece, allowing just enough free play for the jig to slide without wobble. Tighten the knobs, set the bit's cutting depth, and rout the flute. If the second flute is the same distance from the opposite edge of the workpiece as the first flute, simply rotate the jig 180° and rout from the opposite end.



Project design: **Angelo Varisco, Coral Springs, Fla.**

Find dozens of FREE project plans at woodmagazine.com/freeplans

TODAY I DISCOVERED **NEW GORILLA WOOD GLUE**

IS TOUGH ENOUGH FOR EVERY WOODWORKING JOB AND THAT A PERFECT DOVETAIL JOINT CAN MAKE A GROWN MAN CRY



FOR THE TOUGHEST JOBS ON PLANET EARTH.™

1-800-966-3458 • GORILLATOUGH.COM

© 2008 Gorilla Glue Company WGFW01

Circle No. 50

Make Your Bed Movable

3 rock-solid bed-rail options that will let you rest easy.

Beds occupy more floor space than any furniture you'll build. So when moving day comes, you'll appreciate these handy hardware options for taking them apart.

To assemble the pencil-post bed on *page 24*, we used bed bolts that unscrew to detach the rails, headboard, and footboard from the posts. If this assembly loosens from wear or wood movement, simply rotate the decorative bold covers, and tighten the bolts to snug the joints good as new.

Not every furniture style works with bed bolts, though, so we offer these three great alternatives to match your bed design or woodworking skills. We won't tackle step-by-step installation instructions because bed-part sizes vary, but we will equip you with the basics.

1 A simple, solid solution: Tabbed bed-rail brackets

The easiest to install of these three, brackets come in sets of mating pairs **[Photo A]**. Each set includes enough hardware to assemble one bed.

+ Advantages: There's no mortising required; each bracket surface-mounts with four screws, as shown *above*. That makes it easy to center rails on the thickness of the posts. At $8 per set, they're the most economical choice.

– Disadvantages: All hardware can be seen from the top and inside. Rails can separate from the headboard or footboard when lifting the bed.

■ Installation basics: Separate the brackets into interlocking pairs, and each pair into right or left brackets. Drill and screw one bracket from a right pair and one from a left pair centered on the rail height and flush with the rail end. Then with the bracket pairs interlocked, place each rail where desired on the headboard or footboard posts or legs, and mark the bracket-hole locations. Drill and screw the mating brackets to the headboard or footboard.

BRACKETS WORK IN PAIRS

A

Tabbed bed-rail-bracket sets come with two left and right pairs 3¾" or 5¹¹⁄₁₆" (*shown*) long.

continued on page 20

A STEADY PASS
REVEALS MORE THAN
THE CHARACTER OF THE WOOD.
THE CHARACTER OF THE MAN.
CRAFTSMAN
PROFESSIONAL
VibraFree is a TM used under license from Positec Group Ltd.

Introducing the exclusive **Craftsman Professional VibraFree® Sander** – where comfort meets control. State-of-the-art Vibration Canceling Technology™ eliminates more than half the vibration of a standard sander. A unique Cyclonic Dust Separator™ allows for 40% better dust removal and a new, ergonomically designed handgrip was made to fit comfortably in your palm, giving you the steady hand needed to bring out the best in your project. And in you. For tools and advice from America's Most Trusted Tool Brand, visit the Garage of Knowledge™ at craftsman.com

© 2008 Sears Brands, LLC

THERE'S A CRAFTSMAN IN ALL OF US

2 Hook-and-slot fasteners require mortises

Once you learn to rout the shallow mortises to accept the hardware shown **[Photo B]**, you'll appreciate the inconspicuous strength of these fasteners. You'll also find these handy for assembling other knock-down furniture, such as bookcases, where you want concealed fasteners.

HOOKS LOCK INTO SLOTS



B

Working in pairs, these hook-and-slot fasteners both mount inside mortises and disappear on an assembled bed.

+ Advantages: Once assembled, fasteners are hidden for the look of a mortise-and-tenon joint. You'll spend only $11 for a set to build one bed.

– Disadvantages: Mortising the bedposts and rail ends takes time, even with jigs. Half of these mortises must be deepened in places to accept the hooks.

■ Installation basics: To cut the ⅝×5" mortises, first make post and rail-end mortising jigs similar to the one for the bed lock/hook fasteners (*page 22*), but with the opening bounded on four sides and sized for your project.

Attach the indexing cleat to the bottom of the post-mortising jig to center or offset the hardware. To mortise a post, clamp the jig with the opening where you want the slotted bracket. (Remember to index from the same corner on each post.) Set a dado clean-out bit for the jig thickness plus bracket thickness combined, and rout a mortise **[Photo C]**. Remove the jig, and square the corners with a chisel. To provide clearance for the rail-bracket hooks, use a ⅜" bit to drill out portions of the mortise ½" deep **[Photo D]**. Drill pilot holes, and then screw the bracket to the post using the longest screws that fit the post thickness **[Photo E]**.

To mortise the rails, center the mortising jig opening on the rail end, allowing at least 3/16" from the rail edges and faces. Clamp this jig to the rail end, and rout the mortise as you did with the bedpost. Square the corners with a chisel. Now drill ⅜" holes ⅛" deep in the mortise to accept the protrusions on the back side of the hook bracket.

To give the bracket mounting screws better grip than in end grain alone, drill the bottom rail edge to accept a ½" dowel, as shown at *right*. Glue the dowel in place, and trim it flush with the bottom edge of the rail. Now drill 11/32" pilot holes, and attach the bracket with #8×1½" flathead wood screws. Index the jig from the same face or edge, and repeat on the other rail end. Then do the same for the other rail.

ROUT MORTISES FOR HARDWARE



With the jig clamped to a post, rout the initial mortise using a dado clean-out bit inside the jig opening. Size the jig opening to fit the fastener width and length.

DRILL FOR HOOK CLEARANCE



Drill ⅜" holes to provide clearance for hooks on the mating fastener to pass through the post-mounted fastener slots.

INSERT HARDWARE INTO MORTISE



Attach slotted fasteners to posts using #8×1¼" flathead wood screws. For the rail-mounted hook hardware, use #8×1½" screws.

BED-RAIL-END BRACKET



continued on page 22

WITH EACH PRECISE CUT,
A MAN BUILDS MORE
THAN JUST A PROJECT.
HIS REPUTATION.
Introducing the exclusive **Craftsman 10" Laser Table Saw**. The innovative portable saw that combines a riving knife designed to prevent kickback with a unique laser that projects an accurate pre-cut line, and puts them both on the largest table surface in its class, giving you the support and control you need to make the right cut, the first time. Every time. And making sure that no piece of wood, or your good name, is ever at risk again. For tools and advice from America's Most Trusted Tool Brand, visit the Garage of Knowledge™ at craftsman.com
CRAFTSMAN
craftsman.com
© 2008 Sears Brands, LLC
THERE'S A CRAFTSMAN IN ALL OF US

3 Bed lock/hook hardware requires a single mortise

To install these, rout one shallow mortise, and the L-shaped bed lock mounts flush with one bedpost face—far easier than cutting a slot and drilling the post for metal pins to accept the bed hooks.

+ Advantages: Integral metal pins in the bed locks, shown [**Photo F**], avoid potential alignment problems from drilling pin holes into the post. The bed lock holds the hooks at 90° angles for a square bed frame.

– Disadvantages: Bed rails must be at least 1⅛" thick to hide the mortised portion of the bedlock; the rest of the hardware remains exposed. Rails cannot be centered without adjusting the post or rail thickness to accommodate the hardware. At $15.60, four bed locks and hooks cost the most of these three options.

■ Installation basics: To rout consistent mortises, make the jig shown *right*. Position the opening in the jig where you want the mortise, and rout a 1/16" mortise using a dado clean-out bit. Square the rounded mortise corners with a chisel. Drill and screw the bed lock in place. Insert a bed hook into the bed lock, and mark the bed-hook mounting hole positions on the rails. Drill and screw the bed hook to the rail. Then repeat for the three other bed locks and hooks.



F

BED LOCKS HOLD THE BED-RAIL-MOUNTED HOOKS

Bed hooks, on the left, attach to two pins inside the bed locks. Rails must be at least 1⅛" thick to conceal the portion of the bed locks mortised into the posts.

MORTISING JIG



Sources

Bed rail brackets. Four 5¹¹/₁₆" pairs, no. 94K01.01, $7.90, Lee Valley Tools, 800-871-8158, or leevalley.com.

Dado clean-out router bit. No. 102-0802B ½" diameter, ¼" cutting length, $20, Eagle America, 800-872-2511, or eagleamerica.com.

Hook-and-slot fasteners. No. 127456, $11.50 for four sets, Woodcraft, 800-225-1153, or woodcraft.com.

Bed locks and bed hooks. Bed lock no. 01S02.01, $11.50 for four. Bed hooks no. 01S02.07, $4.10 for four, Lee Valley Tools.

Are you buying the best?
INNOVATIVE
Unique fully integrated soft grip handle
"Jorgensen" ISD
18" BAR/SPREADER CLAMP
SUPERIOR
40% More Clamping Force than 500QC series QUICK-GRIP Bar Clamps*
DEPENDABLE
Value Priced Clamps for over 100 years
Bar/Spreader Clamp
"Jorgensen" ISD®
Adjustable Clamp Co. Chicago, IL 60622
www.adjustableclamp.com
* When tested using the same input force. Quick-Grip is a registered trademark of Irwin Industrial Tool Company.
Circle No. 733

ROCKLER®
WOODWORKING AND HARDWARE
Create with Confidence™

Rockler's Exclusive Table Saw Crosscut Sled - 33113

Perfect Accuracy Every Time

When the margin for error is miniscule, a woodworker's tools take on a new level of importance. With an oversized protractor scale and simple micro-adjustability, the Rockler Crosscut Sled delivers perfect accuracy every time, so that even in unforgiving situations, you can always expect the best—another way Rockler helps you ***Create with Confidence.***

Rockler Woodworking and Hardware - Since 1954

For a store near you or free catalog visit Rockler.com | 1-877-ROCKLER

Circle No. 661

Easy
Tapered Legs!
See the article on page 32
Build it with or
without the canopy!

Pencil-Post Bed

Slender tapered bedposts give the pencil-post bed its name. Topped with a canopy—called a "tester"—this beauty fits many decorating styles.

The clean, elegant lines of this cherry four-poster bed, influenced by Shaker designs, make it a beauty to behold and build. Despite its size, you won't have any trouble getting it up stairs or around corners into the bedroom; it disassembles with ease. The bed is part of a matching set that includes a nightstand, a dresser with valet and mirror, and a lingerie chest, shown in the photo *below*.

Start with the posts

1 Laminate cherry blanks for the four bedposts (A). Start with a 1¾×6½×84" board for each post, and book-match the blank. To do that, joint one edge of the board, rip it to 6⅛" wide, and plane it to 1½" thick. Rip the board in half, and fold the two halves together [**Photo A**]. Glue and clamp the blanks, keeping the ends and edges flush.

2 Joint and plane the blanks to 2¾" square, then cut them to length for the bedposts (A) [**Materials List**, *page 31*]. Save one of the cutoff pieces to make a jig later. Mark each bedpost on the bottom for its final position (LH for left-side head, for example).

PROJECT HIGHLIGHTS

- Overall dimensions: 84½" long × 64½" wide × 83¾" high.
- Materials needed: cherry; maple would be appropriate, too.
- Frame holds a queen-size mattress.
- Build it with or without the top canopy frame.
- Bed assembles and disassembles for easy moving.

Skill Builders

- Find out about book-matching stock.
- Discover how to taper long parts.
- Learn how to bandsaw compound-curved finials.


Find plans for the lingerie chest in issue 189.
Find plans for the dresser, valet, and mirror in issue 188.
See page 36 for plans.



BOOK-MATCH THE BEDPOSTS

After ripping, bring together the faces that were on the same side of the board. This book-matching helps hide the joint.



MORTISE TOWARD THE MIDDLE

Start at the ends when you form the mortises, then drill out the middle. Use the depth stop on the drill press for uniformity.



BORE THE BED-BOLT HOLES

Drill through the center of each counterbore into the mortises in the bedposts (A) with a ½" brad-point bit.



CENTER A HOLE ON THE TOP

With the centering jig, drill into the top of each bedpost (A). Masking tape on the drill bit serves as a visual stop for the hole depth.

1 BEDPOSTS



3 On all four bedposts (A), lay out the 6" mortise locations for the side rails and end rails (B, C) along with the centerpoints for the ⅞" counterbores and ½" through holes [**Drawing 1**].

4 On the bedposts for the head of the bed, also lay out the 2" mortises for the headboard (F) [**Drawing 1**]. Place the bedposts side by side and lay out the mortises at the same time for accuracy. Differences in mortise location or length will lead to a lot of fitting when you assemble the bedposts and headboard.

5 Form the headboard (F) mortises in two bedposts (A) with a ¾" Forstner bit and drill press [**Drawing 1, Photo B**]. Support the long leg with a work stand for easier, more accurate drilling. Clean and straighten the mortise sides with a chisel, but leave the corners round to match the tenons on the headboard.

6 Using the same procedure, drill the mortises for the side rails and end rails (B, C) in all four posts (A) [**Drawing 1**]. Clean the mortise sides with a chisel, and square the corners.

7 Drill the ⅞" counterbores with a Forstner bit, then center a ½" hole through the bedpost (A) in each counterbore [**Drawing 1, Photo C**].

8 Cut a 2"-long block from the saved bedpost cutoff to make a centering jig. To do this, first make sure both ends are square to the sides. With a drill press, drill a ½" hole centered on the end of the block. Glue cleats to two opposite sides for clamping. (We made cleats measuring ¾×2×8" from scrapwood.)

SHOP TIP

An easy way to cut stopped chamfers

A simple shop-made gauge helps you set stops for routed chamfers quickly and accurately. To make one, set up your router with a 45° piloted chamfer bit. Then, rout a chamfer 3" to 4" along the edge of a piece of scrapwood, marking the edge of the router base on the piece at your starting point.

To set a stop with the gauge, place the end of the chamfer on your test piece against the endpoint of the chamfer on the workpiece. Transfer the router-edge mark to the workpiece; clamp the stop there.



2 RAIL TENON DETAIL



9 Clamp the jig to the top of each bedpost (A) as a guide, then drill a ½" hole ¾" deep in each post [**Drawing 1, Photo D**].

Taper the bedposts

1 Construct the tapering jig shown on *page 34*. (You'll use the same jig to saw the long tapers and short tapers.)

2 Mark the center on the bottom of each bedpost (A) [**Photo E**]. Drill a 7/64" pilot hole 1½" deep at each center.

3 Install the short-taper bracket on the tapering jig. Set up the jig on your tablesaw, referring to the instructions in the article beginning on *page 32*.

4 Attach a bedpost (A) to the tapering jig, and cut the short tapers on all four sides at the bottom [**Drawing 1, Photo F**]. Repeat for the other bedposts.

5 Change to the long-taper bracket on the jig. Attach a bedpost (A) and cut the long tapers [**Photo G**]. Be sure the bedpost is square to the blade and the jig before starting each cut. Repeat for the remaining bedposts.

6 Lay out the endpoints of the chamfers on the bedposts (A) [**Drawing 1**]. Chuck a piloted 45° chamfer bit into a handheld router, and rout the stopped chamfers along the edges of the bedposts [**Photo H**]. For an easy way to set a stop, see the **Shop Tip** *top*.

7 Sand the tapered faces to remove saw marks. Then, finish-sand the bedposts to 220 grit.

Ready the rails

1 Cut the side rails (B) and end rails (C) to size.



E MAKE YOUR MARK

Clamp the centering jig to the bottom of the bedpost (A). Insert a ½" brad-point bit, and tap the end of the bit with a mallet.

F SAW THE SHORT TAPERS FIRST

The short-taper bracket holds the bottom of the bedpost (A) farther from the jig than the long-taper bracket.

G START LONG TAPERS AT TOP

Position work supports in front of and behind the tablesaw when cutting the long tapers on the bedposts.



H CHAMFER THE BEDPOSTS

A trim router is convenient for forming chamfers on the bedposts (A). Set a stop for accurate, consistent chamfer lengths.

CUT TENONS ON A TABLESAW

To cut tenons on the rails (B, C) using the tablesaw, set up a work support and install a long extension on the miter gauge.



FINISH WITH SHOULDER CUTS

With an auxiliary fence and ¾" dado set, you can set tenon length precisely by measuring from the fence face to the outside blade.

DRILL TRUE WITH A DOWELING JIG

A doweling jig helps keep the holes in the ends of the rails (B, C) perpendicular to the ends, necessary for the bed bolts to line up.



MARK THE TENONS

Align the end of the headboard with the middle of the mortises in the bedpost (A). Mark the mortise locations on the blank.

2 Form tenons on both ends of the rails (B, C) [**Drawing 2**]. We cut the tenon cheeks with a tablesaw and dado blade [**Photo I**], then turned the rails on edge to cut the shoulders, using the same setup [**Photo J**]. Chamfer the top edges and tenon ends [**Drawings 2, 3**].

3 Lay out the ⅝" hole centerpoints on the inside faces of the rails (B, C) [**Drawing 2**]. Install a ⅝" Forstner bit in your drill press, and set the depth stop to bore 1 1/16" deep. Bore a test hole in scrap material the same thickness as the rails. If the point of the bit breaks through the face, reset the stop to bore a shallower hole. Then you can sand or file the end of the barrel nut to align the threaded hole with the bolt when you assemble the bed. Bore the holes, supporting the rail ends with a work stand.

4 Lay out the centers for the ½" holes on the ends of the rail (B, C) tenons [**Drawing 2**]. Drill the holes perpendicular to the rail ends [**Photo K**].

5 Cut the slat cleats (D) to size. Drill and countersink shank holes in the cleats [**Drawing 3**]. (For #8 screws, drill 5/32" shank holes and 7/64" pilot holes.) Glue and clamp the cleats to the side rails (B), centered end to end. Drill pilot holes, and drive the screws.

6 Cut the slats (E) to size, and round over the edges [**Drawing 3**]. Finish-sand the side rails (B/D), end rails (C), and slats to 220 grit.

Shape the headboard

1 Edge-glue stock to make a ¾×16½×61" blank for the headboard (F).

2 Dry-assemble and clamp the bedposts (A) and end rail (C) that will make up the head of the bed. Measure the distance between the bedposts *inside* the headboard mortises. Cut the blank for the headboard (F) to this length.

3 Disassemble the bedposts (A) and end rail (C). Lay one bedpost on your workbench and position the headboard blank (F) with its bottom edge aligned with the bottom edge of the lower headboard mortise [**Photo L**]. Mark the top and bottom of both mortises on the headboard blank. Repeat for the other end of the headboard.

4 Enlarge the **Headboard Half-Size End Pattern** in the *WOOD Patterns®* insert to make a full-size pattern. Using that pattern and the gridded headboard pattern, lay out the headboard (F) on your blank. Make sure the tenons on the end match the mortises on your posts; adjust the tenons as necessary. After you lay out the ends, mark the center of the headboard, and draw the curve along the top with a fairing stick [**Photo M**]. (To download a free fairing stick plan, go to woodmagazine.com/fairing.)

5 Bandsaw the headboard (F) to shape, cutting slightly outside the lines. Sand to the lines.

6 Round over the edges of the headboard (F) with a 5/16" round-over bit in a handheld router.

7 Finish-sand the headboard (F). Sand the tenons to fit the mortises, allowing some clearance so they slide in and out of the mortises easily for assembly and disassembly.

Assemble the bed

1 Lay one head-end bedpost (A) on a workbench, with the mortise for the side rail (B) facing up. Insert the tenons on the headboard (F) into the mortises in the bedpost [**Drawing 3**].

2 Lay an end rail (C) in position, with the inside facing up. Drop a barrel nut into the hole in the inside face of the end rail. Insert a ⅜×5" hexhead bolt into the hole in the tenon, and try to thread it into the barrel nut. If the threads do not line up, remove the barrel nut, and sand or file the inside end until it drops far enough into the hole to start the bolt. Don't try to drill the cross holes in the rails deeper; that risks breaking through the rail.

3 Slide the tenon on the end rail (C) into the mortise in the bedpost (A) [**Drawing 3**]. Insert a bed bolt through the hole in the bedpost and thread it into the barrel nut in the end rail [**Drawing 5**, **Photo N**]. If you have trouble pushing the bolt as you turn it to get it started, see the **Shop Tip** on the *opposite page*.

4 Attach the other head-end bedpost (A) to the end rail (C). Assemble the foot-end bedposts and end rail the same way [**Drawing 3**].

5 Stand the assembled ends (A/C/F and A/C) with the mortises for the side rails (B) facing each other [**Drawing 3**]. Attach the ends to the side rails with bolts, as you did the end rails (C).



SHOP TIP

Starting bolts goes quickly with a dowel in a socket

A dowel rod inside a deep-well socket makes easy work of starting a bolt inside a counterbore. Slide a dowel into the socket and mark the socket depth on it, shown *below*. Then subtract the thickness of the bolt head, shown *below right*. Cut the dowel to that length and drop it into the socket. With the packed socket, you can push the bolt inward as you turn it, for easier starting.



M

LAY OUT THE HEADBOARD

Lay out the curve from the end pattern to the center of the headboard (F). Apply masking tape along the top for easier layout.



N

BOLT THE BED TOGETHER

Put a washer onto the bed bolt, then insert the bolt through the bedpost (A) into the barrel nut. Tighten with a socket wrench.







BANDSAW THE FINIALS

Guide the blank with the dowel handle for better control when bandsawing the finials (I). Saw slightly outside the line (*top*) to cut both patterned faces. After the first cut, sand to the line before reattaching the cut-off pieces for the final cut (*bottom*).



Top it off with a tester

1 Cut the tester side rails (G) and tester cross rails (H) to size.

2 Lay out the rabbets and dadoes on the tester side rails (G) [**Drawing 4**]. Cut them in several passes on a tablesaw with a ¾" dado blade set to cut ¼" deep. You can cut both side rails together.

3 Cut the rabbets on the ends of the tester cross rails (H). You can use the same setup you did for rabbeting the side rails (G), except change the cutting depth to ½".

4 Dry-assemble the four corner joints (G, H) and drill a ½" hole through the center of each joint [**Drawing 4a**].

5 Drill and countersink shank holes at the ends of the remaining two tester cross rails (H) [**Drawing 4**]. Lay the cross rails in position on the side rails (G) and drill pilot holes ⅜" deep. Be careful not to drill through the rails. Finish-sand the side rails (G) and cross rails (H).

6 Cut ½" dowels 2" long [**Drawing 4a**] and insert them into the holes in the tops of the bedposts (A). Lay the tester side rails (G) over the dowels. Install the tester cross rails (H), securing the middle two with screws [**Drawing 4**].

Fashion the finials

1 Cut blanks for the finials (I) ⅛" longer than listed.

2 Drill a ½" hole ¾" deep, centered on the bottom of each blank. Cut a length of ½" dowel rod about 6" long; you'll use this as a handle to saw and sand the finials to shape.

3 Make eight copies of the **Finial Full-size Pattern** in the *WOOD Patterns*® insert. Attach patterns to two adjacent sides of each finial (I) blank. Align the bottom of the pattern with the bottom of the blank (the end with the hole). Insert the dowel handle into one hole.

4 Bandsaw the first face [**Photo O**]. Then, reattach the cut-off pieces with double-faced tape, and saw the pattern line on the taped-on pieces [**Photo P**]. Sand round-overs along the bottom.

5 POST DETAIL



Materials List

Part		FINISHED SIZE T	W	L	Matl.	Qty.
A*	bedposts	2¾"	2¾"	80"	LC	4
B	side rails	1¼"	6½"	79⅞"	C	2
C	end rails	1¼"	6½"	59⅞"	C	2
D	slat cleats	¾"	1"	78½"	C	2
E	slats	¾"	2½"	60½"	C	4
F*	headboard	¾"	15"	60½"	EC	1
G	tester side rails	¾"	1½"	83¼"	C	2
H	tester cross rails	¾"	1½"	63¼"	C	4
I*	finials	1½"	1½"	3"	C	4

*Parts initially cut oversize. See the instructions.

Materials key: C–cherry, EC–edge-glued cherry, LC–laminated cherry.
Supplies: #8×⅝", 1½" flathead wood screws, ½" dowels.
Blade and bits: Chamfer bit, ⅛" round-over bit, rabbeting bit, dado set.

Source

Bed bolts, covers: Set of four 5" hexhead bolts, washers, and brass barrel nuts, no. 05G1701, $13.50 (order two sets); brass bed-bolt covers with screws, Classic style, no. 00A2814, $3.05, (order eight). Lee Valley, 800-871-8158, leevalley.com.

5 Finish-sand the finial (I). Remove the dowel handle and place the finial over the dowel on top of one bedpost (A). Repeat for the other three finials.

It's about time for bed

1 Disassemble the bed for finishing. If you sanded any of the barrel nuts so the bolts would line up, mark their positions. Inspect all parts and touch-up sand as necessary.

2 Stain as desired. (We stained the bed parts with Minwax no. 607 Cherrywood gel stain to enhance the color of the cherry.)

3 Apply a clear finish. (We applied three coats of satin polyurethane, sanding with 320-grit between coats.)

4 Reassemble the bed, and attach decorative covers over the bed-bolt holes in the bedposts (A) [**Drawing 5**], using the screws provided.

Written by **Larry Johnston** with **Chuck Hedlund**
Project design: **Kevin Boyle**
Illustrations: **Roxanne LeMoine**; **Lorna Johnson**

Cutting Diagram


A
1¾ x 6½ x 84" Cherry (8.2 bd. ft.) (4 needed)
B
I
1½ x 7¼ x 96" Cherry (10.7 bd. ft.) (2 needed)
*Plane or resaw to thickness listed in the Materials List.
C
1½ x 7¼ x 60" Cherry (6.7 bd. ft.) (2 needed)
E
D
¾ x 5½ x 96" Cherry (4 bd. ft.)
E
H
¾ x 7¼ x 96" Cherry (5.3 bd. ft.)
E
G
¾ x 7¼ x 96" Cherry (5.3 bd. ft.)
F
¾ x 7¼ x 72" Cherry (4 bd. ft.) (3 needed)
H
¾ x 5½ x 72" Cherry (3 bd. ft.)

2 Techniques for Fast, Accurate Tapers

With these two jigs, you can rip tapers on anything from a footstool leg to a tall bedpost.

When it's time to taper furniture legs, an adjustable jig will handle 90 percent of those jobs. But that other pesky 10 percent—such as the 80" posts for the pencil-post bed on *page 24*—can give you fits. By tailoring a tapering jig to your workpiece though, you'll get consistent results, regardless of its length.

To cut accurate tapers, first make sure your tablesaw fence parallels the blade and the blade aligns 90° to the saw table. A 24-tooth ripping blade helps prevent burn marks. Also, joint and plane all four faces of your workpieces square so they'll index accurately on the jigs. Ready? Let's tackle that 90 percent first.

Build an adjustable jig to handle day-to-day needs

This adjustable tapering jig, **Drawing 1**, holds table or cabinet legs shorter than 34" and up to about 2¼" thick. Build the base by cutting grooves in ¾" birch plywood and gluing ¼" hardboard to the top to form slots. Make the two movable hold-downs and the pivot block from scraps of hardwood and plywood. (To find the jig hardware, see **Sources**.)

To taper two adjoining faces of a leg blank, first mark the tapers on the sides of the leg [**Photos A** and **B**]. Capture the base between the blade and rip fence, and adjust the fence out just a hair to prevent the jig from touching the saw blade. Then set the blade higher than the combined thickness of the jig base and the leg blank.

1a PIVOT BLOCK DETAIL



1 ADJUSTABLE TAPERING JIG



PLAN YOUR SEQUENCE OF TAPERING CUTS TO KEEP A FLAT EDGE AGAINST THE JIG



A

Positioning the workpiece as shown *above* ensures a flat face will rest on the base and against the hold-downs for the second tapering cut.



B

Cutting the first of two tapers on the leg edge shown *above* would place a tapered edge against the jig base for the second cut.



The hold-down block helps position the workpiece on the jig while the clamp holds it for cutting. Use the end of the jig to align workpieces consistently.



The top surface of the jig acts as a backer board to reduce splintering as you cut tapers. This setup allows you to taper two adjoining sides of the workpiece.



To set the pivot screw height, raise or lower the screw until it can be inserted into the leg center hole with the leg blank flat on the jig. Then tighten it in position.

Lay the blank on the jig, aligning the taper marks with the edge of the jig closest to the blade [**Photo A** and **B**]. Make the nontapered workpiece end flush with the trailing end of the jig [**Photo C**]. Slide the hold-down blocks against the workpiece to act as stops, and tighten them down using the nylon nuts. Then secure the blank to the jig with the clamps.

Start the saw, and slide the jig tightly against the fence as you cut the first taper [**Photo D**]. Then rotate the workpiece 90°, and make the second cut.

To taper all four sides of a leg, you must reference from the center of the workpiece because after two cuts, you no longer have square faces to work from. Start by laying out the tapers on the four leg faces. Then mark the center and diagonal lines between the corners. At that mark, drill a ¼" hole ½" deep. Next place the pivot block into a slot at one end of the jig [**Photo E**], and set the pivot-block screw height to align with the centered hole at the end of the leg.

Align the taper line with the edge of the jig as before, and then secure the workpiece using the hold-down blocks and clamps. After cutting the first taper, loosen the clamps, rotate the workpiece 90°, and reinsert the pivot block screw. Make the second cut, and repeat for the remaining two tapers.

Super-size a custom tapering jig for long posts

You could lengthen the adjustable jig to hold almost any size workpiece—even the four 80"-long, 2¾"-thick posts of the pencil-post bed on *page 24*. But you'd seldom need that capacity, and the jig would be cumbersome to use and impossible to store. You're better off tailoring a jig to taper large blanks.

Start by jointing and planing a 2×6 that's about 16" longer than your workpiece to 1¼×5". (We've sized the jig shown for the pencil-post bedposts.) From hardwood or ¾" plywood, make and attach a saddle that captures your tablesaw fence [**Drawing 2**].

The bedposts have two tapers—short ones at their feet and long ones at their tops—requiring separate brackets for the short and long tapers. You'll need a third, front-pivot bracket, too.

From ¾" plywood, cut, glue, and screw together the three brackets, as shown. Mark the pivot-dowel or screw location on each bracket at a distance above the saw table that's half the thickness of the workpiece (1⅜" for the 2¾" square bedpost). The front-pivot dowel should position the workpiece to provide 1" of clearance from the fence guide. Mount the front-pivot bracket flush with the bottom edge of the fence guide, and place the jig on your tablesaw.

2 SUPER-SIZE TAPERING JIG



POSTS PIVOT ON A DOWEL



To save time, use a dowel instead of a screw to pivot the front of the workpiece. Both the short and long brackets on the opposite end keep the post from pulling free.

BRACKETS POSITION POSTS

Mount the short-taper bracket to the tapering-jig fence guide so the long bracket leg fits tight against the workpiece end. The pivot screw holds it in place.

CUT THE SHORT TAPERS FIRST

When cutting short tapers, the square portion of the bedpost rests flat on the saw table. Note that the post was mortised and drilled before tapering.

To tailor the short- and long-taper brackets for the workpiece tapers you want, first mark taper lines on your workpiece. Drill a ½" hole centered in the end of the workpiece; then place the front-pivot bracket dowel in that hole [**Photo F**]. Slide the other workpiece end until the marked taper line parallels the fence guide. Measure from the center of the workpiece end to the fence guide, and drill the end for the pivot screw at that distance. Now screw that bracket to the fence guide to provide a snug fit for the workpiece.

Start with the short tapers

Attach the short-taper bracket to the fence guide, and then screw the leg to the bracket [**Photo G**]. To help control the jig, position infeed and outfeed supports in front and back of your tablesaw.

By tapering the foot of the post first, those tapers provide clearance later for long cuts using the long-taper bracket. Cut the first taper for the foot of the post [**Photo H**]. Then remove the screw, rotate the workpiece 90°, and reinsert the pivot screw. Make the second taper, followed by two more to complete the bedpost foot. Repeat for the remaining posts.

Tackle long tapers

To cut the long tapers, first replace the short-taper bracket with the long-taper bracket. Screw the foot end of the post to the bracket [**Photo I**].

Now move the fence to align the workpiece taper lines with the blade, and add both an infeed and outfeed support. Cut the first taper [**Photo J**], and then rotate the workpiece 90°, keeping an untapered edge against the saw table for the next taper. Repeat for one additional taper, and rotate the workpiece again for the final pass.

INSTALL A LONG-TAPER BRACKET



Cutting the short tapers first allows the post to ride close to the fence guide when cutting long tapers using the smaller bracket.

For the final taper, you no longer have a workpiece edge flat against the saw table. That can allow the workpiece to spin between the centers at the start of the taper when the square section no longer rests on the saw table. To keep the workpiece flat and reduce vibration, double-face-tape a cutoff wedge to the underside of the workpiece to re-create a flat surface flush with the bottom edge of the jig [**Photo K**]. Remount the jig on your fence, and cut the final taper.

Then find a home in your shop for this jig. By customizing the brackets, you can use it again for the oversize tapered parts on your next project.

Sources

Hold-down. Kreg Trak Clamp with bolt and knob, #145831, $5, Woodcraft, 800-225-1153 or woodcraft.com.
Four-arm knob. With through hole and ¼"-20 insert, #142230, $2, Woodcraft.

Written by **Bob Wilson** with **Chuck Hedlund**
Illustrated by **Roxanne LeMoine; Lorna Johnson**

JIG SUPPORTS PREVENT TIPPING



Because of the length of the jig and parts, good infeed and outfeed supports are critical when cutting the long tapers. We used a workbench for infeed support and a table for outfeed support to stabilize the jig and workpiece when cutting long tapers.

STABILIZE THE WORKPIECE

Before cutting the final taper, double-face tape a cutoff wedge to the workpiece flush to the bottom jig edge. This stops the workpiece from rotating as it's cut.

Easy-to-make-and-fit drawers
See *page 38*.

Don't sweat the tapered legs
See *page 32*.

Pretty, Practical Nightstand

Tapered legs lend this nightstand a lithe look, and two generous drawers make it a practical bedside table. Build it on its own or as a companion to the pencil-post bed (*page 24*).

PROJECT HIGHLIGHTS

- Overall dimensions are 23" wide × 19½" deep × 26¾" high.
- Materials needed: Cherry, birch plywood.

Skill Builders

- Learn how to taper two adjacent sides of a leg.
- Build a case with wide mortise-and-tenon joints.

The perfect complement to the pencil-post bed (*page 24*), this nightstand is both beautiful and easy to build. For a complete bedroom suite, plan to build the dresser with valet and mirror in issue 188 (December 2008/January 2009) and the lingerie chest in issue 189 (March 2009).

Start with the legs

1 Cut the legs (A) to size [**Materials List**, *page 39*]. (We used solid stock, but you could laminate two ¾"-thick boards for the legs.)

2 Lay out the mortises on the legs (A) [**Drawing 1**]. The front legs differ from the back ones; lay out two of each.

3 Form the mortises with a mortising machine or by drilling a series of ¼" holes with a drill press [**Photo A**]. Clean the sides and square the ends with ¾" and ¼" chisels.

4 Lay out the tapers on the two *inside* faces of the legs (A) [**Drawing 1**]. Draw pencil lines on the bottom of the leg to divide it into quarters, and mark the quarter adjacent to the two outside faces, which remain straight, with an X.

5 Cut the two tapered sides of the leg (A) on a tablesaw with a tapering jig [**Photos B, C**]. To cut them on a jig like the one shown, align the taper along the edge of the jig base. Slide the fence up to the leg and secure it. Clamp the leg to the fence. (See *pages 32–35* for more about cutting tapers.)

6 Sand the tapered edges to remove the saw marks. Then, finish-sand the legs (A) to 220 grit.

The aprons are next

1 Cut the side aprons (B), front apron (C), and back apron (D) to size.

2 Lay out the tenons on all four aprons (B, C, D) [**Drawing 2**].

3 Cut the tenons with a tablesaw and ¾" dado set, in a setup similar to the one shown in **Photos I** and **J** on *page 28*.

1 SIDE ASSEMBLY
(Right inside face shown)



1a APRON



4 Lay out the arches on the side (B) and front (C) aprons [**Drawings 1a, 3**]. Draw the arches through the endpoints and centerpoint using a fairing stick. (For a free fairing stick plan, go to woodmagazine.com/fairing.)

5 Bandsaw the arches slightly outside the line, and then sand to the line. Finish-sand the aprons (B, C, D).

6 Glue and clamp a front and rear leg (A) to each end of each side apron (B) [**Drawing 1**], keeping the tops of the legs and the apron flush.

7 Glue and clamp the side assemblies (A/B) to the front apron (C) and back apron (D) [**Drawing 3**].

2 APRON TENON DETAIL



A MORTISE THE LEGS

Set the drill-press fence and depth stop, and drill spaced holes for the mortise. Then drill out the waste between the holes.

B

C TAPER THE LEGS

Cut tapers on the mortised faces of the legs (A). Make the first cut with the marked quadrant of the foot against the jig fence and on top [Photo B]. Make the second cut with the flat side of the leg on the jig base and the marked quadrant against the fence [Photo C].



Make the drawer openings

1 Cut the front rails (E) to size. Bandsaw ½×1¼" notches on the ends of the two top rails and ½×½" notches on the bottom one [**Drawing 3**].

2 Drill and countersink shank holes in the back edge of the front rails (E) [**Drawing 3**]. (For #8 screws, drill 5/32" shank holes and 7/64" pilot holes.)

3 Glue and clamp the lower rail (E) flush with the top edge of the front apron (C). Drill pilot holes and drive screws into the legs (A).

4 Cut four 2⅜" temporary spacers; then dry-assemble the upper and middle rails (E) with the spacers [**Photo D**]. Ensure that the upper rail sits flush with the top of the side assembly (A/B). Glue and clamp the rails, drill pilot holes, and drive the screws.

5 Cut the upper (F) and lower drawer supports (G) to size. Drill and countersink shank holes 2" from each end [**Drawing 1**]. Using the temporary spacers, screw the supports to the side aprons (B) [**Drawing 1a, Photo E**].

6 Cut the drawer side spacers (H) to size. Drill and countersink shank holes centered 2" from each end [**Drawing 1**]. Position the spacers on the side aprons (B) [**Drawing 1a**], drill pilot holes, and drive the screws [**Photo F**].

Top it off

1 Edge-glue stock for the top (I), and cut the top to size.

2 Chuck a ⅛" round-over bit in a handheld router, and round over the upper edge of the top (I) [**Drawing 3**]. Rout across the grain on the ends first.

3 Tilt your tablesaw blade 27° from vertical, and cut the bevel along the bottom edge of the top (I) [**Drawing 3**]. Bevel the ends first, then the sides.

4 Sand the edges to remove tool marks; then finish-sand the top (I).

5 With a ¾" Forstner bit, drill a ⅛"-deep recess in the top of each leg (A) for the figure-eight top fasteners [**Drawing 1**]. Drill pilot holes for the screws, and attach the fasteners to the legs.

6 Place the top (I) facedown on a padded surface. Then invert the table assembly on it, centered, and mark locations on the underside of the top for the figure-eight fastener screws. Carefully drill pilot holes, then drive the screws.

Build a pair of drawers

1 Cut the drawer fronts (J), sides (K), backs (L), and bottoms (M) to size [**Drawing 5**].

2 Refer to **Drawings 4** and **4a** to machine the drawer fronts (J) and sides (K). Cut a 1/16" rabbet along the bottoms of the drawer fronts [**Drawing 5a**]. Drill the knob holes.

3 Cut the ½" dado in the drawer sides (K) [**Drawing 4a**] to receive the drawer back (L). Then cut grooves in the front (J) and sides to hold the bottom (M) [**Drawing 5**].

5 DRAWER



Cutting Diagram



¼ x 24 x 48" Birch plywood



¾ x 7¼ x 96" Cherry (5.3 bd. ft.)

¾ x 9¼ x 96" Cherry (6.7 bd. ft.)

*Plane or resaw to the thickness listed in the Materials List.

¾ x 7¼ x 96" Cherry (5.3 bd. ft.)

5a DRAWER FRONT SECTION VIEW



4 Finish-sand the drawer parts. Glue the drawer fronts (J) and backs (L) to the sides (K) [**Drawing 5**]. Slide the bottoms (M) into the grooves in the sides and fronts, but do not glue them. Square the drawers, and clamp. Attach the bottoms to the backs with wire nails.

Finish your nightstand

1 Inspect the assemblies and touch up the finish-sanding as necessary.

2 Stain as desired. (We applied Minwax no. 607 Cherrywood gel stain to match the bed.)

3 Apply a clear finish. (We applied three coats of satin polyurethane, sanding to 320-grit between coats.)

4 Install the drawer knobs. Then slide the drawers into place.

Written by **Larry Johnston** with **Chuck Hedlund**
Project design: **Kevin Boyle**
Illustrations: **Roxanne LeMoine**; **Lorna Johnson**

Materials List

Part		FINISHED SIZE T	W	L	Matl.	Qty.
A	legs	1½"	1½"	26"	C	4
B	side aprons	¾"	8¾"	15¼"	C	2
C	front apron	¾"	2"	15½"	C	1
D	back apron	¾"	8¾"	15½"	C	1
E	front rails	¾"	1¾"	15¼"	C	3
F	upper drawer supports	¾"	1"	13½"	C	4
G	lower drawer supports	¾"	1"	12¾"	C	2
H	drawer side spacers	9⁄16"	¾"	14"	C	4
I	top	¾"	19½"	23"	EC	1
J	drawer fronts	¾"	2 9⁄16"	14 1⁄8"	C	2
K	drawer sides	½"	2 9⁄16"	15½"	C	4
L	drawer backs	½"	2 1⁄16"	13 5⁄8"	C	2
M	drawer bottoms	¼"	13"	13 5⁄8"	BP	2

Materials key: BP–birch plywood, C–cherry, EC–edge-glued cherry.
Supplies: #8 x 5⁄8", ¾", 1", 1¼", 1½", 2" flathead wood screws, figure-eight fasteners (4), 1½" wooden knobs (2).
Blade and bits: ⅛" round-over bit, rabbeting bit, dado set.



D ATTACH THE FRONT RAILS

Temporary spacers equalize the distance between the front rails (E) so the drawer openings will be the same height.

E ADD THE DRAWER SUPPORTS

Attach the top drawer support (F) flush with the top of the side apron (B). Use spacers to position the rest of the supports (F, G).



F PLACE THE SIDE SPACERS

The drawer side spacers (H) center the drawers side-to-side. Place them against the top of the middle and lower supports (F, G).

Fine-Furniture Accuracy from *ANY* Tablesaw

Even old hand-me-down saws and low-cost benchtop machines can produce clean, on-the-money cuts. We'll show you how.

It's all about the setup

Know the angles

You'll find the best and least expensive tablesaw accessories at an office supply store, of all places. Invest about $10 in a couple of plastic drafting triangles. They give you perfect 90°, 45°, 60°, and 30° corners for setting blade angles and miter angles [**Photos A** and **B**].

Ask for an extension

An extension screwed to the miter-gauge head will improve the quality and accuracy of your cuts. Use a flat length of ¾" plywood, MDF, or hardwood [**Photo C**].

The extra surface steadies longer stock. An extension that reaches past the blade backs up the cut, preventing tear-out on the back edge of the workpiece.

Keep it down

If your benchtop saw won't accept a dado blade to cut a rabbet, you need to make a series of cuts and nudge the fence over slightly between passes. The trick with this method is getting each cut precisely the same depth. **Photo D** shows a simple way to apply consistent pressure downward during each pass.

And here's a bonus tip: Use a rip blade for the best results. Its square-profile raker teeth cut a smooth, flat bottom.

Be sneaky; then stop it

It's often smart not to cut to finished size on the first pass. Instead, cut the workpiece slightly oversize; then sneak up on the final dimension for a perfect fit. This works especially well when the piece must fit into an existing opening.

An easy way to sneak up when crosscutting is to use a stopblock. When you can safely hang on to the "keeper" piece, clamp a stopblock to a miter-gauge extension [**Photo C**]. Nudge the stopblock toward the blade between cuts to get to the desired length. Once the stopblock is positioned, you can cut any number of pieces to identical lengths.

For keeper pieces too short to hang on to, attach the stop to the rip fence [**Photo E**]. The stop creates space for the cutoff to rest safely between the blade and fence without being kicked back. Cut test pieces until you have the rip fence and stopblock set properly.

Cutting sheet goods to size can be a challenge on any size saw. Make the initial cut about ⅛" oversize. This reduces the size of the sheet and makes it easier to handle. Then reposition the rip fence to trim the more manageable panel to finished size.

Watch a free video on how to verify tablesaw setups at woodmagazine.com/tssetup

SET DEAD-ON ANGLES WITH TRIANGLES



To set a blade angle, raise the blade fully and register the triangle against the body of the blade, not against the teeth. Raising the blade fully gives you the most surface for the triangle to rest against. Lower the blade to the proper cutting height after setting the angle.

GO LONG



A miter-gauge extension steadies long pieces. Clamp a stopblock to the extension to cut several pieces to identical length.

A PRESSING MATTER



A hold-down prevents the workpiece from rising off the table, ensuring cuts of equal depth. When clamping the hold-down to the fence, use the workpiece as a gauge. Bevel the leading edge of the hold-down to guide the board under it.

"L"-EMENTARY STOPBLOCK



When using this L-shape stopblock, add its 2" length to the desired dimension. Set the rip fence to this new measurement.

4 jigs that put you a cut above

The most useful tablesaw jigs in the *WOOD®* magazine shop: our sleds. Each carries a workpiece past the blade to make a precise cut. We build them precisely, ensuring perfect 90° crosscuts and 45° miters every time. Each of these sleds consists of a base guided by one or two miter-slot guides that fit into the miter-gauge slots.

Mighty miter sled

Setting up perfect miter cuts can be time-consuming. With a miter sled, you do it only once, when building the sled.

Cut the pieces for the miter sled to the dimensions shown in **Drawing 1**. After attaching the miter-slot guides, as shown in the **Shop Tip** *below*, put the jig on the tablesaw and cut a kerf 7½" into the base. Then follow the steps in **Drawing 2,** and use double-faced tape to temporarily attach the fences.

Test your setup by miter-cutting four pieces to identical length and dry-fitting them together as a frame. Check for a tight joint at all four corners. If needed, adjust the fences. Then screw them down in their final positions.

1 MITER SLED



2 INSTALLING THE MITER FENCES



Step 1
Draw a line across the base parallel to its front edge. Center the inside corner of a framing square on the kerf and rotate it until the same dimension on both legs of the square intersects the parallel line.

Step 2
Attach the right-hand fence along one leg of the framing square and the left face against the other.

SHOP TIP

Washers ease guide placement

To precisely mount miter-slot guides to a sled, first place a couple of washers in each miter-gauge slot. Then set the guides on top of them, as shown at *right*. The guides should sit just above the surface of the tablesaw. If they don't, add another washer or two. Put a strip of double-faced tape on top of each guide. Use the rip fence to help squarely position the base as you lower it onto the guides, as shown at *far right*. Press the base firmly onto the guides; then carefully remove the base with the guides attached. Now screw the guides in place.





Zero-clearance crosscut sled

The base of this sled is ¼" hardboard so you don't lose much cutting depth. Because there's no gap between the base and blade, it yields chip-free cuts on the underside of your workpiece.

Cut the base to size [**Drawing 3**]. Then attach the miter-slot guides, as shown in the **Shop Tip** *above*. After attaching the fence, set the saw blade just over ¼" high. Place the jig on the saw and make a cut that stops when the highest point of the blade reaches the front edge of the fence. Glue the blade guard to the rear of the fence in line with the saw kerf.

3 CROSSCUT SLED



Joinery jig

Tight-fitting joints are a snap on any saw when using this jig. Use it to cut tenons, half-laps, and bridle joints [**Drawing 4**].

Start by cutting a 16⅛×10" blank for the stationary and sliding bases [**Drawing 5**]. Cut grooves the length of the blank for the keys; then divide the blank into 8×10" pieces.

To make the slots for the locking knobs, drill a series of holes in the sliding base centered over each dado. Remove the remaining waste and smooth each slot with a chisel. Then glue and screw the brace and face to the sliding base. Make certain the face and base are perpendicular.

Cut the keys from hardwood to fit the dadoes. Dry-fit the bases together with their edges flush and the keys in the dadoes. Make a mark on each key by pressing an awl through each slot at the end closest to the blade. Drill holes at these marks and countersink the bottom of the hole. Then use epoxy to secure the machine screws in their holes. Now you can glue the keys into the dadoes in the stationary base.

Position the miter-slot guide, as shown in the **Shop Tip** *opposite*. Assemble the sliding and stationary bases so the machine screws are at the end of the slots farthest from the blade. Position the sliding base against the blade and bring the rip fence up to help square up the opposite edge of the jig. Press the jig onto the miter-slot guide, then lift the jig and screw the guide in place.

To cut tenons or half-laps, see **Photo F**. For a bridle joint, cut the tenon first. Then to make the open mortise, position the jig to make a cut roughly centered on the thickness of the workpiece. Make a cut, flip the workpiece face for face, and make another cut. Move the sliding base away from the blade and repeat the process until the joint fits together snugly.

4 THREE HARD-WORKING JOINTS



TWO-CUT TENONS OR HALF-LAPS

A kerf establishes the shoulder of the tenon or half-lap. Adjust the blade and position the jig to make an intersecting cut.

5 JOINERY JIG



No-tilt bevel sled

The jig shown in **Drawing 6** helps you cut precise 45° bevels without having to tilt the blade — a real advantage on a benchtop saw where fine-tuning blade tilt can be difficult.

Start by cutting the 45° bevel along one edge of the sled base. Return the blade to 90° and place the miter-slot guide into the miter slot, as shown in the **Shop Tip** *opposite*. Butt the beveled edge of the base against the body of the blade, then remove the base and screw the miter-slot guide in place.

Attach the wedges using the beveled edge of the base as a guide. Now you can screw the top plate to the wedges and the fence to the top plate. With the blade at 90°, trim the top plate and fence.

To prevent workpieces from sliding down toward the blade during a cut, always clamp the workpiece to the top plate and tight to the fence.

6 BEVEL SLED



Written by **Craig Ruegsegger**
Illustrations: **Roxanne LeMoine**; **Lorna Johnson**

Watch a free video of the miter sled being built at woodmagazine.com/mitersled

Better Homes and Gardens®

WOOD® MAGAZINE Project Shop™

Sponsored by

DELTA | PORTER CABLE

From *WOOD* Magazine learn top tool tips, techniques, and how to build projects



Come learn at *WOOD* Magazine's Project Shop at a woodworking show near you. Master Craftsman Jim Heavey will demonstrate valuable tool tips and techniques as he walks you through projects from the pages of *WOOD* Magazine.

The Wood Working Shows

Produced by Straight Line Productions

The Woodworking Shows is the premier event for woodworkers!

Come to this 3-day event and:

- Attend ***FREE*** educational seminars
- See the newest tools
- Find the best deals on tools and supplies
- Get hands-on tool experience at the Hand Tool Rodeo

2008 – 2009 SCHEDULE

Oct. 10-12	St. Paul, MN	Jan. 30- Feb. 1	Indianapolis, IN
Oct. 17-19	Portland, OR	Feb. 6-8	St. Louis, MO
Oct. 24-26	Salt Lake City, UT	Feb. 13-15	Kansas City, KS
Oct. 31-Nov. 2	Costa Mesa, CA	Feb. 20-22	Boston, MA
Nov. 7-9	Tucson, AZ	Feb. 27-Mar. 1	Somerset, NJ
Nov. 14-17	Denver, CO	March 6-8	Hartford, CT
Nov. 21-23	Chicago, IL	March 13-15	Tampa, FL
Dec. 5-7	Dallas, TX	March 20-22	Charlotte, NC
Dec. 12-14	Nashville, TN	March 27-29	Chantilly, VA
Jan. 2-4	Baltimore, MD	April 3-5	Houston, TX
Jan. 9-11	Milwaukee, WI	April 17-19	Seattle, WA
Jan. 16-18	Columbus, OH	April 24-26	Sacramento, CA
Jan. 23-25	Atlanta, GA	May 1-3	Ontario, CA

For more information visit

woodworkingshows.com

woodmagazine.com

deltaportercable.com

Go to **woodworkingshows.com** for discounted tickets!

Better Homes and Gardens®

WOOD® PATTERNS®

November 2008 *Issue 187*

Dear Reader: As a service to you, we've included full-size patterns on this insert for irregular shaped and intricate project parts. You can machine all other project parts using the Materials List and the drawings accompanying the project you're building.

© Copyright Meredith Corporation, 2008. All rights reserved. Printed in the U.S.A. Meredith Corp., the publisher of WOOD Patterns®, allows the purchaser of this pattern insert to photocopy these patterns solely for personal use. Any other reproduction of these patterns is strictly prohibited.



Desk Clock
Page 74

Pencil-Post Bed
Page 24



Magnetic-Calendar Icons
Page 68

Desk Clock
Page 74









Pencil-Post Bed
Page 24

Pencil-Post Bed
Page 24













Magnetic-Calendar Icons
Page 68





©2008 Media Services S-8053 OF20390R-1 Advertisement

AS HEARD ON PAUL HARVEY NEWS

New advanced portable heater can cut your heating bill up to 50%

Heats a large room in minutes with even heat wall to wall and floor to ceiling

Does not get hot, cannot start a fire and will not reduce humidity or oxygen

A new advanced quartz infrared portable heater, the EdenPURE™, can cut your heating bills by up to 50%.

You have probably heard about the remarkable EdenPURE™ as heard on Paul Harvey News and on television features across the nation.

The EdenPURE™ can pay for itself in a matter of weeks and then start putting a great deal of extra money in your pocket after that.

A major cause of residential fires in the United States is portable heaters. But the EdenPURE™ cannot cause a fire. That is because the quartz infrared heating element never gets to a temperature that can ignite anything.

The outside of the EdenPURE™ only gets warm to the touch so that it will not burn children or pets. Pets can sleep on it when it is operating without harm.

The advanced space-age EdenPURE™ Quartz Infrared Portable Heater also heats the room evenly, wall-to-wall and floor-to-ceiling. And, as you know, portable heaters only heat an area a few feet around the heater.

Unlike other heating sources, the EdenPURE™ cannot put poisonous carbon monoxide into a room or any type of fumes or any type of harmful radiation.

Q. What is the origin of this amazing heating element in the EdenPURE™?

A. This advanced heating element was discovered accidentally by a man named John Jones.

Q. What advantages does infrared quartz tube heating source have over other heating source products?

A. John Jones designed his heating source around the three most important consumer benefits: economy, comfort, and safety.

In the EdenPURE™ system, electricity is used to generate infrared light which, in turn, creates a very safe heat.

Never be cold again

Cannot start a fire; a child or animal can touch or sit on it without harm

After a great deal of research and development, very efficient infrared heat chambers were developed that utilize three unique patented solid copper heat exchangers in one EdenPURE™ heater.

Q. How can a person cut their heating bill by up to 50% with the EdenPURE™?

A. The EdenPURE™ will heat a room in minutes. Therefore, you can turn the heat down in your house to as low as 50 degrees, but the room you are occupying, which has the EdenPURE™, will be warm and comfortable. The EdenPURE™ is portable. When you move to another room, it will quickly heat that room also. This can drastically cut heating bills, in some instances, by up to 50%.

The EdenPURE™ comes in 2 models. GEN3 Model 500 heats a room up to 300 square feet and GEN3 Model 1000 heats a room up to 1,000 square feet.

End of interview.

The EdenPURE™ will pay for itself in weeks. It will put a great deal of extra money in a users pocket. Because of today's spiraling gas, oil, propane, and other energy costs, the EdenPURE™ will provide even greater savings as the time goes by.

Readers who wish can obtain the EdenPURE™ Quartz Infrared Portable Heater at a $75 discount if they order in the next 10 days. Please see the Special Readers Discount Coupon on this page. For those readers ordering after 10 days from the date of this publication, we reserve the right to either accept or reject order requests at the discounted price.

How it works:


Heats floor to the same temperature as ceiling.
CUTAWAY VIEW
1. Electricity ignites powerful quartz infrared lamp.
2. The quartz infrared lamp without combustion gently warms the patented cured copper tubes.
3. The heat from the copper tubing rides the humidity in the room and provides moist, soft heat ceiling to floor, wall to wall without reducing oxygen or humidity.

SPECIAL READER'S DISCOUNT COUPON

The price of the EdenPURE™ GEN3 Model 500 is $372 plus $17 shipping for a total of $389 delivered. The GEN3 Model 1000 is $472 plus $27 shipping and handling for a total of $499 delivered. People reading this publication get a $75 discount with this coupon and pay only $297 delivered for the GEN3 Model 500 and $397 delivered for the GEN3 Model 1000 if you order within 10 days. The EdenPURE™ comes in the decorator color of black with burled wood accent which goes with any decor. There is a strict limit of 3 units at the discount price - no exceptions please.

Check below which model and number you want:

☐ GEN3 Model 500, number _____ ☐ GEN3 Model 1000, number _____

- To order by phone, call TOLL FREE **1-800-588-5608 Ext. EPH8065**. Place your order by using your credit card. Operators are on duty 24 hours, 7 days.
- To order online, log on to www.epheater.com
- To order by mail, by check or credit card, fill out and mail in this coupon.

This product carries a 60-day satisfaction guarantee. If you are not totally satisfied, your purchase price will be refunded. No questions asked. There is also a three year warranty.

NAME _____

ADDRESS _____

CITY _____ STATE _____ ZIP CODE _____

Check below to get discount:

☐ I am ordering within 10 days of the date of this publication, therefore I get a $75 discount and my price is only $297 for GEN3 Model 500 and $397 for GEN3 Model 1000 delivered.

☐ I am ordering past 10 days of the date of this publication, therefore I pay shipping and handling and full price totaling $389 for GEN3 Model 500 and $499 for GEN3 Model 1000.

Enclosed is $_____ in: ☐ Cash ☐ Check ☐ Money Order
(Make check payable to BioTech Research) or charge my:

☐ VISA ☐ MasterCard ☐ Am. Exp./Optima ☐ Discover/Novus

Account No. _____ Exp. Date ___/___

Signature _____

MAIL TO: BioTech Research Dept. EPH8065
7800 Whipple Ave. N.W.
Canton, OH 44767

SHOP TESTED

Hybrid Tablesaws

These machines combine some of the beefy qualities of 3-hp cabinet saws with the lighter weight and 110-volt convenience of contractor-style saws. You'll find out whether one belongs in your shop, and if so, which model to buy.

Centuries ago, someone bred a horse with a donkey to produce the mule—a hybrid that packs strength and durability into a midsize package. Fast-forward to the late 20th century, when power-tool manufacturers crossbred 3-hp cabinet tablesaws with 1½-hp open-leg contractor saws. The resulting hybrid saws typically look like cabinet saws (with dust- and noise-capturing closed bases) but perform and adjust more like contractor saws. Most hybrid saws are priced between deluxe contractor saws ($700) and bare-bones cabinet saws ($1,200), although two hybrids in this test come in north of the $1,200 mark. So with these machines borrowing features from both "parents," do they really provide you with the best of both worlds?

To find out, we gathered 10 models for head-to-head testing. We also tested two 3-hp cabinet saws that fall into the price range of these hybrids. Using new Freud 10" blades on each saw, we ripped, crosscut, mitered, and beveled solid red oak and birch plywood, just as you would in your own shop. In some respects, we found vast differences between the saws, and in others, it became a toss-up as to which unit performed best. Read on to find out how they fared.

A catchy title means nothing without power

Each of the hybrids has a 110-volt induction motor, rated from 1½ to 2 hp, mounted below the blade. To test each model's true power, we outfitted them with identical full-kerf 24-tooth blades, then ripped 2"-thick red oak as fast as each saw could handle, at 0° and 45° bevels. As shown in the chart on the *next page*, the Shop Fox W1748 demonstrated the most power, as it breezed through the wood without bogging down. It even bested two 3-hp saws.

Grizzly's G0478, a near twin to the Shop Fox, finished second among

Shop Fox Dominates Power Test

We tested each saw's power and cutting speed by ripping 2"-thick red oak with identical Freud 24-tooth blades, pushing the wood as fast as each machine could handle it.



hybrids, 3½ feet per minute off the pace, with the Hitachi C10LA and DeWalt DW746X close behind. The 1⅛"-wide drive belts on the three top-performing saws (including the 3-hp Grizzly G1023SL) seem to transfer power better from the motor to the blade.

Four saws cut only about half as fast as the Shop Fox. Although these models don't have the power of the leaders, they still cut everything we threw at them when we reduced the feed rate. As with a contractor saw, these hybrids will cut faster using thin-kerf blades.

Sturdy fence, miter gauge will be your best friends

All of the saws feature T-square-style fences. We liked the Steel City 35670's Deluxe Fence best because it deflected the least (.0033") during tough rip cuts. It has UHMW sideboards, slides easily along the rail, and locks solidly in place. Jet's ProShop aluminum fence features two T-slots on top—handy for mounting accessories—and finished second in the deflection test at .004". Delta finished third (.005"), followed by Hitachi (.0053"), and DeWalt (.006").

We like the matching Aluma-Classic fences on the Grizzly and Shop Fox for their features—T-slots on each face, a scale marked in 1/32" increments over its full length, and a magnifying cursor—but they deflected 0.0077" and 0.009" (sixth and seventh, respectively) in the test. When using a properly aligned blade guard or splitter, you likely won't notice a problem with this amount of fence deflection. But when we ripped on these saws with no guard or splitter, the workpiece cutoff wandered into the back teeth of the blade slightly and resulted in a little spray of sawdust back toward us. Greater amounts of deflection could create potential kickback when you don't use the splitter.

The miter gauges are all basic units, with stops at 0° and 45°. We give a slight edge to those that use a retractable pin (Craftsman, General International, Jet, and Steel City) to contact the adjustable stops. The pins provide a more stable bearing surface than the wobbly flip-up metal tabs of the other miter gauges.

More findings that should help shape your decision

■ **Safety guards.** Like the manufacturers, we encourage you to use your blade guard and splitter. Because most prove difficult to remove and replace, you might be tempted to leave them off. Fortunately, Steel City and Craftsman saws have quick-release systems [**Photo A**], which eliminate the hassle. The General International and Steel City's granite-top 35900G have separate riving knives [**Photo B**], for use when you need to remove the guard. These riving knives mount behind the blades to maintain the kerf openings and prevent kickback, but do not shield you from the blade.

■ **Dust collection.** The enclosed bases keep most of the dust out of your shop's air, but not all the debris goes into your dust collector. The DeWalt outperformed the pack in spite of its open back and bottom, thanks to a shroud around the blade [**Photo C**]. Hitachi's hopper-shaped bottom worked well to corral dust [**Photo D**]. The others allowed much dust to build up in the corners of the cabinet.

A QUICK CHANGE OF THE GUARD

Guards on Steel City and Craftsman saws slide into a tension clip inside the throat and over a bolt on the back. No tools required.

A GOOD SAFETY SUBSTITUTE

A riving knife, like this one on the General International hybrid, keeps the blade kerf open and prevents kickback.

BUILT-IN COMPONENTS CHANNEL DUST TO COLLECTOR

DeWalt's blade shroud captures dust at the point of cut and funnels it to a 2½" port and your shop vacuum or dust collector.



Dust falls downward from the blade to the hopper in Hitachi's cabinet, and into the 4" port in the center of the hopper.

■ **Aligning the tabletop to the blade.** Kudos to Craftsman and Steel City for their cabinet-mounted trunnions, *far right*, that make it easy to align the miter slots to the blade. The other saws' trunnions mount directly to the underside of the tabletop, *near right*. They require loosening four to six bolts inside the cabinet, while you move the trunnion to make the adjustment—not an easy task in many.

■ **Switches.** These come in two types, magnetic or mechanical. We prefer magnetic switches with large paddles over the "off" button. A magnetic switch prevents the machine from restarting if there is a power outage during a cut.

Hybrid Saw



Adjusting trunnions mounted to the top proves difficult because you must reach inside the cabinet to loosen and move them.

Cabinet Saw



Cabinet-mounted trunnions stay put while you loosen the bolts and pivot the table from above to align the blade with the miter slot.

A close-up look at the hybrids (Note: mobile bases not included)

Craftsman 22114, $750

800-383-4814, craftsman.com

High Points

- The safety guard easily mounts and dismounts with no tools.
- The power switch mounts anywhere along the fence rail.
- Setscrews make leveling table extension wings easy, a big plus when assembling the machine.
- The trunnions mount to the cabinet rather than the top, making it easy to align the top to the blade.

Low Points

- The aluminum rip fence deflected 0.027"—the most in our test—despite front and rear clamps.
- It was the slowest-cutting and loudest saw in the test.

More Points

- Centered fence rails provide a little over 25" rip capacity left of the blade (most in the test) and right of the blade (least in the test). Also, we found the rip fence microadjuster difficult to use.
- You must take the arbor washer off the arbor for dado widths greater than 11/16".

DeWalt DW746X, $1,200

800-433-9258, dewalt.com

High Points

- In spite of having the only open cabinet back, it provided the best dust collection, thanks to its blade shroud and 2½" funneled dust port.
- It exhibited above-average power, outmuscling six of its peers during heavy test cuts.
- At about 40×55", this saw has the most compact footprint without sacrificing rip capacity.

Low Points

- Its power switch is small and hard to reach, especially with a knee or thigh.
- When making bevel cuts, the blade moved from its setting unless locked.
- The rip fence proved difficult to adjust parallel to the blade, and you must move the single sideboard to the opposite face for left-of-blade rips.

Delta 36-717B, $1,100

800-223-7278, deltaportercable.com

High Points

- Its large off-switch was easy to reach and bump with a leg.
- A support leg and melamine-coated particleboard extension wing are standard equipment.
- Beefy handwheels ease blade adjustments and lock solidly.
- The bevel-scale cursor sits close to the scale for the easiest setting of angles.

- At 86 decibels, it's one of the quietest saws in the test.
- The rip fence deflected little during cuts.

Low Points

- Its triangular miter gauge was difficult to use and set accurately.
- The blade guard must be held or propped up while changing blades.

General International 50-220RC, $1,575

888-949-1161, general.ca

High Points

- One of only two tested saws with a riving knife (if you choose to remove the blade guard).
- The arbor lock makes one-wrench blade changes quick and easy.
- Its large off-switch was easy to reach and bump with a leg.

Low Points

- We could not correctly calibrate the digital bevel display with the blade.
- Despite a blade shroud and 2½" hose that connects to the 4" port, dust collection proved no better than models without a shroud.

More Points

- The rip fence was solid and held with little deflection, but at 2⅛" tall, it's the shortest fence in the test by nearly ½".
- Because the heavy-duty arbor assembly rides vertically on four columns rather than a cantilevered arm, it's more difficult to raise the blade.
- With an aluminum rip fence, the price drops to $1,470.

"If I'm willing to spend $1,000 on a hybrid...

...should I instead get a 3-hp saw for about the same money?" To find out, we tested two comparably priced 3-hp tablesaws: Grizzly's G1023SL and Steel City's 35675. Both need 220-volt power and have a few similarities (left-tilting arbor, UHMW-faced T-square-style rip fences, cabinet-mounted trunnions for easier top-to-blade alignment, and magnetic switches). The saws also displayed about equal power, with the Grizzly cutting at 20.57 fpm in 2"-thick red oak and the Steel City cutting 18.22. But both saws trailed the 2-hp Shop Fox W1748 hybrid in our testing.

The G1023SL sells for $995 equipped for 30" rip capacity. You get a miter gauge, but no saw blade or plug for the power cord. The 35675 sells for $1,200 with 30" rip capacity. With that you get a 40-tooth blade, miter gauge, and a table-wing extension. You can upgrade each machine's fence rails for 50" rip capacity.

The bottom line: These tablesaws don't quite have the oomph of pricier cabinet saws, such as a Delta Unisaw or Powermatic 66, but they're not bad. As for the choice between these or a hybrid, we say get three horses if you're wired for 220. The Steel City 35675 has the edge in capacities and standard equipment, but for $200 less we'd opt for the performance advantage from the Grizzly G1023SL. (See the bottom rows of the chart on the *next pages* for a head-to-head comparison.)

Grizzly G1023SL

Steel City 35675

Grizzly G0478, $775

800-523-4777, grizzly.com

High Points

- This saw proved the second most powerful hybrid in the test, and it runs smoothly with only slight vibration.
- It has the greatest capacity for crosscuts (13⅜") with the miter gauge resting on the top.
- We like its aluminum rip fence with T-slots on each side and a magnifying cursor.

Low Points

- This power-hungry saw requires a dedicated 20- or 30-amp circuit (depending on the gauge of wire used) for 110 volts to avoid tripping a breaker.
- Despite many attempts, we couldn't get the miter slot and blade parallel (.004" off was the best we could do; we strived for half that).
- It does not come with a plug for the power cord or a saw blade.

More Points

- It has a magnetic power switch, but the off-switch is smaller than most and hard to locate with a leg.
- Although the handwheels crank easily, it takes more than 46 revolutions to fully raise the blade—more than twice as many turns as most of the saws tested.

Jet JPS-10, $950

800-274-6848, jettools.com

High Points

- Its sturdy aluminum rip fence held securely with only slight deflection and has the best magnifying cursor on the scale.
- Its large off-switch was easy to reach and bump with a leg.
- The arbor lock makes one-wrench blade changes quick and easy.

Low Points

- It ranked among the least powerful saws in the test.
- It has the smallest capacity for crosscuts (10½") with the miter gauge resting on the tabletop.

More Points

- Although its cabinet does not extend fully to the floor, it is enclosed and provided respectable dust collection.

Hitachi C10LA, $1,000

800-829-4752, hitachipowertools.com

High Points

- Despite a 1½-hp motor, this saw outpowered beefier saws.
- The included small outfeed table proved handy and effective.
- Microadjusters on the rip fence proved accurate and easy to use.

Low Points

- Its power switch is small and hard to reach.
- You must remove the outfeed table, six hexhead bolts, and the back panel to access the motor and trunnions for adjustments.
- We could not get all the detents on the miter gauge set accurately.
- The blade guard must be held or propped up while changing blades, and the narrow throat opening makes blade changes more difficult.

More Points

- There's no lock on the blade height handwheel, although we never had problems with the blade slipping.

Shop Fox W1748, $980

800-840-8420, shopfox.biz

High Points

- Far and away, this saw proved the most powerful in the test, and it ran smoothly with only slight vibration.
- We like its aluminum rip fence with T-slots on each side and a magnifying cursor.

Low Points

- This power-hungry saw requires a dedicated 20- or 30-amp circuit (depending on the gauge of wire used) for 110 volts to avoid tripping a breaker.
- Bolt placement made adjusting the trunnions more difficult than most when aligning the top parallel to the blade.
- It does not come with a plug for the power cord or a saw blade.

More Points

- It has a magnetic power switch, but the off-switch is smaller than most and hard to locate with a leg.
- Although the handwheels turn easily, it takes more than 43 revolutions to fully raise the blade.

Steel City 35900G, $1,250

877-724-8665, steelcitytoolworks.com

High Points

- This model has a 2"-thick, perfectly flat and smooth solid-granite top that delivered best-in-test vibration dampening.
- The safety guard easily mounts and dismounts with no tools.
- You have two riving knives (tall/full kerf and short/thin kerf) to choose from when not using the blade guard.
- Its large off-switch was easy to reach and bump with a leg.
- The trunnions mount to the cabinet rather than the tabletop, making it easy to align the top to the blade.
- At 84 decibels, it's the quietest saw in the test.

Low Points

- It ranked among the least powerful saws.

More Points

- The industrial rip fence locked solidly and slid smoothly, but exhibited the second most deflection (0.0097") in the test.
- You must leave the arbor washer off the arbor for dado widths greater than 11/16".

Steel City 35670, $1,100

877-724-8665, steelcitytoolworks.com

High Points

- We rate this model's rip fence best-in-class because it showed almost no deflection, locks solidly, glides easily on the rail, and has a scale marked in inches and centimeters.
- The safety guard easily mounts and dismounts with no tools.
- Built-in setscrews make it easy to level the cast-iron wings to the table during assembly.
- It had the only cast-iron table that was perfectly flat and did not need shimming.
- Its large off-switch was easy to reach and bump with a leg.
- The trunnions mount to the cabinet, making it easy to align the top to the blade.

110-VOLT HYBRID TABLESAW SHOWDOWN

BRAND / HYBRID TABLESAWS	MODEL	MOTOR: RATED HORSEPOWER	MOTOR: VOLTAGE	MOTOR: TYPE OF DRIVE BELT (1)	DIMENSIONS, INCHES: OVERALL, H×D×W WITH RIP FENCE AND BLADE GUARD	DIMENSIONS, INCHES: TABLETOP, D×W	DIMENSIONS, INCHES: FRONT OF TABLE TO BLADE	CAPACITIES, INCHES: MAX. RIP, LEFT OF BLADE	CAPACITIES, INCHES: MAX. RIP, RIGHT OF BLADE	CAPACITIES, INCHES: MAX. CUTTING HEIGHT AT 90°	CAPACITIES, INCHES: MAX. CUTTING HEIGHT AT 45°	CAPACITIES, INCHES: MAX. DADO BLADE WIDTH (2)
CRAFTSMAN	22114	1½	110/220	F	39¾ × 42½ × 66⅜	27 × 40⅛	12⁹⁄₁₆	25⁹⁄₁₆	25⅝	3⅝	2⅜	11⁄16
DELTA	36-717B	1¾	110/220	F	38⅞ × 46 × 64⅛	27 × 54⁹⁄₁₆	13	14½	29⅝	3⅛	2¼	13⁄16
DEWALT	DW746X	1¾	110/220	R	39¾ × 37¾ × 55³⁄₁₆	27 × 40³⁄₁₆	12⅛	13¹⁵⁄₁₆	28	3	2³⁄₁₆	13⁄16
GENERAL INTERNATIONAL	50-220RC	1½	110/220	F	39¹⁵⁄₁₆ × 40⅞ × 60¹⁄₁₆	27 × 44	11⁵⁄₁₆	14⁵⁄₁₆	28⁹⁄₁₆	3	2⁵⁄₃₂	13⁄16
GRIZZLY	G0478	2	110/220	F	39³⁄₁₆ × 47⅛ × 60	27 × 39⅝	13⅜	7⁷⁄₁₆	29¾	3¼	2³⁄₁₆	13⁄16
HITACHI	C10LA	1½	110/220	V	42⅛ × 38⅛ × 65¹⁵⁄₁₆	27⅛ × 40¼	12⁵⁄₁₆	18⅜	30⁷⁄₁₆	3⁵⁄₁₆	2¼	13⁄16
JET	JPS-10	1¾	110/220	R	40⁵⁄₁₆ × 37¾ × 59⅝	27 × 44	10⁹⁄₁₆	10⁹⁄₁₆	31⅞	3⅜	2⅜	13⁄16
SHOP FOX	W1748	2	110/220	F	39⅜ × 47⅛ × 60	27 × 39⅝	13⁵⁄₁₆	7⅝	29⁹⁄₁₆	3⅛	2³⁄₁₆	13⁄16
STEEL CITY	35670	1¾	110/220	F	39⅝ × 45¼ × 62¼	27 × 56⅛	12⅝	12⅞	29⅝	3⁵⁄₁₆	2⁷⁄₁₆	11⁄16
	35900G	1¾	110/220	F	41½ × 42¾ × 64⁵⁄₁₆	27 × 56⅛	11¹³⁄₁₆	14	30¼	3⅜	2⅜	11⁄16
3-HP CABINET TABLESAWS												
GRIZZLY	G1023SL	3	220	3V	38¼ × 46⅛ × 55¹³⁄₁₆	27 × 40¹⁄₁₆	12⅜	8¹⁄₁₆	25¹³⁄₁₆	2³¹⁄₃₂	2⅛	15⁄16
STEEL CITY	35675	3	220	F	39½ × 42¾ × 64³⁄₁₆	27 × 56⅛	12½	13⁹⁄₁₆	30⁹⁄₁₆	3³⁄₁₆	2⁵⁄₁₆	11⁄16

1. (F) Flat multi-ribbed
   (R) Ribbed V-belt
   (V) Standard V-belt
   (3V) 3 V-belts
2. Measured with arbor washer on and nut tightened fully onto arbor threads.
3. (A) Aluminum
   (M) Melamine
   (U) UHMW
4. (MA) Magnetic
   (ME) Mechanical
5. (1) Single wrench
   (1L) Single wrench with arbor lock
   (2) Two wrenches
6. A Excellent
   B Good
   C Fair
   NA Blade not included

Low Points

- It ranked among the least powerful saws in the test.
- The blade flutters a little side to side as it coasts down, opening the zero-clearance kerf slightly.

More Points

- You must leave the arbor washer off the arbor for dado widths greater than 11/16".

Put your money toward the power

None of these saws has a flaw so significant that we'd warn you to steer clear of it, but many turned out to be little more than closed-base contractor saws. So we put greater emphasis on power, and that's why the Shop Fox W1748 gets the nod as Top Tool. It not only outpowered the other hybrids, it also humbled two 3-hp saws. The W1748 vibrated a barely noticeable amount, and has a durable aluminum T-square fence, accurate bevel stops, and large, easy-turning handwheels with solid locks.

Written by **Bob Hunter** with **Craig Ruegsegger**
Illustrations: **Tim Cahill**

HANDWHEELS					PERFORMANCE RATINGS (6)																	ACCESSORIES (10)							
					PRIMARY								SECONDARY																
REVOLUTIONS REQUIRED TO RAISE BLADE TO FULL HEIGHT	REVOLUTIONS REQUIRED TO TILT BLADE TO 45°	RIP FENCE SIDEBOARD MATERIAL (3)	TYPE OF ON/OFF SWITCH (4)	BLADE CHANGE METHOD (5)	POWER (7)	OVERALL QUALITY OF RIP FENCE	ABSENCE OF FENCE DEFLECTION (8)	ABSENCE OF VIBRATION	EASE OF ALIGNING TABLE AND BLADE	EASE OF ADJUSTING FENCE TO BLADE	EFFECTIVENESS OF SAFETY GUARDS	EASE OF REACHING ON/OFF SWITCH	QUALITY OF MITER GAUGE	EASE OF CHANGING BLADES	EASE OF ADJUSTING BEVEL STOPS	ACCURACY OF BEVEL SCALE	ACCURACY OF RIP FENCE SCALE	DUST COLLECTION (9)	EASE OF ADJUSTING WINGS TO TOP	EASE OF REMOVING BLADE GUARD	EASE OF USING HANDWHEELS	QUALITY OF INCLUDED BLADE	STANDARD	OPTIONAL	NOISE LEVEL, DECIBELS	WEIGHT, LBS	CORD LENGTH, FEET	WARRANTY, YEARS (11)	COUNTRY OF ASSEMBLY (12)	SELLING PRICE (13)
18½	31	A	ME	2	B	B-	C-	B	A	B	B-	A	b+	a	a	b	a	b-	a	a	a	b	B,F,M		95	315	8	1	C	$750
18	31½	M	ME	2	B+	B+	A-	B	B	B	B-	A	c	b+	a	b	a	b+	a	b	a	b	B,E,F,M	R	86	315	8	2	C	$1,100
21½	22½	A	ME	2	A-	B+	A-	B	B	B	B-	C+	b-	b	a	c	a	a-	a	c	b-	b	B,F,M	R	94	276	8	3	C	$1,200
19	42	M	ME	1L	B+	A-	B	B	B	B	B	A	b	a	a	b-	a	b-	b	b+	b	b	B,F,M	R	87	330	10	2	T	$1,575*
46½	50½	A	MA	1	A-	A-	B+	A-	B-	A	B-	B-	b-	b	a	b+	a	b	b	c	a	na	F,M	R	89	316	10	1	C	$775
23	16	A	ME	1L	A-	A-	A-	A-	B	B	B-	C+	b	b	c	a-	a	a-	b	b+	b	b	B(2),F,M		92	275	6¾	2	C	$1,000
34½	38	A	ME	1L	B	A	A	A-	B	A	B-	B-	b	a	a	b+	a	b+	b	b+	b	na	F,M	R	92	297	6	5	C	$950
43½	49½	A	MA	1	A	A-	B	A-	B-	A	B-	B-	b-	b	a	b+	a	b	b	c	a	na	F,M	R	89	319	10	2	T	$980
18½	31	U	ME	2	B	A	A	B-	A	B	B-	B+	b+	a	a	b-	a	b	a	a	b+	b	B,E,F,M	R	86	355	8	5	C	$1,100
19	62	U	ME	2	B	B+	B	A	A	A	B	B+	b+	a	a	b-	a	b	a	a	b+	b	B,E,F,M	R	84	470	8	5*	C	$1,250
13	29½	U	MA	2	A	A-	A	A-	A	B	B-	B	b-	a	a	a	a	b	b+	b	b-	na	F,M	R	94	410	12	1	C	$995
18½	32	U	MA	2	A-	B+	B	B	A	A	B-	B+	b+	a	a	b-	a	b	a	a	b+	b	B,E,F,M	R	88	347	8	5	C	$1,200

7. Timed cuts ripping 2"-thick red oak, average of three tests.

8. A=.006" or less
B=.0061" to .0150"
C=.0151" to .0300"

9. Using a 1½-hp dust collector.

10. (B) 10" Blade
(E) Table extension
(F) Rip fence
(M) Miter gauge
(R) 50"-rip-capacity fence rails

11. * 10-year warranty on granite top

12. (C) China
(T) Taiwan

13. Prices current at time of article production and do not include shipping, where applicable.
* Available for $1,470 with aluminum rip fence system

BASIC-BUILT™

GREAT PROJECTS MADE SIMPLE.

Bow-Front Display Case

Go ahead and build one—it's easier than you might think!

With its adjustable framed-glass shelves and open sides, this easy-to-build display case will let your collectibles shine. But you won't have to collect a shopful of tools to build it, just the ones shown on the *next page*.

Build the top and bottom

1 Cut the top/bottom panels (A) to size [**Materials List**, *page 61*]. Then cut the end trim (B, C) to size. Cut the front trim (D, E) ¼" wider than listed.

2 Glue and clamp the narrow end trim (B) to the ends of the bottom panel (A) [**Drawing 1**] with the tops flush with the best surface of the plywood [**Photo A**]. ***Note:*** The plywood and ¾" hardwood will not be the same thickness, but that's okay. After the glue dries, glue and clamp one piece of narrow front trim (D) to the front edge of the bottom panel.

3 Glue the wide end trim (C) flush with the best surface of the top panel (A). Glue and clamp one piece of wide front trim (E) to the front edge of the top panel.

4 Clamp the bottom panel assembly (A/B/D) to your bench. Mark the curve centerline and ends on the narrow front trim (D) [**Drawing 2**]. Use a fairing stick to trace the curve. (See **Shop Tip** on



Raise the plywood panel (A) on a scrapwood spacer, and glue the narrow end trim (B) flush with the top of the bottom panel. The difference in thickness will be hidden later.

Overall dimensions:
30" wide × 14½" deep × 50½" high.

WHAT YOU'LL NEED



- **Materials:** ¾" red oak boards, and ¼" and ¾" red oak-veneer plywood.
- **Blade and bits:** Dado set, ⅜" round-over bit, ¼" straight bit, ⅜" cove bit, rabbeting bit, ⅜" core box bit.

page 58.) Jigsaw the curve on the waste side and sand to the line.

5 Double-face-tape the unmounted narrow front trim (D) to the bottom of the bottom panel assembly [**Photo B**], and trace the curve. Remove the front trim, jigsaw 1/16" from the line on the waste side, and retape the trim to the assembly. With a bottom-bearing pattern bit, rout the trim flush [**Photo C**].

6 Rip two ¼"-wide spacer strips from ¾" MDF about 36" long. Bend and tape both tight against the curved edge of the bottom panel assembly (A/B/D) [**Photo D**]. Center the bottom panel

1 EXPLODED VIEW



FIRST CURVE ACTS AS A TEMPLATE



To save time, use the curve on the bottom panel assembly (A/B/D) to trace and rout the identical curve on the narrow front trim (D).

2 NARROW FRONT TRIM



PATTERN-ROUT FRONT TRIM



The pattern-bit bearing rides against the bottom panel assembly (A/B/D) to rout a matching curve on the narrow front trim (D).

SHOP TIP

Trace smooth curves using a fairing stick

To draw a consistent curve on the narrow front trim (D), use a fairing stick made from medium-density fiberboard. (MDF bends evenly and easily because it has no grain.) First rip a ⅜"-wide strip of ¾" MDF about 36" long. Place clamps on the narrow front trim so the inside edge of the fairing stick aligns with the end marks. At the centerline, pull the fairing stick to the center layout mark, and hold it in place. Then trace a curve along the inside edge.

3 TOP AND BOTTOM TRIM DETAIL



4 FRONT TRIM ASSEMBLY DETAIL



assembly on the top panel assembly (A/C/E), and trace the curve on the top panel assembly.

7 Separate the top (A/C/E) and bottom (A/B/D) panel assemblies, and jigsaw the top-panel curve on the waste side. Double-face tape it to the bottom panel assembly, and pattern-rout the curve on the top panel assembly flush with the spacer strips. Then remove the strips.

8 Double-face-tape the loose wide front trim piece (E) to the wide front trim piece of the top panel assembly (A/C/E). Trace the curve, jigsaw it, and rout the curve flush as you did in **Step 5**.

9 Double-face-tape the narrow front trim (D) to the top panel assembly (A/C/E) and the wide front trim (E) to the bottom panel assembly (A/B/D) as they'll look on the finished case [**Drawing 1**]. Rout cove profiles on the wide front trim, including the unmounted end trim (C). Rout round-overs on the narrow front trim [**Drawing 3**] and end trim (B). Sand all parts to 220 grit.

Machine the side parts

1 Cut the rear stiles (F) to size. Cut the front stiles (G) and the face stiles (H) ¼" wider than listed. Save some scrap the same width and thickness as the front stiles and face stiles for test cuts.

2 Tilt your tablesaw blade 13° from vertical, and rip one edge of both test pieces. Stand the scraps on end ⅛" from the edges of the routed profile at a corner of the bottom panel assembly (A/B/D) [**Photo E**]. If the test piece representing the face stile (H) doesn't match the angle of the curve in the narrow front trim (D), adjust the tablesaw blade angle, and make new test cuts until it does. Bevel-rip the front edge of each front stile (G) and both parallel edges of the face stiles [**Drawing 4**] to width.

3 To rout flutes in the face stiles (H), install a ⅜" core box bit (also called a roundnose bit) in your table-mounted router, and adjust it to cut 3/16" above the router-table top. (If you don't have a router table, make the simple router table and fence shown on *page 6*.) Set the fence to center a flute on the front of the face stile, and rout a flute [**Photo F**]. Repeat for the other face stile.

4 Adjust the fence, and rout flutes on both sides of the center flute on both face stiles (H) [**Drawing 4**].

5 Cut the side rails (I) to size. (Save some scraps the same thickness as the side rails.) Install a ¼" straight bit in

MARK AN OFFSET CURVE



Taping two ¼" strips to the narrow front trim (D) makes it easy to trace, cut, and pattern-rout mating curves on the wide front trim (E).

TEST BEVEL ANGLES ON SCRAP



With the beveled test pieces taped together, check that the ends parallel the edges of the routed profile on the bottom panel assembly.

ROUT THE CENTER FLUTE FIRST



Keep the point of the beveled edge on the face stile (H) firmly against the router-table fence as you rout each flute.

your table-mounted router, and adjust it to cut ⅜" deep. Attach a hardboard auxiliary fence to the router-table fence for a smooth surface, and use side-rail scraps to test and adjust the fence position until the groove is centered on the thickness of the scraps [**Photo G**].

6 Attach a stop to the router-table auxiliary fence 2½" from the bit center. Using a pushpad, rout a groove at both ends of each side rail (I) [**Photo H**] and on the inside edges of the rear stiles (F) and front side stiles (G) [**Drawing 5**]. Leave your router table set up this way, without the stopblocks, for the shelves.

7 Cut the shelf back rails (N) to size. Then cut 3½"-wide blanks to length for each pair of shelf sides (O), and cut the shelf front rails (P) ¼" oversize in width. Using the router-table setup from **Step 6**, rout ⅜"-deep centered grooves on the inside edges of the shelf back rails and front rails [**Drawing 7**].

8 Use a pushpad and backer block to rout grooves in the ends and then the edges of the shelf side blanks (O). With the grooved edges against the fence, rip the blanks to width [**Drawing 7**]. Then set them aside.

9 Lay out and drill shelf-pin holes in the rear and front stiles (F, G) [**Drawing 5**]. We used a handheld drill with the bit taped ⅜" from the tip as a depth stop. (Watch a free video on drilling shelf-pin holes at woodmagazine.com/videos.)

Assemble the sides

1 Make three ¾×2½×4" scrapwood alignment blocks, and cover one face of each with clear packing tape. Double-face-tape the covered face of the blocks to the outside face of a front stile (G) near the ends and middle to keep the glue-up from slipping as it's clamped. Then glue and clamp a face stile (H) to a front side stile [**Photo I**]. Repeat for the other front stile and face stile.

2 Rip spline blanks (J) ¼" wide from ¾" hardwood. From one blank, cut eight splines 2½" long. Set aside the remaining blanks.

3 Glue and insert splines (J) into the ends of the side rails (I). Then glue

5 RIGHT SIDE ASSEMBLY (Viewed from inside)





To test for a centered groove, rout test passes in two scraps. Turn one scrap upside down, and check whether the grooves align.



Double-face-tape an auxiliary fence to the router-table fence to keep the side rail (I) ends from catching as you rout.



Alignment blocks taped to the front stile (G) keep it from sliding out of position. Packing tape on the block keeps glue from sticking.



Splines help align the stiles (F, G) with the rails (I) during assembly. Use clamps with padded faces to avoid marring the surfaces.

Clamp the side assemblies to the bottom panel assembly (A/B/D) on a flat surface to avoid twisting the case.

and clamp the side rails between the rear stile (F) and front face stile (G/H) [**Photo J**]. Repeat for the other side.

Complete the case

1 Glue and clamp a narrow end trim piece (B) with its inside edge flush with the inside face and the back of a side assembly (F/G/H/I) [**Drawing 1**]. Repeat for the other side assembly.

2 Glue and clamp the side assemblies to the bottom panel assembly, leaving a ⅛" reveal from the routed profile [**Drawing 4**, **Photo K**].

3 Glue and clamp the narrow front trim (D) to the side assemblies and narrow end trim (B) [**Drawing 1**].

4 Glue and clamp the top panel assembly to the narrow end trim (B) and narrow front trim (D) [**Photo L**]. Then glue and clamp the wide end trim (C) and the wide front trim (E) to the bottom panel assembly, with the end trim inside edges flush with the narrow end trim (B) edge.

5 Mount an auxiliary router base, as shown in the **Shop Tip**, *opposite top*, and rout a ⅜" rabbet ¼" deep in the inside edges of the rear stiles (F) and the top and bottom panel assemblies.

6 Cut the back (K) to fit the rabbeted opening. Then use a jigsaw and sanding block to round the corners. Drill and screw the back in place. (For the #8 screws, drill 5/32" shank holes and 7/64" pilot holes.)

7 Laminate two pieces of ¾×4×12" oak to make a 1½"-thick blank for the front (L) and back (M) feet. Cut the feet to size and shape [**Drawings 1** and **6**].

8 Glue and clamp the front feet (L) and back feet (M) ⅛" from the edges of the bottom wide end trim (C) and wide front trim (E).

Now make three shelves

1 Cut splines (J) the length of the shelf back rails (N) and shelf front rails (P). Glue and clamp splines into the grooves in the rails [**Drawing 7**].

2 Glue and clamp the shelf back rails (N), shelf sides (O), and shelf front rails (P) [**Drawing 7**]. After the glue dries, cut splines to fit the shelf-side grooves. Center, glue, and clamp them in place.

6 FRONT FOOT



3 Use a fairing stick to mark the curve [**Drawing 7**] on one shelf front (P) on the assembled shelf frame (N/O/P). Jigsaw on the waste side, and sand to the

7 SHELF



ADD THE TOP PANEL ASSEMBLY

Glue and clamp the top panel assembly centered between the narrow end trim (B) on the side assemblies.

SHOP TIP

No tipping allowed

Rabbeting a ¾"-wide edge can leave bumps and gouges if the router wobbles. Stabilize it with a ¾×6×48" auxiliary base that rests on opposite edges of the case. Drill a centered 1½"-diameter bit hole in from one end a distance half the width of your router base. Use the same method as for mounting a router in the shop-built table on *page 6* to mount it on the auxiliary base. Now your router will feel like it's supported on a tabletop, not a tightrope.

line. Trace the curved-front shelf onto the other two shelf frames, then jigsaw on the waste side, and pattern-rout the curves to match the first shelf.

4 Insert a ⅜" cove bit into a handheld router, and rout the bottom front edge of each shelf front rail (P). Then cut ¼" glass panels to fit within the shelf frame resting on the splines (J).

5 Remove the back and shelves from the case and the glass from the shelves, then finish-sand all parts to 220 grit. Apply stain (we used Varathane Mission Oak) and three coats of satin polyurethane. Sand with 320-grit abrasive between coats. Now you're ready to show off your keepsakes and your improved woodworking skills.

Written by **Bob Wilson** with **Jeff Mertz**
Project design: **Jeff Mertz**
Illustrations: **Roxanne LeMoine**; **Lorna Johnson**

Basic-Built projects require only a limited number of inexpensive and readily available tools and materials. For more information, go to woodmagazine.com/basicbuilt

Cutting Diagram



¾ x 7¼ x 96" Oak (5.3 bd. ft.)



¾ x 7¼ x 96" Oak (5.3 bd. ft.)



¾ x 7¼ x 96" Oak (5.3 bd. ft.)

¾ x 3½ x 96" Oak (2.7 bd. ft.)



¾ x 24 x 48" Oak plywood



¼ x 48 x 48" Oak plywood

Materials List

		FINISHED SIZE T	W	L	Matl.	Qty.
Carcase						
A	top/bottom panels	¾"	11¼"	26½"	OP	2
B	narrow end trim	¾"	1¼"	11¼"	O	4
C	wide end trim	¾"	1¾"	11¼"	O	4
D*	narrow front trim	¾"	3"	29"	O	2
E*	wide front trim	¾"	3⅜"	30"	O	2
F	rear stiles	¾"	2¼"	46"	O	2
G*	front stiles	¾"	1 11/16"	46"	O	2
H*	face stiles	¾"	2⅜"	46"	O	2
I	side rails	¾"	3"	7"	O	4
J	spline blanks	¼"	¾"	36"	O	7
K*	back	¼"	27¼"	47½"	OP	1
L*	front feet	1½"	3¾"	3"	LO	2
M*	back feet	1½"	1¾"	2¼"	LO	2
Shelves (3)						
N	shelf back rails	¾"	1½"	26⅜"	O	3
O*	shelf sides	¾"	1½"	8"	O	6
P*	shelf front rails	¾"	3"	26⅜"	O	3

*Parts initially cut oversize. See the instructions.

Materials key: OP–oak-veneer plywood , O–oak, LO–laminated oak.
Supplies: ¼×7⅞×23¼" glass (3), shelf supports (12), #8×¾" flathead wood screws.

22 All-time Top Shop Tips

Some of our most helpful advice comes from you, our readers.

If football is a game of inches, woodworking is a game of fractions where you measure success in sixty-fourths of an inch. And any technique or jig that increases accuracy or efficiency brings you one step closer to success.

From the thousands of Shop Tips that *WOOD®* magazine has published during the past 24 years, our editorial staff picked out the cream of the crop. Then we added fresh ideas to make them even better ways to:

- create shop-made jigs
- ease cabinet construction
- avoid goofs
- work around problems or the limitations of your tools.

Handy Homemade Helpers

Keep right angles right

You'll never again guess the squareness of an assembly if you use these right-angle clamping blocks. They ensure a 90° alignment, as shown *below left*. Start by cutting 12" squares of ¾" Baltic birch plywood and dividing them diagonally. Then cut notches for the clamps, as shown *below center*. You can vary the sizes to suit larger or smaller projects.

Blocks help with more than glue-ups. Clamp a pair to a chest, as shown *below*, as a support to install hinges.







Rip thin strips reliably

Safely ripping uniformly thin strips on a tablesaw involves making a cut, resetting the fence, and making the next cut. This jig eliminates the hard part: moving the fence precisely the same distance after each cut.

Build the jig from ¾" plywood with a hardwood miter-slot runner attached to its bottom, as shown *right*. Drill a 7/16" hole 2" deep centered along one edge of the plywood, and epoxy a ¼" nylon-insert lock nut inside the hole. After the epoxy cures, thread a 2"-long ¼"-20 roundhead machine screw.

Place the jig in your tablesaw's miter slot and turn the machine screw until the distance between the screwhead and the saw blade equals the width of the strips you want. Sandwich a blank between the rip fence and the screwhead, lock the fence, remove the jig, and rip the strip. Then return the jig to the miter slot and repeat until your blank gets too narrow to cut safely using push-sticks, usually about ¾".



Square makes a quick and easy stop

To consistently position a hole in multiple workpieces, clamp a framing square to your drill-press table. The two legs of the square act as both a fence and stop. Squares don't come with dust-relief grooves, though, so blow away chips and dust after each hole to prevent debris from becoming trapped between your workpiece and the square.



Conquer curves with a fairing stick

An adjustable string tensions this bow-like tool to create smooth arcs with ease. Unlike the super-simple fairing stick on *page 60*, this one doesn't need to be clamped in place to hold its arc.

To make one, cut a ¾"-wide piece of ⅛" tempered hardboard and assemble it as shown *right*. The ones in our shop range from 2' to 3' long. For fairing sticks longer than 3', make the width about 1½". To use the fairing stick, mark the curve endpoints and midpoint. Bow the stick, sliding the toggle along the string until the curve touches the midpoint and both endpoints. Hold the stick firmly against the workpiece and trace the curve. When you're finished, release the tension on the stick.



Note: All holes are ⅛" diameter, located ¼" from ends of piece.

Add clamping jigs for less slip, more grip

Juggling two pairs of clamps to glue a mitered frame can end in frustration. With these jigs, however, one set of clamps squares the frame.



To make a pair, rip two pieces of ¾"-thick scrap ½" wider than the thickness of the frame parts and 3" longer than the frame sides, as shown *right*. Then install a ¾" dado blade, and adjust it to cut a dado ⅛" shallower than the thickness of the frame parts. With the jig pieces taped together on edge, cut dadoes where illustrated at *left*.

To use the jigs, glue the miters and assemble the frame flat on a workbench, aligning the corners with a framing square. (Protect the workbench with a plastic trash bag.) Position the jigs close to the inside corners, capturing the frame ends in the dadoes. Now clamp the frame sides, as shown *below*, while the jigs hold the short frame members in place.



Case and Cabinet Accuracy Aids

6 Hold cabinet parts upright

If you've tried standing cabinet parts on edge only to see them topple like a house of cards, check out these scrapwood workholders. Slide one of the two uprights into the base, prop a panel on edge against it, then slide the other upright against your workpiece to hold it while you assemble the project. You can flip the uprights around, as shown *right*, slide two together in the base, and use the angled edges to hold work at a 45° angle, when making a corner cabinet, for example.




45°
#8 x 1½" F.H. wood screw
¾ x 7 x 10" plywood (upright)
#8 x 1" F.H. wood screw, countersunk
1 x 1⅜ x 16" hardwood
½" rabbets ⅝" deep
½ x 1⅞ x 7" plywood
2x4 16" long (base)

7 Turn scraps into gauge blocks and spacers

When mounting hardware, such as hinges and drawer slides, there's more than one way to ensure accuracy. To mount upper and lower hinges consistently on several doors, use a gauge block, as shown *below left*. You'll need one for the door frame and another that's 1/16" longer (to allow for the reveal) for the case frame, as shown *below*.





8

To accurately space drawer slides on both sides of a case, use a panel scrap. Start by cutting a scrap spacer for mounting the uppermost slides. Then drill mounting-screw holes, and attach the slides, as shown *below*. Now cut the spacer to length for the next highest group of slides, and repeat.



9 Make bookcase biscuits a breeze every time

Transfer biscuit locations accurately from a case side to a shelf end using this custom T-square. Assemble it from medium-density fiberboard (MDF) or melamine-covered particleboard scraps to make pencil marks easy to erase. Mark the biscuit location centerlines on the long leg of the square.

To use the square, clamp it to a shelf, as shown *right*, with the short leg against the front edge, and use the lines to cut biscuit slots on the shelf ends. Then clamp the square to the case side with the short leg against the front edge. Using the same centerlines, cut slots on the inside face of each case side.





Goof Blockers

10 A close shave with no nicks

Wooden plugs provide easy concealment for screws, but cutting the plugs flush without marring the surrounding wood can be tricky. For a clean cut, reuse a worn-out sanding disc, as shown *right*. With the abrasive side down, slip the exposed plug through one of the holes in the sanding disc. Then saw the plug flush with the disc. There'll be a little extra left above the surface, but it's easier to sand that away than saw marks.



11 Scoring cut skips the chips

If both faces of a veneer plywood will be visible on your project, minimize chip-out on each side by dividing the cut. First make a shallow scoring cut 1/16" to 1/8" deep, as shown *below*. Then raise the blade, and make another pass to cut completely through the workpiece.

12 Trap glue squeeze-out

Glue globs and surface smears will mar a finish, especially when you're applying stain. Stop the problem before it starts on face-to-face joints by cutting 1/8"-deep saw kerfs about 1/8" from both edges, as shown *right*. Apply glue only between the kerfs and, as you press the two parts together, any squeeze-out will flow into the kerfs. If the ends will be visible in the completed project, use a table-mounted router and a 1/8" straight bit to make stopped grooves.

13 Keep glue smears from marring joints

Glue kerfs solve face-to-face glue-up problems, but mortise-and-tenon joints require another strategy. For joints like the one shown *right*, dry-assemble the joint, and tape the mortised piece around the tenon piece using masking tape or blue painter's tape. Then tape the tenon part next to the joint. Glue, assemble, and clamp the joint, making sure no squeeze-out drips off the tape.

For dowel tenons in round holes, first tape over the mortise and cut away the tape over the hole, as shown *far right*. Insert the dowel or round tenon, and tape where it meets the surface of the mortised piece. Then glue and assemble the joint. In both instances, wait until the glue dries before pulling off the tape and finishing your project.



Problem-Solvers

14 Here's the skinny on planing thin stock

Most planer manufacturers don't recommend planing stock less than ½" thick and 12" long because of the risk of it breaking. To safely work around these limits, piggyback the workpiece to a flat ¾" carrier board, as shown *right*. The carrier board should be at least as wide as and 2" longer than your workpiece. Using this technique, you can safely plane wood to 1/16" thick. To remove wood that thin from the carrier, gently pry it off using a putty knife starting at the ends. If the piece becomes too fragile to pry, dissolve the tape adhesive with lacquer thinner.



15 Tape your way to tight glue joints

Assembling boxes with more than four sides presents a clamping challenge. Here's an easy alternative: First lay out the box pieces with the top or bottom edge against a straightedge and the outside corners touching. Use masking tape to pull the outside edges tightly together, as shown *below top*. Next apply glue, and roll the segments around the base, as shown *below*. Tape the beginning and end segments, apply pressure with a band clamp, if necessary, and allow the assembly to dry on a flat surface.



16 Make a portable drill as accurate as a drill press

Even if you own only a portable drill or your drill-press table can't accommodate a large workpiece, you can drill 90° holes using this easy-to-make right-angle jig. Build one by joining two scrap blocks at 90°. Place the tip of the bit where you want the hole, slide the jig against the bit as you straighten it, and bore your perpendicular hole, as shown *right*. If you need to drill deeper than the right-angle jig allows, drill the hole as far as possible using the jig, remove the jig, and drill further, guided by the hole already drilled.



17 Make on-the-mark cuts with your circular saw

Faster to set up and more accurate than a Speed Square, the cutoff jig *below* was designed for 6" boards. But you can increase the width for larger workpieces, or angle the fence and enlarge the jig to make 45° cuts.

To make one, measure the distance from the edge of the widest portion of your circular-saw base to the blade, add ¼", and mount the fence that dimension from one end of the base. Then use your circular saw with the base against the fence to trim the jig end to final length.

To use the jig, clamp it with the stop against the workpiece edge and the right end of the jig aligned with your cutline. Hold the saw-base edge against the fence as you cut, as shown *above right*.





18 Square makes a fast fence

If your bandsaw didn't come with a fence, substitute a Speed Square. With the square's flange against the front edge of the bandsaw table, clamp it in place where you want to begin your cut. These squares cost only a few dollars, and their thickness provides enough edge to guide workpieces lying flat.

19 Give solid edge bands that clean-cut look

Trimming solid-wood edge bands on plywood shelves can leave handsaw scratches or rounded edges from sanding. Instead make a spacer block with parallel edges. Then set your tablesaw fence to remove just a whisker more than the blade width from the end of one edge.

Without moving the fence, lay the spacer block between the fence and a piece of test scrap. Push both a couple of inches into the blade. If the scrap touches the blade, move the fence a hair closer to the blade, and make a second test cut. Once the scrap clears the blade, place your shelf edge against the spacer block, as shown *below*, and push both just far enough into the blade to remove the edge banding. Sand off any that's left.



20 Cut big panels down to size

Wrestling with 4×8 panels in a small shop can be a losing battle. Here's a way to cut them before taking them into your shop. First make a straightedge using the factory-cut edge of a 10"-wide scrap of plywood or medium-density fiberboard. Next lay the panel on a sheet of rigid foam insulation at least 1" thick. Measure from the saw-base edge to the blade, and clamp your straightedge that distance from the cutline. Clamp the guide in place; set the blade cutting depth to penetrate ¼" into the foam insulation, and then make the cut, as shown *right*.

21 Cut to the chase

Here's a quick, accurate way to make a freehand squaring cut on your bandsaw, as you would for a turning blank. After making a tick mark to indicate the cutline, and with your bandsaw table 90° to the blade, cut a shallow kerf at your tick mark. Then rotate the stock a quarter turn so the kerf is on top, and cut along the kerf—no drawing, no square, and no miter gauge.



22 Rip thin stock safely with a zero-clearance tabletop

You'll cut thin stock with less tear-out on a saw with a zero-clearance insert. But there's an easier way to get the same results while raising the workpiece enough to keep it from sliding under the fence. This tip also works great for cutting thin sheet brass.

First cut a piece of ¼" medium-density fiberboard or hardboard large enough to cover the saw table from front to back and wide enough to support your workpiece. Position the fence for the cut, and lower the blade beneath the tabletop. Then double-face tape the hardboard to the saw table with one edge against the fence.

Start the saw and gradually raise the blade through the zero-clearance top to the correct height. Always use pushsticks to control stock narrower than 2".

Did we miss one?

Do you know a tip that's as good as or better than these? If so, send your tip and contact information to **Shop Tips, *WOOD* magazine, 1716 Locust St., LS-221, Des Moines, IA 50309-3023**. Or e-mail us at shoptips@woodmagazine.com and include your contact information. You might earn $100 or a valuable tool prize.



Calendar Keeper

Make any calendar look right at home in this simple but elegant frame.

No matter how beautiful its photographs, a calendar invariably looks "tacked up" when stuck to a wall or refrigerator. This frame solves that problem, with style to spare. To ramp up the fun factor, it includes a variety of scrollsawn magnet-backed icons for marking family holidays and events. They stick to a steel plate behind the calendar.

Mark important dates and events with magnetic scrollsawn icons. They store in a hinged compartment below the calendar.

First, make the frame

We sized our frame to fit a 12×11" calendar that measures 12×22" when open. Find your calendar, measure it, and adjust any part sizes as necessary before you start building.

1 Cut the frame stiles (A), top rail (B), and bottom rail (C) to size [**Materials List**, *page 70*], as well as some scrap stock matching the thickness of the stiles and rails. Install a ¾" dado set on your tablesaw and adjust its height to cut half-lap joints, testing your settings in the scrap. After installing an auxiliary face on the rip fence, cut 1" rabbets at one end of the stiles [**Drawing 1**]. Reset the fence and cut 3¼" rabbets at the other end of the stiles. Reposition the fence again, and cut 1½" rabbets on both ends of the top and bottom rails. Glue and clamp the frame, and remove any glue squeeze-out [**Photo A**].

2 Rout a ¼" rabbet ½" deep on the inside edge of the back face of the frame assembly (A/B/C). To reduce tearout, cut the rabbet in progressively deeper passes until reaching the final depth. Square the corners of the rabbet [**Photo B**], then finish-sand the frame.

3 Cut the top (D) to size. Chuck a ½" cove bit into your table-mounted router, and form a cove on the ends and front edge [**Drawing 1**]. Finish-sand the top. Glue and clamp the top to the top rail (B), with the back edges flush and centered from side to side.

Build the storage box

1 Cut a blank 2⅝×35" from ⅜" stock for the box front (E), sides (F), and bottom (G). Then, cut the front and sides to length and final width. Machine the grooves in the sides and the rabbets on the front [**Drawing 2**]. Cut the bottom (G) to length. Now, glue and clamp the box together, with the ends and edges flush. Remove any glue squeeze-out, and set aside to dry.

SPACERS EASE CLAMPING



Elevate the frame on spacers to provide clamp clearance. Glue and clamp the frame, checking for square.

CHISELS MAKE SQUARE CORRECTS



Use a sharp chisel to square up the rabbeted corners. Take small bites with the chisel for the cleanest results.

CUT ALIGNED HINGE MORTISES



To cut the hinge mortises, use a dado blade, and attach a backer board to your miter gauge to prevent tear-out.



1 EXPLODED VIEW

2 Cut the lid support (H) and lid (I) to size. Using double-faced tape, attach the lid support to the lid, with one edge and the ends flush. Lay out the locations of the hinge mortises [**Drawing 2**], and place painter's tape at the marks to aid in visibility [**Photo C**]. Cut the mortises.

3 Chuck a ⅛" round-over bit into your table-mounted router, and rout the round-overs on the box assembly (E/F/G), lid support (H), and lid (I) [**Drawing 2**]. Finish-sand the parts.

4 Glue and clamp the box assembly (E/F/G) to the bottom rail (C) and stiles (A). Center the box from side to side, with the bottom edges flush.

5 Position the hinges in the lid-support (H) mortises, with the leaf flush with the bottom edge. Mark and drill 5/64" pilot holes. Repeat this procedure for the lid (I). To prevent breaking the soft brass screws later, first mount the hinges using #4 steel screws. Remove the hinges, and glue the lid support to the box assembly (E/F/G), with their back edges flush. Set the lid aside for now.





To cut the metal backer, sandwich it between the two backs (J), and clamp the pieces to the workbench. Cut along the plywood edge.

Add the back

1 Cut two pieces of ¼" birch plywood to 12⅝×10⅞" for the backs (J).

2 To form the metal backer, first sand both faces of a piece of 23-gauge steel using 320-grit sandpaper. Clean the surfaces with acetone to remove any oily residue and metal dust. Using heavy-duty spray adhesive, attach one back (J) to the steel, with two adjacent edges flush. Clamp the back and steel together, and allow to cure for 30 minutes.

3 Retrieve the other back (J), and position it (don't glue it) on the opposite side of the metal backer flush with the edges. Clamp this plywood/steel/plywood sandwich to the corner of your workbench, with the steel overhanging the edges [**Photo D**]. Using a jigsaw with a metal-cutting blade, cut the metal following along the edge of the back (J). Sandwiching the metal this way makes for a smoother, more controlled cut.

4 Remove the unglued back (J) from the sandwich. Sand any burrs from the edge of the metal backer, and apply a coat of satin aerosol lacquer to the metal surface. Glue and clamp the upper back to the rabbet on the back of the frame (A/B/C), making sure it is tight against the rabbet on the top rail (B) [**Drawing 1**]. Cut the back support (K) to size, and glue and clamp it in place. Cut the back stops (L) to size. Place the lower back (J) into the rabbet, with the bottom edge tight against the rabbet in the bottom rail (C), leaving a gap between the two backs. Glue and clamp the back stops in place.

5 Finish-sand, and apply three coats of aerosol lacquer, lightly sanding between coats with a 320-grit sanding sponge. Reattach the hinges using brass screws, and add the sawtooth hangers to the back of the top rail (B) [**Drawing 1**]. To hold your calendar in place, screw in a ½" L-hook.

Next: decorative magnets

1 Make a photocopy of the calendar icons in the *WOOD Patterns*® insert, and adhere it to ⅛" stock. (We used hard maple for its durability.) Cut out the icons using a #2 blade in your scrollsaw. Finish-sand the icons, and apply a clear finish. (We used an aerosol lacquer.)

2 Attach a ½×½" piece of self-adhesive magnetic tape to the back of each icon, and you're ready to mark time in a decorative way. For the best performance of the magnets, slide the pages of past months through the slot in the center of the frame so the magnets have to pull through only one layer of paper.

Written by **Kevin Boyle** with **Jeff Mertz**
Project design: **Kevin Boyle**
Illustrations: **Roxanne LeMoine**; **Lorna Johnson**

Materials List

Part		FINISHED SIZE T	W	L	Matl.	Qty.
A	stiles	¾"	1½"	26½"	M	2
B	top rail	¾"	1"	15⅛"	M	1
C	bottom rail	¾"	3¼"	15⅛"	M	1
D	top	¾"	1¾"	16⅞"	M	1
E*	box front	⅜"	2⅛"	14⅜"	M	1
F*	box sides	⅜"	2⅛"	2¾"	M	2
G*	box bottom	⅜"	2⅝"	13⅞"	M	1
H	lid support	⅜"	½"	15⅛"	M	1
I	box lid	⅜"	2¾"	15⅛"	M	1
J	backs	¼"	12⅝"	10⅞"	BP	2
K	back support	¼"	2"	12⅝"	M	1
L	back stops	¼"	¼"	20¾"	M	2
M*	scrollsaw blank	⅛"	2"	20"	M	1

*Parts initially cut oversize. See the instructions.

Materials key: M–maple, BP–birch plywood.
Supplies: Double-faced tape, spray adhesive, ⅜x1" brass hinges (2), sawtooth hangers (2), 10⅞×12⅝" 23-gauge steel, #4×1" flathead wood screws, ½" L-hook, self-adhesive magnetic tape.
Blades and bits: ⅛" round-over, ½" cove, and rabbeting router bits; dado set; metal-cutting jigsaw blade; #2 scrollsaw blade.

Cutting Diagram



¼ x 24 x 48" Birch plywood



¾ x 5½ x 96" Maple (4 bd. ft.)
*Plane or resaw to the thicknesses listed in the Materials List.

MLCSwoodworking.com...

Free "Online Videos" show you how to rout it, join it, and build it.

"Hide the Ply"

The Edge Banding router bit set adds an attractive edge to plywood panel doors and shelves. Two piece, carbide tipped, 1/2" shank.

#1475 - T & G $44.95
#1474 - 90° $39.95

"Custom Made Doors"

Our Mitered Door Frame Kit creates elegant Rail & Stile Doors. Includes 1/2" shank carbide tipped Profile Router Bit, 1/4" & 5/32" Slot Cutter bits & 100 #11 biscuits.

Item #1480.....$79.95

"Portable Versatility"

The Marvel 40 3-In-1 Router Kit is a 1 HP Router, Laminate Trimmer & Cut-Out Tool with 1/4" & 1/8" collets, 3 bases, straight edge, and circle cutter.

Item #1478 .....$89.95

"Classic Strength"

Make strong Half Blind 1/2" Dovetail Joints. Our set includes a solid Aluminum Template, 12" Steel Jig, and a carbide tipped 1/4" or 1/2" shank Dovetail Router Bit.

1/4" shank • #1483 | 1/2" shank • #1484.....$59.95

"Beauty-In-Utility"

The Shaker Cabinetmaker Router Bit Set makes professional Raised Panel Doors and Drawers. Five piece, carbide tipped, 1/2" shank.

Item #1485.....$114.95

ONLINE VIDEO

1-800-533-9298
PROFESSIONAL ROUTER BITS & WOODWORKING PRODUCTS

MLCS

FREE SHIPPING!
IN CONTIGUOUS USA • P.O. BOX 4053DA, RYDAL PA, 19046 *2008

Circle No. 245

WOODWorkersCenter.com

FREE Product Information from Advertisers in This Issue

Looking for FREE product information? Fill out the coupon in this section to receive FREE product info and catalogs. Or, for quicker service and instant access to information, visit us online at www.woodworkerscenter.com

Adhesives & Finishes

DONJER PRODUCTS CORPORATION Spray-on suede. Line boxes in seconds. No skill required. **Circle No. 17.**

TITEBOND® III ULTIMATE WOOD GLUE Superior bond strength, waterproof, longer open-assembly time. The Best Wood Glue Ever! **Circle No. 24.**

THE GORILLA GLUE COMPANY Bonds wood, stone, metal, ceramic, and more. Incredibly strong — 100% waterproof. **Circle No. 50.**

UNITED GILSONITE LABORATORIES Finishing Touch Brochure — guide for best results using ZAR Wood Stain/Finishes. **Circle No. 128.**

UNITED GILSONITE LABORATORIES Hardwood Floor Guide — step-by-step finishing instructions using ZAR Wood Stain/Finishes. **Circle No. 154.**

Bits, Blades, Cutting Tools

CARTER PRODUCTS COMPANY, INC. AccuRight Bandsaw Blades — length 72" to 136", widths 1/8" to 1". **Circle No. 176.**

DISPOZ-A-BLADE Self-setting German quality jointer/planer double-edged knives. **Circle No. 188.**

DOVETAIL MASTER Create dovetail joints incredibly fast & easy; innovative, new tool design. **Circle No. 190.**

FLEXCUT CUTTING TOOLS Carving tools for every need. **Circle No. 195.**

FORREST MFG. CO., INC. Top quality blades and dados for an ultra smooth finish. **Circle No. 206.**

FREUD SAW BLADES This 48-page catalog illustrates the features and benefits for all Freud saw blades. **Circle No. 219.**

FREUD ROUTER BITS All Freud router bits are represented in this 84-page catalog, including more than 130 new bits and sets. **Circle No. 232.**

INFINITY CUTTING TOOLS Premium quality router bits/sets, shaper cutters, saw blades, planer/jointer knives. **Circle No. 235.**

MLCS WOODWORKING Best quality, huge selection, low prices, superior service. Free Shipping! **Circle No. 245.**

SOMMERFELD'S TOOLS FOR WOOD Router Bits, Blades, Tools and Tips. FREE catalog & shipping! **Circle No. 284.**

Books, Plans and Videos

AMERICAN FURNITURE DESIGN CO. 150 of America's best furniture plans, comprehensive instruction guide. Catalog. **Circle No. 336.**

MEISEL HARDWARE SPECIALTIES CATALOG 2,000+ full-size project plans and hard-to-find hardware. **Circle No. 401.**

U-BILD WOODWORKING PLANS Since 1948! Hundreds of full-size plans, downloadable plans, low prices. **Circle No. 435.**

General Woodworking Catalogs

ARMOR CRAFTS Full-size plans to build cradles, rocking horses, clocks and more. Also hardware and wood craft supplies. **Circle No. 556.**

THE BEALL TOOL COMPANY Inventive solutions for shop problems: wood threading, buffing & more. **Circle No. 558.**

GRIZZLY INDUSTRIAL, INC. 12,000 woodworking and metalworking machines, tools and accessories — unbeatable prices! **Circle No. 583.**

HARTVILLE TOOL CATALOG Quality woodworking tools and supplies at the best prices around. **Circle No. 596.**

MITERSET.COM Adjust your original equipment miter gauge in .5 degree increments. **Circle No. 650.**

PEACHTREE WOODWORKING SUPPLY "Your One Stop Supply Shop"—over 4,000 items. **Circle No. 654.**

ROCKLER WOODWORKING & HARDWARE Our premium tools make woodworking efficient and enjoyable. FREE Catalog. **Circle No. 661.**

WOODCRAFT SUPPLY CORP. Over 15,000 top quality woodworking tools, supplies, and accessories. **Circle No. 700.**

WOODWORKERS HARDWARE Over 8,000 items stocked. Largest selection of cabinetmakers hardware. Lowest prices. **Circle No. 713.**

Hand Tools, Jigs & Clamps

ADJUSTABLE CLAMP COMPANY Adjustable Clamp Company manufactures a full line of woodworking clamps, miter saws and vises. **Circle No. 733.**

BESSEY TOOLS NORTH AMERICA German company that manufactures over 1,500 clamping and cutting tools. **Circle No. 745.**

KREG TOOL CO. Your one stop shop for everything Pocket-Screw related. **Circle No. 802.**

LOWELL THOMAS TOOLS/ALPHA CLAMPS New Generation bar clamp does what other clamps can't. **Circle No. 806.**

DOWELMAX JOINT-MAKING SYSTEM Dowelmax creates joints which are quick, easy, accurate, and strong. **Circle No. 825.**

TOOLS FOR WORKING WOOD Our 100-page catalog has some of the finest woodworking tools available today. **Circle No. 830.**

Hardwood & Lumber

CURIOUS WOODS Superior quality hardwoods, for superior results. Domestic and Exotics. **Circle No. 842.**

STEVE H. WALL LUMBER CO. Quality hardwoods, plywood, exotic lumber. Ship UPS/motor freight, wholesale prices. **Circle No. 856.**

WOODWORKERS SOURCE Hardwoods from around the world. **Circle No. 869.**

Income Opportunities & Education

WOODCRAFT RETAIL FRANCHISE Own a Woodcraft Store — franchises offered for stores across the country. **Circle No. 924.**

Kits

KLOCKIT The leading supplier of clock-making supplies for over 35 years! **Circle No. 973.**

Miscellaneous

AZTEC STEEL CORP. Quality pre-engineered arch-style steel buildings at the lowest cost anywhere. **Circle No. 1064.**

CENTRAL BOILER Classic Wood Furnaces – clean, safe, efficient heat for your home. **Circle No. 1105.**

DAKOTA ALERT, INC. An alert sounds in the house when someone enters the drive. **Circle No. 1129.**

RADIANT FLOOR COMPANY Radiant Heating Systems—design, manufacture and sale for the DIY. **Circle No. 1301.**

Power Tools

CARVEWRIGHT WOODWORKING SYSTEM Computer controlled carving machine. **Circle No. 1463.**

COOK'S SAW MFG., L.L.C. Portable sawmills, Edgers, Sharpeners, Band Blades… Free catalog. Video available. **Circle No. 1480.**

DRILL DOCTOR Sharpen your dull and broken drill bits with The Drill Doctor. **Circle No. 1511.**

EPILOG Wood engraving and cutting systems — Low Price, High-Quality Laser Systems. **Circle No. 1515.**

FEIN POWER TOOLS NEW Multi-Master—one tool, a few attachments… thousands of projects. **Circle No. 1520.**

FREUD POWER TOOLS 16-page catalog illustrates dependable power tools with traditional Freud quality. **Circle No. 1532.**

GENERAL, GENERAL INTERNATIONAL AND EXCALIBUR BY GENERAL INTERNATIONAL A complete line of quality woodworking machinery & accessories. **Circle No. 1552.**

GRANBERG INTERNATIONAL Alaskan Saw Mill, chain saw accessories. Made in USA. **Circle No. 1558.**

JET SUPERSAW Cast iron wings, sliding crosscut table, micro-adjust fence. Totally enclosed cabinet. **Circle No. 1588.**

PLASMA CAM, INC. Put metal into your wood projects! Free Demo Video! **Circle No. 1641.**

WORK SHARP Sharpen your woodworking tools with the new WORK SHARP. **Circle No. 1665.**

SHOPBOT TOOLS INC. Complete CNC systems for applications in wood, plastic and metal. **Circle No. 1714.**

TOOLMART INC. Makita, DeWalt, Porter-Cable, Milwaukee, Bosch, Freud. **Circle No. 1770.**

WOOD-MIZER PRODUCTS Eight Portable Sawmills Available starting with the LT10 at $3995. **Circle No. 1805.**

Request FREE product information today. Log on to www.WOODWorkersCenter.com

WOODMASTER TOOLS Multi-duty planers that mold, sand & saw. **Circle No. 1820.**

WOODSTOCK INTERNATIONAL, INC. SHOP FOX Woodworking Machines offering professional-level quality. Dealer supplied. **Circle No. 1824.**

Project Parts & Materials

ADAMS WOOD PRODUCTS Offers a free catalog of their stock solid wood components. **Circle No. 1831.**

CABINETWORKS LTD. Wall Bed Systems—DIY hardware or the complete assembly. **Circle No. 1843.**

PIERCED TIN DESIGNS, LTD. BY COUNTRY ACCENTS Handmade punched tin—12 types of metal. Do-it-yourself supplies too. **Circle No. 1845.**

OSBORNE WOOD PRODUCTS, INC. A free catalog of table legs, corbels, and island legs. **Circle No. 1849.**

OSBORNE WOOD PRODUCTS, INC. WOOD CORBELS offer classic corbels in a broad range of styles. **Circle No. 1851.**

WILDWOOD DESIGNS SCROLLSAW PATTERNS Up to 74" clocks, 300+ patterns, books, clock parts, saw blades, tools, wood! **Circle No. 1857.**

Shop Accessories

CARTER PRODUCTS COMPANY, INC. Bandsaw Guide kits, tires, stabilizer guides, and many other products. **Circle No. 1883.**

EZEE-FEED MANUFACTURING Set up your tablesaw to cut large sheet goods in a matter of minutes. **Circle No. 1952.**

THE JDS COMPANY Specializing in the finest air filtration and dust collection equipment. **Circle No. 1974.**

LIGNOMAT USA, LTD. Affordable, reliable, pin and pinless moisture meters for wood. Free catalog. **Circle No. 2013.**

ONEIDA AIR SYSTEMS, INC. Free informative catalog contains dust collection systems and complete ductwork. **Circle No. 2039.**

PENN STATE INDUSTRIES Award-winning dust collection. Collectors, Cyclones, Ductwork and more. **Circle No. 2045.**

PHASE-A-MATIC, INC. Convert 1-phase electric power into 3-phase; run 3-phase equipment anywhere. **Circle No. 2052.**

RED HILL CORP. SUPERGRIT® ABRASIVES Industrial quality sanding belts, discs, rolls, sheets at wholesale prices to small consumers. **Circle No. 2065.**

Shop Supplies

CLEANSTREAM PRO FILTERS With CleanStream's HEPA filtration fine dust doesn't stand a chance. **Circle No. 2124.**

Woodturning Supplies

BEREA HARDWOODS Quality pen kits and other turning kits. **Circle No. 2127.**

HUT PRODUCTS Woods, acrylics and supplies for pen and game call turning. **Circle No. 2133.**

PACKARD WOODWORKS Free Catalog for WOODTURNERS! — Quality Lathes, Tools and Supplies. **Circle No. 2143.**

PENN STATE INDUSTRIES Leading supplier of Turning Products. Pen kits, project, finishes and more. **Circle No. 2151.**

Make Your Shop Better TODAY

128 pages of shop-proven tips, tricks, and jigs from the editors of *WOOD®* magazine.

On Your Newsstand NOW!

$6.99 U.S.
$8.99 Canada

Order online at **woodmagazine.com/publications**
or call toll free **888-636-4478**

WD1108

WOODWorkersCenter.com

DEPT. WON008

FREE Product Information

CIRCLE THE NUMBERS BELOW CORRESPONDING TO ITEMS IN THIS ISSUE.

17	195	336	654	825	1105	1532	1805	1857	2065
24	205	401	661	830	1129	1552	1820	1883	2124
50	206	435	700	842	1301	1558	1824	1952	2127
128	219	556	713	856	1463	1588	1831	1974	2133
154	232	558	733	869	1480	1641	1843	2013	2143
176	235	583	745	924	1511	1665	1845	2039	2151
188	245	596	802	973	1515	1714	1849	2045	4000
190	284	650	806	1064	1520	1770	1851	2052	

Discover how rewarding woodworking can be! Get one full year of WOOD® for just $28.00 (7 issues). Simply circle No. 4000. You will be billed later.

NAME _____

ADDRESS _____

CITY _____ STATE _____ ZIP _____

E-MAIL ADDRESS _____

PHONE (OPTIONAL) _____

TO ENSURE PROMPT HANDLING OF YOUR ORDER, PLEASE:
- Circle Your Choice(s) in the box above
- Send card to WOOD® Magazine, Dept. WON008, P.O. Box 5135, Buffalo, NY 14205-5135
- Allow 4-6 weeks for delivery
- This card expires April 7, 2009

ART DECO DESK CLOCK

We all have 'em: wood scraps too little to be of much use, but too beautiful to toss out. Now you can fashion those exotic or figured castoffs into a handsome timepiece.

Form the body and wings

1 Cut a ¾×3¼×3" blank for the body (A). (We used lacewood and curly maple for the clock *above*, and spalted maple and walnut for the one *opposite, top*.) Photocopy the **Body Pattern** from the *WOOD Patterns*® insert, and adhere it to the blank with spray adhesive, aligning the bottom edge of the pattern flush with the end of the blank.

2 Using a 1⅜" Forstner bit in your drill press, bore a hole ⅜" deep in the body (A) where marked on the pattern.

3 Bandsaw or scrollsaw the body (A) to just outside the pattern lines, then sand the edges to the lines.

4 To cut the stopped grooves on the sides of the body (A), install a ¼" straight bit in a table-mounted router. Adjust the fence to center the bit in the ¾" stock. Now set a stopblock so when the body is pushed across the bit, it stops at the indicated mark on the pattern [**Photo A**]. Rout the grooves on both sides of the body.



With a stopblock and feather board in place, cut a groove in each side of the body (A). Slide your hand on top of the fence for safety.

5 Using a 45° chamfer bit in your table-mounted router, cut a 1/16" chamfer around the front and back faces of the body (A) [**Photo B**]. (You'll use the same setup to chamfer the base [C] shortly.) Remove the pattern, and finish-sand the body to 220 grit.

6 Cut two ¼×1¾×3¼" blanks for the wings (B). Make two copies of the **Wing Pattern** and adhere one to each blank, with the long, straight edge of the pattern flush with the edge of the blank. Bandsaw or scrollsaw the wings to shape, then sand away any saw marks on the cut edges. Remove the pattern, and finish-sand the wings to 220 grit.

Now make the base

1 Cut a ¾×2¼×10" blank for the base (C). Resaw the blank to ⅝" thick. (We used a tablesaw.) Then crosscut the blank to 6".

continued on page 76



Optional Micro-Adjuster

An Entirely New ROUT.

Unlike conventional router tables, our all new **Precision Router Table** utilizes a self-squaring tablesaw inspired fence to dramatically improve the way you work. Because the fence always moves parallel to the miter slot, even the most minor adjustment made on the fence's scale translates perfectly to the bit. It's the kind of innovation you've come to expect from Kreg, and we're confident it will make all the difference in your shop.

Visit us online to watch a video of this product in action.

Self-Squaring Fence



Steel Reinforced MDF Top

Built-In Vertical Jointer

Kreg®

www.kregtool.com | 800.447.8638

Circle No. 802

Breathe Easier with a One Stop Dust Collection Solution

With 20 years experience and a superior product line, the experts at Penn State Industries will provide you effective solutions for a cleaner shop.



BEST in class Cyclone Filtration 452-700 sq. ft. at 1/2-micron capturing 99.9% of particles.

FREE Ductwork Plan

Call Bill at 1-800-377-7297 x16 to help you plan the best solution for your shop or CNC applications. Mention this ad for information on how to get a FREE ductwork plan and a FREE catalog.

TEMPEST ™ Cyclones
- ▲ 2.5HP - 1450CFM - $995
- ▲ 3.5HP - 1700CFM - $1125
- ▲ 5.0HP - 1800CFM - $1395

Premium Ductwork
- ▲ Pipe for maximum airflow
- ▲ Fittings and hoods for most applications

Ductwork Planning Service
- ▲ An accurate layout of your shop to save you hours of planning

More Collection Solutions
- ▲ High performance bag-style collectors, air cleaners and portable collectors ideal for any size home shop

Circle No. 2045

Penn State Industries

1-800-377-7297 • www.pennstateind.com/nodustwm

Contrasting species highlight the clock's shapely figure. Here we chose spalted maple and walnut for a blond-over-brown variation.

Use a starter pin and a push pad for safety when freehand routing the chamfers on the front and back of the body (A).

With the base aligned to cut the mortises, lock the drill-press fence in place, and drill overlapping holes with a Forstner bit.



2 Photocopy the **Base Pattern** and adhere it, centered, to the blank.

3 To form the mortises in the base (C) to receive the wings (B), chuck a ¼" bit in your drill press. We prefer the flat bottoms produced by a Forstner bit, but a brad-point bit also will work. Adjust your drill-press fence to center the bit over the marked mortises on the pattern.

4 To make the mortises, drill overlapping holes ¼" deep in the base (C) where shown on the pattern [**Photo C**]. Use a chisel to clean up the edges and square the corners of the mortises. Bandsaw or scrollsaw the base to shape.

5 Rout the 1⁄16" chamfer on the bottom of the base (C) using a starter pin, as you did earlier. Change to a ¼" round-over bit, leave the starter pin in place, and rout the top of the base. Remove the pattern, and finish-sand to 220 grit.

Assemble and finish

1 Apply glue to the grooves in the body (A), and insert the wings (B). To hold the parts in position, use masking tape as a clamp. Next apply glue to the mortises in the base (C), insert the body and wing assembly (A/B) into the base, and clamp.

2 After the glue dries, apply a clear finish. (We sprayed on three coats of aerosol satin lacquer, sanding between coats with a 320-grit sanding sponge.)

3 Install the clock movement, put the clock on your desk, and enjoy watching time pass.

Written by **Jeff Mertz** with **Kevin Boyle**
Project design: **Matt Seiler**
Illustrations: **Roxanne LeMoine**; **Lorna Johnson**

Cutting Diagram

¾ x 3½ x 12" Lacewood (.33 bd. ft.)

¾ x 2¼ x 10" Maple (.21 bd. ft.)
*Plane or resaw to the thicknesses listed in the Materials List.

Materials List

Part		FINISHED SIZE T	W	L	Matl.	Qty.
A*	body	¾"	3¼"	2¾"	C	1
B*	wings	¼"	1 11⁄16"	2⅞"	C	2
C*	base	⅝"	2"	5½"	C	1

*Parts initially cut oversize. See the instructions.

Materials key: C–choice of contrasting woods, such as curly maple and lacewood, curly maple and walnut, ash and cherry, or curly maple and ash.
Supplies: Spray adhesive.
Bits: ¼" and 1⅜" Forstner bits; 45° chamfer, ¼" round-over, and ¼" straight router bits.

Source

Mini quartz movement: White Arabic Dial with Chrome Bezel no. 15267, $7.49 ea. from Klockit (800-556-2548, klockit.com).

The new FEIN MultiMaster: The universal tool for remodeling and renovation.

One tool, a few attachments... Thousands of projects!

40% more powerful! The new FEIN MultiMaster is more versatile and powerful than ever. Replace windows, flooring, and tile; repair furniture, refinish molding; work on cars, boats... the list is endless! The MultiMaster oscillates for smooth running. A wide range of accessories are available.

MADE IN GERMANY

NEW QuickIN accessory changing! Change accessories quickly and easily...without tools!

NEW star arbor mounting system locks accessories tightly in place.

For more information, a free brochure or to see the complete line of MultiMasters at a dealer near you, call **1-800-441-9878** or visit us at **www.feinus.com**.

Look for the new FEIN infomercial starring Jodi Marks and Pat Simpson of HGTV!

Circle No. 1520

Create Beautiful Pens in Minutes

If you're looking for an easy, relaxing and rewarding woodworking hobby that won't break the bank – then pen making is for you. Impress your friends and family with a beautiful hand turned pen. Great for gift giving or sales potential.

Get started now with an all-inclusive Super Pen Making Starter Set.

Save up to $135

Starter Set without lathe	Starter Set with Turncrafter Pro 1/2 HP Variable Speed Midi Lathe	Starter Set with Turncrafter Pro 1/2 HP Midi Lathe
Item #: PK073SPECX	Item #: PK073SPECV	Item #: PK073SPEC
PRICE $299.95	PRICE $575.00	PRICE $485.00
REG. ~~$384.95~~	REG. ~~$695.00~~	REG. ~~$620.00~~
You Save $85	*You Save $120*	*You Save $135*

SPECIAL OFFER
WOOD® Readers
Get an additional $15 off on any of these sets
Use coupon code: WMSTART15
Expires: 11/31/08

The result . . . an elegant "Slimline" pen.

Starter Set includes:

Circle No. 2151

Penn State Industries

1-800-377-7297 • www.pennstateind.com/getstarted

Ask WOOD

Answers to your questions from letters, e-mails, and WOOD Online®

HAVE A QUESTION?

For an answer to your woodworking question, write to **ASK WOOD, 1716 Locust St., LS-221, Des Moines, IA 50309-3023,** or e-mail us at **askwood@woodmagazine.com**. For immediate feedback from your fellow woodworkers, post your questions on one of our woodworking forums at **woodmagazine.com/forums**.

Is my benchtop saw biting off more than it can chew?

Q: I have a 1-hp benchtop tablesaw with a 40-tooth carbide-tipped blade. When I tried to rip a 2×4, I had to feed the wood slowly to keep the saw from bogging down and tripping the breaker. But the slow feed rate made the wood smoke. Am I feeding this saw more than it can handle?

—Scott Taylor, Goddard, Kan.

A: There's no reason that a properly tuned and outfitted benchtop tablesaw can't easily rip 2×4s, Scott. You can do a few things to improve your saw's performance, however. First, trade out the 40-tooth blade for a 24-tooth, thin-kerf blade made for ripping. Fewer teeth make for easier chip ejection and cooler cuts. A thinner blade removes less wood, putting less strain on the motor and helping it maintain its rpm. With the blade installed, adjust it and the fence parallel to the miter slot. Burning often can be traced to a misaligned blade or fence pinching the wood.

Finally, leave that splitter and blade guard installed, as shown *right*. Pine 2×4s may have internal stresses that cause them to pinch the blade during rip cuts—exactly the problem your splitter was meant to cure.

A splitter keeps stress-prone 2×4s from binding up the tablesaw blade, preventing burning, eliminating dangerous kickbacks, and keeping the motor from bogging down.

Peachtree Woodworking Supply Inc.™
"Your One Stop Supply Shop"®

Clamps, Sawblades, Router Bits, Abrasives, Books, Videos and More.
Find the brand names you're looking for at

ptreeusa.com

Over 5000 woodworking items! Orders ship within 24 hours.

Circle No. 654

BESSEY freud IRWIN QUICK-GRIP NORTON Titebond III Kreg MIRKA WOODSTOCK SHOPFOX OLSON Peachtree Woodworking

Peachtree Woodworking Supply Inc.™, 3250 Oakcliff Industrial Street, Atlanta GA, 30340 - Call Toll Free: 1-888-512-9069

Confused by lookalikes leopardwood and lacewood

Q: The July 2008 issue of *WOOD*® magazine shows leopardwood on page 65 and lacewood on page 44. They look similar to me, and I've seen each labeled both ways in hardwood stores. If they are different species, how do I tell them apart?

—Roy Galbreath, Diamond, Ill.

A: Leopardwood and lacewood are indeed two distinct species, Roy, though people (even hardwood dealers) often confuse them with one another. Use these characteristics to tell the two apart: Both leopardwood, *below*, and lacewood, *bottom*, display flecks caused by rays that bisect the growth rings. But leopardwood's flecks tend to be splashy and round (like a leopard's spots), where lacewood's appear wispy, coming to a point on both ends. With a pinkish-brown to chocolate-brown color range, leopardwood weighs in as the denser and darker of the two woods. Lacewood has a light-pink to light-brown color and a sheen that makes it appear to glow.



Leopardwood

Lacewood

continued on page 80

Warm to the comfort of radiant heat

RADIANT Floor Company

Efficient, Quiet, Reliable

It's never been easier to do it yourself

compatible with any fuel source:
GAS, PROPANE
SOLAR, OIL, WOOD
ELECTRIC,
GEOTHERMAL

VISIT OUR WEBSITE
CALL FOR A FREE QUOTE
www.radiantcompany.com
Barton, Vermont
(toll free) 1.866.WARM-TOES (927.6863)

Circle No. 1301

WoodWorks Show

Where woodworking comes alive!

2008-2009 Show Schedule

York, PA	Novi, MI	West Springfield, MA	Show Hours
York Expo Center	Rock Financial Showplace	Eastern States Exposition	Friday 3pm-9pm
November 7-9, 2008	December 12-14, 2008	January 9-11, 2009	Saturday 10am-5pm
			Sunday 10am-3pm

Buy your tickets online and save!

For complete details about each show, or to receive show discounts, call **toll-free 866-749-4988**, or visit:

www.woodworksevents.com

Can't make the shows? At the beginning of 2009 WOODMagazine.com will have online videos of the most popular seminars. Stay tuned for more details.

At each show, make sure to stop by the SawDust Café®, sponsored by *WOOD*® Magazine.

- Chat with fellow woodworkers
- Enter your projects in daily woodworking competitions
- Learn about woodworking clubs and schools in your area

SawDust Café

NEW MODEL 50-220R
10" LEFT-TILT "HYBRID" SAW

New design includes a combination riving style splitter / blade guard assembly and a separate European style riving knife.



Unique digital display for blade angle.
44" x 27" cast-iron table with extension wings.
Ruggedly built saw carriage with solid cast-iron trunnions.
Large stop switch.
Dual direct dust collection includes built-in blade shroud connected to a standard 4" dust outlet.
Powerful 2 HP motor.

3 Fence options including:
- *New Excalibur Aluminum T-fence system (50-220R M1)*
- *FS6 T26 General T-fence system (50-220RC M1)*
- *FS6 T52 General T-Fence system (50-220RCL M1 – not shown)*

For current promotions, complete product info and a list of dealers near you:
WWW.GENERAL.CA

Circle No. 1552

WOODCRAFT®

celebrating 80 years WOODCRAFT

For A Free Catalog Or To Find Your Local Woodcraft Store, Visit www.woodcraft.com Or Call 800-225-1153.

Cocobolo, zebrawood, or purpleheart pens and pencils? No problems! With your wood and our premium quality mechanisms, you can easily make customized pens and pencils on your lathe.

Wood Pen Blank Assortments

We have assembled a giant assortment of domestic and exotic wood and over 150 acrylic pen and pencil blanks!

Woodcraft Pens and Pencil Kits

Pen making has become a popular, and profitable, hobby among woodworkers. Whether you make them as gifts or as products to sell, your friends and customers will appreciate the long lasting durability of Woodcraft's Pen and Pencil mechanisms. Assembly is fast and easy, all of our kits include detailed instructions that cover setup, turning, assembly, and finishing. Your success is practically guaranteed!

Dept: C8WI11R

QUALITY WOODWORKING TOOLS SUPPLIES • ADVICE®

Circle No. 700

Ask WOOD

Watermarked walnut woes

Q: A recent basement flood left a dark "waterline" on some walnut frames that were waiting to be finished. Is there a way to erase the blemish?

—Beth Krehbiel, Deer Creek, Okla.

A: If there is no damage, such as swelling or spreading joints, you might have gotten lucky, Beth. Try this: Re-sand all the surfaces through 80, 120, 180, and 220 grit, paying special attention to the watermarked areas. This should remove most of the surface stain and knock down any raised fibers. Then, wipe on a generous coating of boiled linseed oil. Allow it to penetrate for 5–10 minutes before wiping it off with a paper towel. For dark woods, like your walnut, the penetrating finish blends any remaining stains into the wood grain.

SINCE 1972
Hartville Tool
WOODWORKING

Special Limited Time Offer!

WORKSHARP WS3000 with Bonus Leather Hone Kit $29.99 Value FREE!

Only! $199.98
H21755

Coupon Code: WM0811
Offer Expires 12/31/08

FREE! GROUND SHIPPING
On Orders Over $75
(Lower 48 States)

FREE! Leather Hone Kit

Order Online or Call Us:
FREE Woodworking Catalog!

hartvilletool.com
800-345-2396

Circle No. 596

OSBORNE
Wood Products, Inc.

www.osbornewood.com

Osborne Wood Products, Inc. introduces Mission products that feature the clean lines and classic design indicative of the Mission style.

4618 GA Highway 123 N
Toccoa GA 30577

Order Line: 800.849.8876
For a Catalog: 800.746.3233
info@osbornewood.com

Circle No. 1849

NEW! AND IMPROVED

JDS Cyclone

For more information call:
800.480.7269

With more performance and more features JDS is raising the bar for 2-stage Cyclone Dust Collection!

Portability:
The JDS Cyclones have a base with wheels that allow the cyclones to be transported anywhere!

Step 1 Lift Drum Lever

Step 2 Remove Drum

Quick Connect Drum Lever:
Disposing of collected waste is quick and easy! Just lift up the drum lever and slide the steel drum out. Return the drum and lock down the lever, its that easy!

Self Cleaning Canister:
The JDS Cyclones are equipped with a 1 micron canister that is self cleaning. Every time the unit is turned off a signal is sent to the canister motor that activates cleaning "flappers" inside the canister!

More Power:
The unique "Turbo-Fan" impeller from JDS now provides more CFM and greater performance at high levels of static pressure.

JDS company

www.jdstools.com

Circle No. 1974

Forrest Blades

Experienced woodworkers know that Forrest blades are ideal for remodeling high-end kitchens and baths.

Forrest blades deliver smooth, quiet cuts *without* splintering, scratching, or tearouts. Our proprietary manufacturing process, hand straightening, and unique grade of C-4 micrograin carbide are perfect for cabinets, countertops, and flooring. In fact, independent tests rate us #1 for rip cuts and crosscuts.

"Your blades are without question the best by miles, and I have tried them all."
Bob Jensen, Fridley, MN

Order from any Forrest dealer or retailer, online, or by calling directly. Our blades are manufactured in the U.S.A. and backed by our *30-day, money-back guarantee*.

Forrest Quality Shows

Duraline Hi-AT—Great for cutting two-sided veneers and low pressure laminates.

Woodworker II—Best rated, all-purpose blade for rips and crosscuts.

FORREST
The First Choice of Serious Woodworkers Since 1946

www.ForrestBlades.com
1-800-733-7111
(In NJ, call 973-473-5236)

© 2007 Forrest Manufacturing Code WM

Circle No. 205

WOODCRAFT®

Your Best Work Starts With Us!

With over 15,000 of the finest woodworking tools in the world, Woodcraft can help you work more efficiently and skillfully than ever. Call for your FREE copy today.

FREE Tool Catalog!

1-800-542-9115
woodcraft.com

406 Airport Industrial Park Road
P.O. Box 1686
Parkersburg, WV 26102-1686

Dept: C08WI11Q

Circle No. 700

SOMMERFELD'S TOOLS *For Wood*

ENTER TO WIN TODAY
Professional Woodworking System!

Enter to WIN $400.00
of Sommerfeld's Tools
The One and Only place for high quality, innovative woodworking tools!

Call or go online to enter for your chance to WIN the a set of professional woodworking tools... This set is great for weekend projects! You'll win our six-piece Cabinetmaking Set, New Easy Set height adjustment gauge and we'll even throw in all seven of Marc Sommerfeld's DVDs! These DVD's show you the fast, simple way to do a multitude of jobs!

A winner will be selected by random drawing from all eligible entries received by the 30th of November 2008. No Purchase Necessary. Void where prohibited.

6 Piece Cabinetmaking Set

Easy Set

7 Instructional DVD's

GO ONLINE TO ENTER!

To Enter or for a FREE Catalog call today...

Source Code WM98

Toll Free 888-228-9268
Visit us on the web... www.SOMMERFELDTOOLS.com

Circle No. 284

Infinite Engraving and Cutting Possibilities
for as little as $7,995

- Create custom inlays
- Add accents to cabinets and drawer fronts
- Laser cut prototypes, jigs and templates
- Engrave personalized designs for customers

Systems starting at $7,995!

20 Years in 08

Contact us NOW to receive your free informational kit which includes:

- Epilog's Full Brochure
- A CD Demo featuring our machines in action
- Engraved and cut samples
- A laser engraving wood workers guide.

EPILOG LASER

Epilog Laser • 1.888.437.4564 • sales@epiloglaser.com
www.epiloglaser.com/bhg.htm

Circle No. 1515

A TRADITION OF ELEGANCE

www.osbornewood.com

Osborne Wood Products, Inc. features the Traditional Elegance collection. These timeless product styles highlight the dignity of design that has remained classic through the centuries. To see the complete selection of wood components available visit: www.osbornewood.com.

Graceful, yet bold...

with an air of distinction...

4618 GA Highway 123 N
Toccoa GA 30577
Order Line: 800.849.8876
For a Catalog: 800.746.3233
info@osbornewood.com

Circle No. 1851

www.toolmarts.com 1-800-735-8665

Air Locker 18 Ga Brad Nailer
F630 Shoots upto 1-1/4"
B630 Shoots upto 2"
F630 $32.99 B630 $39.99

Air Locker $39.99
22 Ga Upholstery Stapler U630
U630 Shoots between 1/4" to 5/8" Staples

VARIOUS SIZES OF BRADS & STAPLES ARE ALSO AVAILABLE

Air Locker $59.99
23 Ga Micro Pin Nailer P630
P630 Shoots between 1/2" to 1-3/16" 23Ga Pins

Air Locker
Maintenance Kit PK630M
$9.99

Comes in a Rugged Aluminum Case

BUY AS A KIT AND GET 5 PACKS OF PINS FOR $ 69.99

Fein Top MultiMaster FMM 250Q
$399.99 FREE Shipping

E-Cut Universal 6-35-02-152-02-0
3 Packs
$69.99

TM P003 Multipurpose
$4.99
Get ToolmartsToolbag with purchase of these Fein Products on a Special Price!

WE HAVE THE LARGEST SELECTION OF FEIN TOOLS & ACCESSORIES ON THE WEB

JET Cabinet Saw PM2000
$50 Rebate 1792000K
$2699.99 FREE Shipping

JET ProShop 708480K
$50 Rebate 10" 1-1/2HP 30" SW
$899.99

Place Order over $2000 of Jet/Powermatic products and get FREE Shipping

LARGEST SELECTION OF JET / POWERMATIC TOOLS ONLINE

OASIS MACHINERY Miter Saw Stand
BST07 $119.99
5-1/2 ft beam Support upto 16 ft of material
BST08 $99.99
4 ft beam Support upto 10 ft of material

OASIS MACHINERY Miter Saw Work Station
BST11
$159.99

VISIT OUR ONLINE STORE FOR NAILERS, SANDERS, SAWS, PLANERS, DUST COLLECTORS & ACCESSORIES

Circle No. 1770

No, It's Not a Planer

The CarveWright Woodworking System is a revolution in computer controlled carving, bringing unimagined possibilities to the home shop. For more information and projects visit www.carvewright.com.

CARVEWRIGHT™ WOODWORKING SYSTEM

Woodworking for the 21st Century

Circle No. 1463

Dovetails

Made Easy with Leigh Joinery Jigs

Through | Single Pass Half-Blind | Variably Spaced Half-Blind | Sliding

24" Leigh D4R | 24" Leigh Super24

18" Leigh Super18 | 12" Leigh Super12

See the Videos at leighjigs.com

LEIGH Leigh Router Joinery Jigs

leighjigs.com 800-663-8932

Make Money In Metal Art

The PlasmaCAM machine makes it easy for you to cut intricate metal shapes that really enhance your wood projects. Call today for your FREE demo video to see what you can do with this amazing machine!

"We used to cut everything by hand and had a lot of trouble. Now our PlasmaCAM does it all, attaining levels of production not thought possible before. It's run 40-50 hours a week for the past three years. It attains incredible detail, is very easy and cost efficient to operate, and requires little maintenance. The bottom line is: ***this machine makes me money!***"

-Jon, Restaurant Lighting & Fixtures

Ask about our exclusive Art Discs with ready-to-cut artwork!

(719) 676-2700 • www.plasmacam.com
PO Box 19818 • Colorado City, CO 81019

Plasma CAM Inc.

Circle No. 1641

WOODCRAFT®

For more information call 800 344-3348 or e-mail: bill_carroll@woodcraft.com

"When I think about owning my own business ...

When woodworking is your passion, and owning your own business is your goal, Woodcraft can help you take your skill and expertise to the retail level.

... I think of Woodcraft"

Bill Carroll CFE
Director Of Franchising

I'm Bill Carroll, call me & I'll show you how you can own a Woodcraft franchise

1177 Rosemar Road
P.O. Box 245
Parkersburg, WV 26102-0245

F08WI11Q

RETAIL FRANCHISE OPPORTUNITIES™

Circle No. 924

We have the hardware and supplies you need!

Request a FREE catalog - Promotion #822

Woodworker's Hardware
woodworkershardware.com
or 1-800-383-0130

Circle No. 713

Put a ShopBot Buddy CNC to Work for You

The ShopBot Buddy is the "ultimate workshop tool," allowing you to create a huge variety of projects and components, from simple 2D shapes to intricate relief carvings. American built and engineered, the Buddy is a professional-grade CNC tool with the performance, size and price to fit your needs, space and budget.

With complete systems for less than $6,000, the Buddy is the perfect tool for many applications, whether you need a flexible CNC machine to add to your manufacturing operation or you're looking for a way to take a hobby or small business to a new level of quality or profitability.

Buddy is available in two sizes - 24"x32" and 24"x48" - and the optional PowerStick attachment extends the length up to 12 feet, so the system can grow as your needs change. Plus, it's fully mobile, so it's never in the way when you're not using it.

Buddy 32

Buddy 48

Call or visit us online to learn how you can put Buddy to work in your shop.

The ShopBot Jamboree is coming to Austin, TX!
Join us October 15-17 at the Travis Co. Fairgrounds.

ShopBot®
www.shopbottools.com 888-680-4466
What would you like to make today?

Circle No. 1714

PRECISION MILLED TEETH | INDUCTION HARDENED
FLEXBACK CONSTRUCTION | MATCH TOOTH WELDED

"THE BEST BLADE I'VE EVER USED."

carter classic
bandsaw upgrades

AccuRight™ Bandsaw Blades

A new standard
precision
durability.

the company
that has been making
bandsaws better
for over 75 years.

Buy three bandsaw blades.
Get FREE "Bandsaw Tuning" DVD.
($14.95 Value)

carter products

Circle No. 176

www.carterproducts.com | Toll-Free 888.622.7837

FREE SHIPPING**

You'd pay hundreds more if you purchased these router bits separately!

EXTREMELY LIMITED QUANTITIES

BIGGER & BETTER 35 PIECE SET

A dream buy for wood workers... 35 high-quality router bits for just $1.14 each! This incredible set has a huge assortment of bits that let you V-groove, flush trim, chamfer, dovetail and much more with professional results every time. Bits have 1/4" shank and are solid carbide or carbide tipped for years of dependable use and clean cuts with a working error of less than 0.2 mm. Bits come in a wooden storage case with labels to keep them clean and organized.

Compare At: $310.09
YOUR PRICE $39.99 FREE Ship ~~$7.50~~
Item No. UB49-56652

Bore clean, deep holes in soft or hard wood with virtually no effort!

16 PIECE SET — EASTERN STEEL

For running electrical wires through floor joists, assembling 2x4 wood playsets for the kids and other tasks, these auger bits make the job a snap! Put some excitement into your next "boring" job with this tradesman's quality 16-pc. set. Each bit is forged from #45 carbon steel and has a heat-treated to HRC47 hardness tip, flutes ground behind the lands to pull chips up for fast, clean cutting and a polished finish. Includes 3/8", 1/2", 5/8", 3/4", 7/8" and 1" bits in both 4-3/4" and 8" lengths and 1/2", 5/8" and 3/4" bits in 16" length. Bits come in protective case.

COMMERCIAL QUALITY FOR INSTITUTIONAL & INDUSTRIAL USE

Compare At: $154.99
YOUR PRICE $29.99 FREE Ship ~~$7.50~~
Item No. UB49-56447
SPECIAL BUY LIMITED QUANTITIES

The next energy crisis could strike at any time! Will you be ready?

Price breakthrough! This 1000W generator is priced under 130* - that's $579 less than competing models! When the power goes out or you're camping miles away from the nearest outlet, this generator delivers the juice you need. The 2HP air cooled two-stroke engine and brushless generator deliver the power you need to run lights, power tools, electric appliances and more. Features a 120V AC outlet with circuit breaker, 12V DC outlet, a DC trickle charger for charging your car battery and eight hours of run time per tank of gas at half load. Also has a hushed design for reduced noise. 15" x 13" x 14". Not available in CA. Outdoor use only (see manual).

Power on demand for:
- Blackouts
- Brownouts
- Storm outages
- Camping
- Worksites
- More!

1000 WATTS

UP TO 8 HOURS OF RUN TIME

PUBLIC NOTICE: Natural disasters & power problems strike with little or no notice. So plan ahead & don't get caught in the dark this year. Our limited allocations of generators will sell out quickly, so reserve yours today to avoid disappointment!

Compare At: $709.00
WAS: ~~$299.99~~
Item No. UB49-50557
Ship ~~$34.95~~ $17.95

PRICE BREAKTHROUGH
NOW ONLY! $129.99*

GAS POWERED

*Price reflects $20.00 mail-in rebate. Price before rebate is $149.99. Rebate expires 12/31/08.

At last! A chain saw that requires no costly gas or cumbersome electric cords!

TORNADO by KINETIC RESEARCH

Tornado Tools™ 18V cordless chain saw offers unparalleled convenience without compromising performance! Need to clean up branches after a thunderstorm, trim a tree or cut some firewood while camping? This cordless chain saw will get the job done quickly and safely. Its 18V motor and rechargeable NiCad battery power the chain at 576 FPM chain speed to zip through brancheswith amazing ease. Also has double safety switch to help prevent accidents, safety nose guard design for anti-kick back and a lightweight outdoor tough design that weighs just 9 lbs. Battery charger included. Additional batteries available. Ask your operator for details. 23-1/2" x 6-1/2" x 6-3/4".

RECHARGEABLE

Compare At: $269.99
YOUR PRICE $79.99 $3.95 Ship ~~$7.95~~
No. UB49-51958
SPECIAL BUY LIMITED QUANTITIES

The look of yesterday with the technology & sound quality of today — plays LPs, 45s, 78, cassettes, CDs & even iPods® or MP3 players!

Anders Nicholson's™ nostalgic home stereo combines yesterday's classic look with today's advanced technology! Bring out those old LPs and singles ... and don't forget your favorite CDs and cassettes. This unit plays them all! Whether you're listening to the radio or your favorite CD, this stereo unit fills the room with terrific sound. Quality crafted throughout, it features a turntable that plays 33-1/3, 45, and 78 records, an aux input for iPod* or other MP3 player, front loading full-function CD player, AM/FM stereo radio and LCDdisplay. Comes in oak finish wood case (shown), also available in cherry and measures 17-3/4"x13-1/4"x9-1/2".

Anders Nicholson

SOLID WOOD

TURNTABLE 3SPEED

AM/FM

Classic Nostalgia Detailing

Compare At: $249.00
WAS: ~~$149.99~~
Oak No. UB49-40008
Cherry No. UB49-40009
NOW ONLY! $99.99/each
Ship ~~$22.95~~ $11.95

EXTREMELY LIMITED QUANTITIES

*iPod, iPod mini, iPhone and iPod photo are trademarks of Apple Inc., register in the U.S. and other countries.

Discover a pirate's treasure, a cache of gold coins, jewelry and valuable relics from days gone by!

GREAT GIFT IDEA

MSR: $160.00
WAS: ~~$69.99~~
NOW ONLY $49.99 FREE Ship ~~$7.50~~
No. UB49-21932

Famous Trails

Get a pair of solar powered coach post lanterns for less than you'd expect to pay for one!

SOLAR POWERED

Compare At: $77.00
SET OF 2 ONLY $29.99 FREE
No. UB49-63420 Ship ~~$7.50~~

Strap it on your wrist and help disarm the silent killer!

St. John's MEDICAL

Compare At: $109.95
ONLY $19.99 FREE Ship ~~$7.50~~
No. UB49-97272

1 TOUCH Auto-Inflation AND Auto Deflation

VISA MasterCard AMERICAN EXPRESS DISCOVER NETWORK

Call Toll-Free,
24 hours a day,
7 days a week

National Headquarters:
8085 Century Blvd.
Chaska, MN 55318

CA RESIDENTS WARNING: The products offered for sale in this ad may contain chemicals, including lead, known to the state of California to cause cancer and birth defects or other reproductive harm.

HEARTLAND AMERICA

The Best Values Direct to you from the Heartland!

**Some limitations may apply. Ask your operator for details.
Overweight items have dramatically reduced shipping.

1-800-229-2901

FREE SHIPPING**

Receive FREE Shipping On Your 1st Online Order!
Enter Code: UB49UB49
www.HEARTLANDAMERICA.com

Woodworking Plans!

Make This President Coin Collection!
Order Plan #W3249

FREE color catalog features plans for over 1,000 different projects. Mention Offer #1200

Meisel Hardware Specialties P.O. Box 70 Mound, MN 55364

Call: 1-800-441-9870 Or visit our web site

www.meiselwoodhobby.com

Circle No. 401

STOP BUYING LUMBER!

Use your chain saw and Granberg's mill to create perfect slabs of wood

1. MKIII Attachment
Easily Mounts on Bar
Sizes from 24" to 56"

2. MINI MILL Attachment
Great partner for MKIII
Ideal for edging, and reducing log diameters

3. SMALL LOG Attachment
Add to chain saw and start making lumber!

WWW.GRANBERG.COM
CALL NOW FOR FREE CATALOG! 800-233-6499
50 Years of Customer Satisfaction!

Circle No. 1558

AMERICAN STEEL SPAN®

Great for Your Workshop
Ideal for Your Garage
Made in the USA



Designed with Protection in Mind
SOLID • SECURE • SAFE

800-891-6733

www.steelspan.com ext. 1118

Circle No. 1064

Walking the talk.

Hand tools for the serious woodworker

TOOLS FOR WORKING WOOD

800.426.4613
32 33rd St. Bklyn, NY 11232
www.toolsforworkingwood

Circle No. 830

MOISTURE METER

LOW-COST, HIGH-PERFORMANCE

- mini-Ligno E/D -
Proven accuracy and quality at an affordable price. Designed for wood-workers.

MEMBER TESTED HANDYMAN RECOMMENDED

sales@lignomat.com
www.lignomat.com
503-257-8957

LIGNOMAT USA : 800-227-2105

Circle No. 2013

Make Time!

Create your own wooden gear clock!

Need just the pattern?
Or the complete kit?
Build it *YOUR* way!

Wooden-Gear-Clocks.com
clocks, kits, and do-it-yourself patterns

(715) 955-4104

www.wooden-gear-clocks.com

Tools for the Art of Woodcarving

Made in USA



Woodcarvings by David Bennett

Flexcut® CARVING TOOLS

www.Flexcut.com

Circle No. 195

TILTBOX°

Pat. Pend.

Accurately reads relative angles



Magnets on the sides cling to metal surfaces.

Also gauges actual level

THE BEALL TOOL CO.

1-800-331-4718 Fax 1-740-345-5880
www.bealltool.com Dpt. WM

Circle No. 558

WORKSHOPS & GARAGES

Call Now! Limited Factory Specials!

MIRACLETRUSS®
STRENGTH | VALUE | STYLE

866-748-9921 • miracletruss.com

HARDWOODS

Lumber • Veneer • Turning Stock

exoticwoods.net
800.423.2450
Wood Descriptions • Secure Online Ordering

WOODWORKERS Source

18115 N. Black Canyon Hwy. • Phoenix, AZ 85023
645 W. Elliott Rd. • Tempe, AZ 85284
3441 S. Palo Verde • Tucson, AZ 85713

Circle No. 869

Ezee-Feed

MANUFACTURING

INFEED/ OUTFEED SYSTEMS

SEE OUR REVIEW! FINE WOODWORKING MAGAZINE APRIL 2008

FOR YOUR WOOD SHOP!

WWW.EZEE-FEED.COM

Circle No. 1952

Knifemaking Made Easy!

Still Time For Gift Giving!

1-800-351-8900

Prestige Cutlery

High quality 440C surgical stainless blades satin finish, sharpened to an exceptional edge. Handles predrilled. Easy to complete with rivets, handle material, detailed instructions.

SS809 .....$99.95

Full Color 100 pg Catalog $5.00 Free w/order

JANTZ SUPPLY

309 WEST MAIN-DEPT WD - DAVIS OK 73030

www.knifemaking.com

Knife making kits, Metals, Exotic Woods, Horn, Pearl, Ivory, Abrasives, Polishing And Finishing Supplies, Precision Tools, Schrimshaw and Leathercraft Supplies, Books, Videos, And More!

Projects and Plans

Vendor Cart

Kit to build includes 2-24" **iron wheels** *that really work*, **axles** and step-by-step **plans**. Finished project measures 50"L x 25"W x 34"H. $76.80 plus S/H

ByeGone Workshop

888-279-3941 8-5 M-F EST

www.byegone.com

ROLL TOP DESK

Introducing the finest plan on the market today! Pages of directions and 36 by 48 CAD generated plan. Roll Top Desks are a part of American History and are a challenging project to build

FREE CATALOG

Plan #151

AMERICAN FURNITURE DESIGN
P.O. BOX 300100 ESCONDIDO, CA 92030
ROLL TOP DESK PLAN $21.95 +$6.00 S&H
760 743-6923
www.americanfurnituredsgn.com

Circle No. 336

Cut Your Own Wood!

With the MP-32 Sawmill you can cut your own lumber for a Home, Fence, Furniture, and much More!

Affordable, Powerful, & Reliable! Call for your FREE Catalog today!

Cook's Saw Mfg.,LLC

1-800-473-4804

www.cookssaw.com

Circle No. 1480

Create Dovetails Easier, Faster and Better than the Setup Time for Traditional Jigs.

Use the Dovetail Master with your mortiser or drill press to create randomly spaced & sized dovetail joints. Low noise & dust.



Made with the finest tool steel by one of the oldest manufacturers of mortising chisels!

For more details & demo, go to:

www.dovetailmaster.com

or call 215.297.9722

Dovetail Master, LLC

6837 Groveland Road

Pipersville, Pa. 18947

Circle No. 190

Adams Wood Products, Inc.™

FURNITURE COMPONENTS

STOCK ITEMS • NO MINIMUM CUSTOM COMPONENTS

FREE COLOR CATALOG

WE WILL MAKE PRODUCTION RUNS OF YOUR PART

NEW ITEMS

A0753-12 A0755-12 CORBELS

1032 Table Queen Anne Rams Head Claw/Ball

545 Bun 536 Bun 530 Bun 537 Bun A0914 A0921 A0924 ISLAND LEGS

P.O. Box 728, Dept.M60
Morristown, TN 37815-0728
Phone 423-587-2942 Fax 423-586-2188
www.adamswoodproducts.com
info@adamswoodproducts.com

Made in Tennessee by American Craftsmen

Circle No. 1831

Create A Classic

Baby Cradle Plan # M62 $15.95 Size 21x35x39

Build These Classics With Our Full Size Plans

more info at armorplans.com

Trim pack info at armorplans.com

Size 44 L x 27 H

Cycle Rocker Plan # M82 $18.50

VISA/MC 1-800-292-8296

Armor Box 445 E. Northport NY 11731

Circle No. 556

STEVE WALL LUMBER CO.

Quality Hardwoods and Woodworking machinery For The Craftsman and Educational Institutions

Ash	4/4	Select	$ 2.60		$ 94.00
Basswood	4/4	Select	$ 1.95		$ 80.00
Birch	4/4	Select	$ 3.55		$ 108.00
Butternut	4/4	1C	$ 2.95		$ 88.00
Cherry	4/4	Select	$ 4.90		$ 117.00
Hickory - Pecan	4/4	Select	$ 3.00		$ 100.00
Mahogany (Genuine)	4/4	Select	$ 4.70		$ 112.00
Maple (Hard)	4/4	Select	$ 3.45		$ 108.00
Maple (Soft)	4/4	Select	$ 2.50		$ 88.00
Poplar	4/4	Select	$ 1.80		$ 78.00
Red Oak	4/4	Select	$ 2.70		$ 96.00
Walnut	4/4	Select	$ 4.90		$ 115.00
White Oak	4/4	Select	$ 2.70		$ 96.00
Cedar (Aromatic Red)	4/4	1C+Btr.	$ 1.80		$ 78.00
Cypress	4/4	Select	$ 2.60		$ 90.00
White Pine	4/4	F.G.	$ 1.25		$ 70.00
Yellow Pine	4/4	Clear	$ 2.30		$ 82.00

UPS Specials

SEE OUR CATALOG ON THE WEB!

Above prices are for 100' quantities of kilndried rough lumber sold by the Bd. Ft. FOB Mayodan, NC. Call for quantity discounts. Other sizes and grades available.

Above prices are 20 bd. ft. bundles of clear kilndried lumber 3"-10" wide • 3'-5' long (Random widths & lengths) Surfaced 2 sides or rough. Delivered UPS prepaid in the Continental U.S.

OLIVER MACHINERY DEALER
HARDWOOD PLYWOOD
CUSTOM RAISED PANEL DOORS
CUSTOM PLANK HARDWOOD FLOORING
THIN CRAFTWOOD
EXOTIC LUMBER

STEVE H. WALL LUMBER CO.
BOX 287
MAYODAN, N.C. 27027
336-427-0637
1-800-633-4062
FAX 336-427-7588
Email: wood@walllumber.com
Website: www.walllumber.com

Send $1.00 For Lumber Catalog
Prices Subject to Change Without Notice

Circle No. 856

H L &M LAKELAND FLORIDA Est. 1998 863/646-8681
Hardwood Lumber & Millwork
Over 50 Species in stock
Plywoods - Turning Stock - Mouldings
Stair Parts - Architectural Millwork
Pull your own wood - Import & Domestic
Discounts on 100 and 300 bd ft of lumber
Rough cut or surfaced to your specs
Largest retail distributor in Florida
Hours of Operation M-F 9-5, Sat by appt

TURN TO PACKARD FOR QUALITY TURNING TOOLS AND SUPPLIES
Robert Sorby Patriot Chuck pictured above
Packard WOODWORKS INC.
1-800-683-8876
PACKARDWOODWORKS.COM
Circle No. 2143

Wireless Driveway Alarm

Alerts you when someone is walking or driving onto your property.
Free Literature
Dakota Alert
PO Box 130, Elk Point, SD 57025
605-356-2772 • www.dakotaalert.com
Circle No. 1129

The New Generation Of Bar Clamps

ALPHA CLAMP
• Clamp
• Hoist
• Jack
• Levels
• Rulers
• Adjustable 13" Throat
New!
Lowell Thomas Tool, Inc.
(406) 595-3416
www.AlphaClamps.com
Proudly Made In The USA!
Circle No. 806

LOGS TO LUMBER
Saw Logs Into Valuable Lumber

LT10 Ultra Compact... store in garage
Large Log Capacity 24" dia. by 11'
(Add optional 7' bed extension, no limit to the length)
7.0 HP Gas Engine
Large Capacity Sawmill ONLY $3,795*
SEVEN Other Sawmill Models to Choose from.
* U.S. Dollars. Prices subject to change without notice.
Wood-Mizer
800.553.0182
woodmizer.com/A917
Circle No. 1805

curiouswoods.com
SUPERIOR QUALITY HARDWOODS... FOR SUPERIOR RESULTS.
Save 5%
Curious Woods
on your next order.
Use promo code: WM5
at online checkout
Small to Truckload Quantity Orders • Secure Online and Phone Ordering • Personal Service Is Our Specialty!
Hand selected native and imported hardwoods, turning stock, burls, plywood, veneers, flooring and fine finishing oils.
VISIT OUR STORE - ROUTE 67, BALLSTON SPA, NY
Circle No. 842

Use Your Miter Gauge with Instant Precision!

$29.99
Proudly Made In America
MiterSet
ORDER NOW!
www.miterset.com
209-835-1626
Amazing Speed with 1/2° Increments
Circle No. 650

BUILD A BETTER BANDSAW
blades
guides
tires
tension devices
www.carterproducts.com
toll-free: 888.622.7837
Circle No. 1883

RP1176A
Hand-pierced metal panels. Easy to order! Standard ready-to-ship sizes or order custom sizes in 12 metals – your choice! Do-it-yourself materials, too! Download FREE Full Line Catalog online or order our printed catalog for $5.00.
www.piercedtin.com
email sales@piercedtin.com
Pierced Tin Design, Ltd. by Country Accents
1723 Scaife Road, Williamsport, PA 17701
Ph 570) 478-4127 9-5 EST • Fax 570) 478-2007
Circle No. 1845

DOWELMAX
PRECISION ENGINEERED MULTIPLE DOWEL JOINERY SYSTEM
GOLD MEDAL WINNER AT THE TOMORROW'S WORLD SCIENCE FAIR, LONDON, ENGLAND

This china cabinet was built with Dowelmax to create 60 precision hardwood dowel joints for the strongest and most accurate construction possible.
Our Unconditional Guarantee: Wood joints that are stronger than a mortise and tenon, and a joinery system that is more accurate and versatile than any other system on the market.

For more information, or to order call 1.877.986.9400
or log on to www.dowelmax.com
Circle No. 825

Supergrit® SANDPAPER
HOOK & LOOP DISCS

2" $18/100 3" $20/100
4½" or 5" 5 or 8 Holes $15.00/50
6" 6, 8, or 16 Holes $19.00/50
9" $1.50 ea 12" $2.50 ea

ABRALON® 6" Polishing Disc
Grits 360 to 4000
ABRANET® 5" & 6" Mesh Disc
Grits 80 to 600

BELTS—A.O. Resin

1 x 30	$.80	4 x 24	$1.30
1 x 42	$.85	4 x 36	$1.70
3 x 21	$.90	6 x 48	$3.70
3 x 24	$.90	6 x 89	$6.80

SHEETS—9" x 11". A.O.

50D, 80D	$15/50
120C. 150C	$24/100
180A, 220A	$22/100

ABRASIVE ROLLS

RED HILL CORP.
P.O. BOX 4234
GETTYSBURG, PA 17325
FREE 48 PAGE CATALOG
& incredible close-out sheets
(800) 822-4003
WWW.SUPERGRIT.COM
Circle No. 2065

KLOCKIT®
Leading Supplier To Woodworkers For 35 Years!

- Easy To Follow Plans
- Extensive Line Of Clock Components
- Easy To Assemble Kits
- Detailed Instructions With All Movements
- Industry Leading Technical Support!

Call Today For Your FREE Catalog!
1-800-556-2548
www.klockit.com
Dept. Code: WD1108
Circle No. 973

SUEDE-TEX SPRAY-ON FIBERS
Line boxes in seconds • No cutting
• No pasting...no skill required!
Available in 30 + colors
*Call for **FREE** brochure with sample of finish enclosed*

DONJER PRODUCTS
13142 Murphy Rd., Winnebago, IL 61088
800-336-6537 • 815-247-8775 *(outside the US)*
www.donjer.com
Circle No. 17

WOOD HEAT CLASSIC
Outdoor Wood Furnace
100% Wood Heat for Your Home, Water, Shop and More.

- Heat multiple buildings, pool, domestic water and more.
- Clean, safe and efficient heat.
- Adapts to new and existing heating systems.

Central Boiler
Find your nearest dealer at:
centralboiler.com
800-248-4681
©2008 Central Boiler ad4754
Circle No. 1105

INFINITY CUTTING TOOLS NEW
Professional Coping Sled
Item: COP-100

Sale $129.90
877-USA-BITS
Visit infinitytools.com for the video
Circle No. 235

U-BILD.COM

On-line catalog pictures hundreds of full-size woodworking plans at low prices, plus more than 30 downloadable plans. Indoor, outdoor, kids and holiday projects for all skill levels.
(800) 82-U-BILD
Circle No. 435

SELF-SET®
JOINTER / PLANER KNIFE



Effortless and Accurate Blade Changes Every Time
Precisely Located Stops on the SELF-SET Holder Ensure Perfect Set-Ups Every Time
DISPOZABLADE.com
800-557-8092
Circle No. 188

WALLBED KITS!
It's easy to build your own with our Tried and True Coil Spring Mechanism.

Starting at $289
COMPLETE BEDS ALSO AVAILABLE!
FACTORY DIRECT: 1-888-249-6188
WWW.DISAPPEARINGWALLBEDS.COM
Circle No. 1843

NEW!
TURN TIMBER INTO CASH!
Rugged, Hard-Working, Dependable

4 models to choose from including the NEW 2400 SUPER-PRO–King of them all!

- **Premium Quality** Accurate, stable 4-Post design
- **Proud Heritage** Serving America's Sawyers since 1929
- **Broad Selection** Weekend sawyer to full-time entrepreneur, there's a TimberKing mill for you
- **Best Consumer Protection** 30-Day FREE Trial, 2 & 5 Year Limited Warranties

FREE FACT KIT TIMBERKING SAWMILLS

CALL TOLL FREE 1-800-942-4406 EXT. ZB 05
TIMBERKING, Dept. ZB05, P.O. Box 34284, Kansas City, MO 64120
www.timberking.com

PHASE-A-MATIC™
PHASE CONVERTERS

CONVERTS 1-PHASE to 3-PHASE POWER!
1-800-962-6976
www.phase-a-matic.com
Circle No. 2052

WOODWORKING'S MUST-SEE TV

WOODVISION®
Woodworking Video Clips
FREE



More than 75 FREE How-to Videos!

woodmagazine.com/videos

Turn to Quality

Shop on-line @

www.hutproducts.com
1-800-547-5461

HUT® Products

Circle No. 2133

Wildwood DESIGNS INC.
2104 Beloit Ave
Janesville, WI 53546
1-800-470-9090

Excalibur BY GENERAL INTERNATIONAL
21" & 30 Precision Scroll Saws

Galaxy
Scroll Saw Blades & Pin Nailers

SIMPLY WILD ABOUT SCROLL SAWING

www.wildwooddesigns.com

Circle No. 1857

What's Ahead

A sneak peek inside the December/January 2008/2009 issue (on sale November 18)

FEATURED PROJECT

Cherry dresser

This beautiful six-drawer chest matches the pencil-post bed and nightstand in this issue (*pages 24–31* and *36–39*). You'll also find complete instructions for the dresser-top valet and wall mirror shown.

Basic-Built three-table set

You can't build matching tables any simpler than this. All three pieces have the same parts that vary only in length.

Wine holder

Keep up to six bottles of wine at hand for dining or entertaining with this countertop rack. Straightforward joinery and full-size patterns for most parts make it a cinch to build.

TOOL TEST

6" Stacked dado sets

Most of us cut dadoes less than an inch deep, so a 6"-diameter set will handle all our needs—and save money over an 8" set. Find the blades that best meet your needs.

Consistent color on plies and solid wood

There's more than one way to get even stain color on sheet-goods veneers and adjoining solid woods. We'll show you three of them.

Making woodworking your business

Interested in earning a living from your time in the shop? Learn the ins and outs from this former accountant who now turns bowls full-time.

Better Homes and Gardens® WOOD® magazine (ISSN-0743-894X) is published seven times a year in March, May, July, September, October, November, and December/January by Meredith Corporation, 1716 Locust St., Des Moines, IA 50309-3023. Periodicals postage paid at Des Moines, Iowa, and additional mailing offices. Better Homes and Gardens trademark registered in Canada and Australia. Marca Registrada en México. One-year subscription prices: U.S. and its possessions, $28; Canada, $41; other countries, $49. Canada Post Publications Mail Sales Product Agreement No. 40069223. Canadian BN 12348 2887 RT. Return undeliverable Canadian addresses to: Better Homes and Gardens WOOD magazine, 2835 Kew Drive, Windsor, ON, N8T 3B7. POSTMASTER: Send address changes to Better Homes and Gardens WOOD magazine, P.O. Box 37439, Boone, IA 50037-0439.

Get Stuck on Arrow® with the TR550™ Professional Hot Melt Glue Gun

Hot Melt Glue Guns are ***NOT*** all the same. The Professional TR550™ proves it. This feature packed Glue Gun is an important tool for every workshop.

- ***Full Grip Easy Squeeze Lever reduces painful 2-finger trigger fatigue***
- ***Solid State PTC Heating System quickly brings temperature to correct melt level and keeps it there for consistent bonding***
- ***Automatic Glue Control Check Valve***
- ***Automatic Clutch Mechanism prevents glue backup***
- ***Large Volume Melt Chamber***
- ***Commonsense Safety Stand/Drip Tray prevents surface damage***

The complete selection of Arrow® Hot Melt Glue Guns and special adhesives that permanently bond leather, metal, ceramics, and furniture, are available at Lumber Yards, Home Improvement Centers, Craft Shops, and Hardware Stores.

ARROW
PROFESSIONAL FASTENING
— SINCE 1929 —

Arrow Fastener Company, Inc.

USA	Tel: 201.843.6900	Fax: 201.843.3911
Canada	Tel: 514.321.3983	Fax: 514.321.9424
UK	Tel: 44.208.686.9180	Fax: 44.208.686.9197

www.arrowfastener.com

© 2008 Arrow Fastener Company, Inc.
Arrow® is a Registered Trademark of Arrow Fastener Co, Inc.

The facts are hard to ignore.

Titebond® III outperforms polyurethane glues.

As the leader in wood glues, we want you to know the truth about polyurethane glue and woodworking. A straightforward comparison between Titebond® III Ultimate Wood Glue and polyurethane glue tells the story.

Titebond® III is THE ultimate choice for bonding wood to wood. Period.

For more information and a detailed comparison, please visit www.titebond.com/TBIIIvsPolyurethane

Made in the USA

Proud Sponsor Of THE NEW YANKEE WORKSHOP

Circle No. 24